

SPEED TOUCH Pro

CLI Reference Guide

with Firewall DSL Router



Status Released

Change Note BD F aa 39813

Short Title CD-RG STFire CLI

All rights reserved. Passing on and copying of this document, use and communication of its contents not permitted without written authorization from Alcatel.

Contents

Preface	5
1 ADSL Commands	21
2 ATMF Commands	23
3 Bridge Commands	31
4 CIP Commands	47
5 Config Commands	57
6 DHCP Commands	63
7 DNS Commands	101
8 Firewall Commands	123
9 IP Commands	149
10 MER Commands	171
11 NAT Commands	181
12 Phonebook Commands	197
13 PPP Commands	207
14 PPTP Commands	225
15 Software Commands	233
16 SHDSL Commands	239
17 System Commands	245
18 TD Commands	253
Index	257

Preface

Welcome to the **Alcatel SpeedTouch™ Pro with Firewall Series Command Line Interface Reference Guide !**

This Reference Guide aims to give the fastidious user a concise, practical and easy to use document for configuring the **SpeedTouch™ Pro with Firewall** via its character based Command Line Interface.

Although the **SpeedTouch™ Pro with Firewall** Web interface is adequate enough for most users, access via the CLI may be still important for advanced and detailed configuration and troubleshooting.

This CLI Reference Guide covers the CLI commands of the following Alcatel DSL SpeedTouch products:

- ▶ **Alcatel SpeedTouch™ Pro with Firewall**
- ▶ **Alcatel SpeedTouch™ Pro with Firewall ISDN**
- ▶ **Alcatel SpeedTouch™ Pro with Firewall SHDSL**

The Reference Guide consists of three main parts:

▶ **Part 1 : CLI Navigation**

This part is meant to make the user familiar with the use and operation of the **SpeedTouch™ Pro with Firewall** CLI. Next to describing the various access methods to the CLI, this part will describe in brief some general manipulations to navigate through and to perform some operations on the CLI.

▶ **Part 2 : CLI Command Description**

This part forms the main part of this Reference Guide. Here all available CLI commands of the **SpeedTouch™ Pro with Firewall** products are alphabetically described per group selection.

Each command is described in a systematic manner:

- The full name of the CLI command (including the group selection)
- A short description of the CLI command, if needed completed by a description of the possible impact on the user and/or the **SpeedTouch™ Pro with Firewall**
- The syntax of the command with a description of each parameter
- An example to demonstrate the use of the CLI command
- A list of related CLI commands.

▶ **Part 3 : CLI Command Index**

This part allows the user to look up a command alphabetically in its incomplete form.

► **Trademarks**

The following trademarks are used in this document:

- Speed Touch™ is a trademark of the Alcatel Company
- Netscape® and Netscape Navigator® are registered trademarks of Netscape Communications Corporation
- Windows™ and Internet Explorer™ are trademarks of Microsoft Corporation
- Apple® and Mac®OS are registered trademarks of Apple Computer Inc.
- UNIX® is a registered trademark of UNIX System Laboratories, Inc.
- Ethernet™ is a trademark of Xerox Corporation.

Other products may be trademarks or registered trademarks of their respective manufacturers.

► **Updates**

Due to the continuous evolution of the Alcatel DSL technology, existing products are regularly upgraded. Alcatel documentation changes accordingly.

For more information on the newest technological changes and documents, please consult the Alcatel web site at following URL:

<http://www.alcatel.com>

<http://www.alcateldsl.com>

► **Directive**

Unless expressly and unambiguously approved by Alcatel, you may not:

- disassemble, de-compile, reverse engineer, trace or otherwise analyze the equipment, its content, operation, or functionality, or otherwise attempt to derive source code (or the underlying ideas, algorithms, structure or organization) from the equipment or from any other information provided by Alcatel, except to the extent that this restriction is expressly prohibited by local law;
- copy, rent, loan, re-sell, sublicense, or otherwise transfer or distribute the equipment to others;
- modify, adapt or create a derivative work of the equipment;
- remove from any copies of the equipment any product identification, copyright or other notices;
- disseminate performance information or analysis (including, without limitation, benchmarks) from any source relating to the equipment.

Such acts not expressly approved by Alcatel will result in the loss of product warranty and will invalidate the user's authority to operate this equipment.

Alcatel SpeedTouch™ Pro with Firewall

CLI Navigation


Accessing the Command Line Interface

Users can access the Command Line Interface via:

- ▶ The **SpeedTouch™ Pro with Firewall** CLI web pages
This requires that TCP/IP connectivity exists between the host from which the web browser is opened and the **SpeedTouch™ Pro with Firewall**
- ▶ A Telnet session
This requires that TCP/IP connectivity exists between the host from which the Telnet session is opened and the **SpeedTouch™ Pro with Firewall**
- ▶ The serial 'Console' interface.

Access via the Web Pages

The **SpeedTouch™ Pro with Firewall** CLI is accessible via its web interface. Browse to the **SpeedTouch™ Pro with Firewall** web pages and click  in the left frame. As a result the CLI web menu is opened in a new browser window:



You can open the CLI web pages directly by pointing the browser to the following URL:
<http://10.0.0.138/cli.htm> (in which the 10.0.0.138 IP address should be replaced by the actual **SpeedTouch™ Pro with Firewall** IP address if needed).

All CLI groups and commands are placed in a menu. You can open a group by clicking the  mark next to a group name, or clicking the group name.

Clicking on a command name will execute it. Commands without parameters are indicated with  and are executed immediately.

Commands which require additional parameters are indicated with . After you configured all parameters you must click  to execute the command.

Access via a Telnet Session or Serial Console

As soon a session to the CLI is opened, the **SpeedTouch™ Pro with Firewall** banner pops up, followed by the CLI prompt.

In case of a Telnet session authentication via the System password might be required before access is granted.

The following figure shows an example of the **SpeedTouch™ Pro with Firewall** banner after opening a Telnet session and authentication.

EXAMPLE:

Navigation and Manipulation

Manipulation commands are commands that manipulate operations on the command line, for example changing the command group, go to the beginning of the command line, go to the end of the command line, etc.

Command group Navigation

From top level, you can change to a command group by executing the name of the desired command group.

To obtain a list of all available command groups, execute **help** from the top level.

EXAMPLE:

```
=>help
Following commands are available :
help      : Displays this help information
?         : Displays this help information
exit     : Exits this shell.
..       : Exits group selection.

Following command groups are available :
dhcp      dns      td      atm      mer
bridge    pptp     ppp     cip      nat
adsl/shdsl qosbook   phonebook ip      software
system    config   firewall

=>
```

To return to top level, or to descend one level (in case of nested command groups) execute

EXAMPLE:

```
=>phonebook
[phonebook]=>
[phonebook]=>..
=>
```

The Help Command

Execute **help** from top level to list all available command groups for the **SpeedTouch™ Pro with Firewall**.

EXAMPLE:

```
=>help
Following commands are available :
help      : Displays this help information
?         : Displays this help information
exit     : Exits this shell.
..       : Exits group selection.

Following command groups are available :
dhcp      dns      td      atmfc      mer
bridge    pptp     ppp     cip       nat
adsl/shdsl qosbook   phonebook ip        software
system    config   firewall

=>
```

You can execute the **help** command from each command group selection. This results in a list of the available commands (and nested command groups, if available) in this particular command group.

EXAMPLE:

```
=>firewall
[firewall]=>
[firewall]=>help
Following commands are available :

tron      : Enables verbose console messaging.
troff     : Disables verbose console messaging.
match     : Defines an ip packet match.
assign    : Assign a chain to an entry point.
list      : Shows a list of all the hooks with the chain attached.
flush     : Clears all hooks. If a hook is provided, that hook is cleared.

Following command groups are available :

chain     rule

[firewall]=>
```

Executing e.g. **help firewall** from top level gives the same result as executing **help** from the firewall command group selection.

EXAMPLE:

```
=>firewall help
Following commands are available :

tron      : Enables verbose console messaging.
troff     : Disables verbose console messaging.
match     : Defines an ip packet match.
assign    : Assign a chain to an entry point.
list      : Shows a list of all the hooks with the chain attached.
flush     : Clears all hooks. If a hook is provided, that hook is cleared.

Following command groups are available :

chain     rule

=>
```

Entering **help** followed by a specific command, e.g. **help firewall assign** (starting from top level) or **help assign** (e.g. on the firewall command group selection) results in a description of the syntax for the command.

EXAMPLE:

```
=>help firewall assign
Assign a chain to an entry point.
Syntax : assign hook = <{input|sink|forward|source|output}> chain = <string>

parameters :
  hook = <{input|sink|forward|source|output}>
    Name of hook to assign chain to.
  chain = <string>
    Name of chain to use.

=>
```

Command Completion

The CLI features command completion, which means that when starting to enter a command it can be completed by pressing the “**Tab**” key.

For example, entering **a** at the firewall command group selection, followed by a “**Tab**” stroke results in the full **assign** command being completed. Entering **firewall a** from top level gives the same result.

For the completion to be successful, the part to be added must be unique. Completion works for the command groups, for the commands, for the options, but not for values.

EXAMPLE:

```
=>firewall  
[firewall]=>a "Tab"  
[firewall]=>assign
```

Going to the beginning or end of the Command Line

Go to the beginning of the Command Line by pressing “**Ctrl+A**”; to go to the end of the Command Line press “**Ctrl+E**”.

In the following example, the first || indicates the position of the cursor after pressing “**Ctrl+A**”, the second || the position of the cursor after pressing “**Ctrl+E**”.

EXAMPLE:

```
=>||list||
```

Breaking off Commands

You can break off a command by pressing “**Ctrl+G**”. This can be useful in a situation where a user is prompted to enter a value which it does not know and wants to abort the command. Instead of being prompted over and over again for the same value, this allows to break off the command.

In the example below “**Ctrl+G**” is pressed after the third prompt ‘vpi =’. The command is broken off and the user returns to the command line.

EXAMPLE:

```
[firewall]=>match  
chain =  
chain =  
chain = "Ctrl+G"  
[firewall]=>
```

History of Commands

To retake previous commands press the up arrow “↑” and come back to more recent commands with the down arrow “↓”. Press “**Enter** (J)” to select and execute the retaken command.

EXAMPLE:

```
=>firewall
[firewall]=>list
assign hook=input chain=input
assign hook=sink chain=sink
assign hook=forward chain=forward
assign hook=source chain=source
[firewall]=>"↑"
[firewall]=>:firewall list
```

Command Line Interface Top Level Structure

The following command groups are available:

- ▶ **adsl** (only applicable for the **SpeedTouch™ Pro with Firewall** ADSL/POTS variant)
- ▶ **atmf** (only applicable for models equipped with an ATMF-25.6Mbpsport)
- ▶ **bridge**
- ▶ **cip**
- ▶ **config**
- ▶ **dhcp**
- ▶ **dns**
- ▶ **firewall**
- ▶ **ip**
- ▶ **mer**
- ▶ **nat**
- ▶ **phonebook**
- ▶ **ppp**
- ▶ **pptp**
- ▶ **shdsl** (only applicable for the **SpeedTouch™ Pro with Firewall** SHDSL variant)
- ▶ **software**
- ▶ **system**
- ▶ **td**

Command Line Interface Commands

All CLI commands are commands that operate on, or configure, the **SpeedTouch™ Pro with Firewall**.

You can execute these commands from top level, preceded by the name of the command group from which the command should be executed (e. g. **firewall list**).

You can also execute the commands from the command group itself, using the reduced form of the command (e.g. **list** at the firewall command group selection).

'!' in a command means 'NOT', e.g. the '**[!]syn**' parameter in the **firewall rule create** command.

EXAMPLE:

```
=>firewall list
assign hook=input chain=input
assign hook=sink chain=sink
assign hook=forward chain=forward
assign hook=source chain=source
=>firewall
[firewall]=>list
assign hook=input chain=input
assign hook=sink chain=sink
assign hook=forward chain=forward
assign hook=source chain=source
[firewall]=>
```

Instead of entering a completely built-up command with all its parameters, you can also enter just the command itself, without its parameters. After this you are prompted to complete the command with the required and the optional parameters. For the optional parameters you can simply press enter without giving a value.

The example below is the equivalent of '**firewall assign hook=input chain=input**'. To break off such incomplete command press "**Ctrl+G**".

EXAMPLE:

```
=>firewall assign
hook = input
chain= input
=>
```

Alcatel SpeedTouch™ Pro with Firewall

CLI Command Description

1 ADSL Commands

The adsl command group is only applicable to the **SpeedTouch™ Pro with Firewall** ADSL/POTS variant, NOT to the **SpeedTouch™ Pro with Firewall** ADSL/ISDN and **SpeedTouch™ Pro with Firewall** SHDSL variant.

adsl (to access the ADSL level)

adsl info

adsl info

Show ADSL/POTS statistics and information about the **SpeedTouch™ Pro with Firewall** status.

SYNTAX:

```
adsl info
```

EXAMPLE:

```
=>adsl info
Modemstate      : up
Operation Mode   : G.DMT Annex A [ POTS Overlay Mode ]
Channel Mode     : fast
Number of resets : 1

Vendor (ITU)
  Country       : Of
  Vendor        : ALCB
  VendorSpecific : 0000
  StandardRevisionNr: 01

                                         Local          Remote
Margin      [dB]    :           31          31
Attenuation [dB]  :           26          13

Available Bandwidth
  Downstream    : Cells          Kbits
  Upstream      : 2641          1014
                  : 301           115

Transfer statistics
  Total since power On
    Downstream   : Cells          Kbits
    Upstream     : 185670         71297
  Current Connection
    Downstream   : 10254          3937
    Upstream     : N/Avail
  Errors
    Received FEC : 0
    Received CRC : 0
    Received HEC : 0
=>
```

2 ATMF Commands

The atmf command group is only applicable to the **SpeedTouch™ Pro with Firewall** ADSL/POTS variant equipped with an ATMF-25.6Mbps port.

atmf (to access the ATMF level)

atmf add

atmf delete

atmf flush

atmf list

atmf load

atmf save

atmf add

Add a cross-connection between the ATMf-25 interface and the WAN interface.

SYNTAX:

atmf add	vpi = <number {0-7}>
	vci = <number {0-511}>

vpi	A number between 0 and 7. Represents the Virtual Path identifier.	REQUIRED
-----	--	----------

vci	A number between 0 and 511. Represents the Virtual Channel identifier. Use VCI=0 for a VP cross-connection.	REQUIRED
-----	---	----------

EXAMPLE:

```
=>atmf list
VPI = 1 VCI = 0
VPI = 2 VCI = 0
VPI = 3 VCI = 0
VPI = 4 VCI = 0
VPI = 5 VCI = 0
VPI = 6 VCI = 0
VPI = 7 VCI = 0
=>atmf add vpi=0 vci=35
=>atmf list
VPI = 0 VCI = 35
VPI = 1 VCI = 0
VPI = 2 VCI = 0
VPI = 3 VCI = 0
VPI = 4 VCI = 0
VPI = 5 VCI = 0
VPI = 6 VCI = 0
VPI = 7 VCI = 0
=>
```

RELATED COMMANDS:

atmf delete	Delete a cross-connection on the ATMf-25 interface.
atmf list	Show current ATMf-25 interface configuration.

atmf delete

Delete a cross-connection on the ATMF-25 interface.

SYNTAX:

atmf delete	vpi = <number {0-7}>
	vci = <number {0-511}>

vpi	A number between 0 and 7. Represents the Virtual Path identifier.	REQUIRED
-----	--	----------

vci	A number between 0 and 511. Represents the Virtual Channel identifier. Use VCI=0 for a VP cross-connection.	REQUIRED
-----	---	----------

EXAMPLE:

```
=>atmf list
VPI = 0 VCI = 35
VPI = 1 VCI = 0
VPI = 2 VCI = 0
VPI = 3 VCI = 0
VPI = 4 VCI = 0
VPI = 5 VCI = 0
VPI = 6 VCI = 0
VPI = 7 VCI = 0
=>atmf delete vpi=0 vci=35
=>atmf list
VPI = 1 VCI = 0
VPI = 2 VCI = 0
VPI = 3 VCI = 0
VPI = 4 VCI = 0
VPI = 5 VCI = 0
VPI = 6 VCI = 0
VPI = 7 VCI = 0
=>
```

RELATED COMMANDS:

atmf add	Add a cross-connection on the ATMF-25 interface.
atmf list	Show current ATMF-25 interface configuration.

atmf flush

Flush complete ATMF-25 interface configuration.

The flush command does not impact previously saved configurations.

SYNTAX:

```
atmf flush
```

EXAMPLE:

```
=>atmf list
VPI = 1 VCI = 0
VPI = 2 VCI = 0
VPI = 3 VCI = 0
VPI = 4 VCI = 0
VPI = 5 VCI = 0
VPI = 6 VCI = 0
VPI = 7 VCI = 0
=>atmf flush
=>atmf list
=>
```

RELATED COMMANDS:

atmf load

Load saved or default ATMF-25 interface configuration.

atmf save

Save current ATMF-25 interface configuration.

atmf list

Show all current ATMF-25 interface cross-connections .

SYNTAX:

```
atmf list
```

EXAMPLE OUTPUT:

```
=>atmf list
VPI = 0    VCI = 35
VPI = 1    VCI = 0
VPI = 2    VCI = 0
VPI = 3    VCI = 0
VPI = 4    VCI = 0
VPI = 5    VCI = 0
VPI = 6    VCI = 0
VPI = 7    VCI = 0
=>
```

RELATED COMMANDS:

atmf add	Add an ATMF-25 interface cross-connection.
atmf delete	Delete a cross-connection on the ATMF-25 interface.

atmf load

Load saved (or default) ATMF-25 interface configuration.

Execute **atmf flush** prior to **atmf load**.

SYNTAX:

atmf load	[defaults = <yes no>]
------------------	------------------------------------

[defaults]	Load factory defaults (yes) or saved configuration (no). Not specifying this parameter loads the saved configuration	OPTIONAL
-------------------	---	----------

EXAMPLE:

```
=>atmf list
VPI = 0 VCI = 35
=>atmf save
=>atmf flush
=>atmf load defaults=yes
=>atmf list
VPI = 0 VCI = 0
VPI = 1 VCI = 0
VPI = 2 VCI = 0
VPI = 3 VCI = 0
VPI = 4 VCI = 0
VPI = 5 VCI = 0
VPI = 6 VCI = 0
VPI = 7 VCI = 0
=>atmf flush
=>atmf load defaults=no
=>atmf list
VPI = 0 VCI = 35
=>
```

RELATED COMMANDS:

atmf flush	Flush complete ATMF-25 interface configuration.
atmf save	Save current ATMF-25 interface configuration.

atmf save

Save current ATMF-25 interface configuration.

SYNTAX:

```
atmf save
```

EXAMPLE:

```
=>atmf list
VPI = 0 VCI = 35
VPI = 1 VCI = 0
VPI = 2 VCI = 0
VPI = 3 VCI = 0
VPI = 4 VCI = 0
VPI = 5 VCI = 0
VPI = 6 VCI = 0
VPI = 7 VCI = 0
=>atmf save
=>atmf flush
=>atmf list
=>atmf load
=>atmf list
VPI = 0 VCI = 35
VPI = 1 VCI = 0
VPI = 2 VCI = 0
VPI = 3 VCI = 0
VPI = 4 VCI = 0
VPI = 5 VCI = 0
VPI = 6 VCI = 0
VPI = 7 VCI = 0
=>
```

RELATED COMMANDS:

atmf flush

Flush complete ATMF-25 interface configuration.

atmf load

Load saved or default ATMF-25 interface configuration.

3 Bridge Commands

bridge (to access the Bridge level)
bridge config
bridge flush
bridge ifadd
bridge ifattach
bridge ifconfig
bridge ifdelete
bridge ifdetach
bridge iflist
bridge load
bridge macadd
bridge macdelete
bridge maclist
bridge save

bridge config

Show/set bridge aging policy.

SYNTAX:

bridge config	[age = <number {10 - 100000}>]
----------------------	---

[age]	A number between 10 and 100000 (seconds). Represents the lifetime of a dynamically learned MAC address. By default the aging timer is 300 seconds.	OPTIONAL
-------	--	----------

EXAMPLE:

=> bridge config Aging : 300 => bridge config age=600 => bridge config <u>Aging : 600</u> =>
--

bridge flush

Flush complete bridging configuration.

The flush command does not impact previously saved configurations.

SYNTAX:

bridge flush

EXAMPLE:

```
=>bridge iflist
OBC      : Internal
          Connection State: connected    Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82768372   frames: 341221  dropframes: 0
eth0     : Internal
          Connection State: connected    Port: eth0     PortState: forwarding
          RX bytes: 156344216   frames: 5899238
          TX bytes: 75689      frames: 425      dropframes: 5558017
Br1      : dest : Br1
          Retry: 10   QoS: default   Encaps: llc/snap  Fcs: off
          Connection State: connected    Port: wan0     PortState: forwarding
          RX bytes: 75          frames: 12
          TX bytes: 30246      frames: 91      dropframes: 0
Br2      : dest : Br2
          Retry: 10   QoS: default   Encaps: llc/snap  Fcs: off
          Connection State: connected    Port: wan1     PortState: forwarding
          RX bytes: 167356345   frames: 7453312
          TX bytes: 64234246   frames: 2846491      dropframes: 0
=>bridge flush
=>bridge iflist
OBC      : Internal
          Connection State: connected    Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82908667   frames: 341735    dropframes: 0
eth0     : Internal
          Connection State: connected    Port: eth0     PortState: forwarding
          RX bytes: 156553257   frames: 5904070
          TX bytes: 75689      frames: 425      dropframes: 5562335
=>
```

RELATED COMMANDS:

bridge load

Load saved or default bridge configuration.

bridge save

Save current bridge configuration.

bridge ifadd

Create a bridge interface.

SYNTAX:

bridge ifadd	<i>intf = <string></i>
	<i>dest = <phonebook entry></i>

<i>intf</i>	The bridge interface name. If not specified, the destination parameter must be specified. In this case the name of the destination will double as interface name.	OPTIONAL
<i>dest</i>	The destination address for the new interface. Typically a phonebook entry.	OPTIONAL

EXAMPLE:

```
=>bridge iflist
OBC      : Internal
          Connection State: connected    Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82768372   frames: 341221  dropframes:  0
eth0     : Internal
          Connection State: connected    Port: eth0     PortState: forwarding
          RX bytes: 156344216   frames: 5899238
          TX bytes: 75689      frames: 425      dropframes:  5558017
=>phonebook list
Name      Type    Use   Address
Br1       bridge  0    8.35
Br2       bridge  0    8.36
CIPPVC3   cip     1    8.82
CIPPVC4   cip     1    8.83
=>bridge ifadd intf=NewBridge dest=Br1
=>bridge iflist
OBC      : Internal
          Connection State: connected    Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82843610   frames: 341554  dropframes:  0
eth0     : Internal
          Connection State: connected    Port: eth0     PortState: forwarding
          RX bytes: 156472129   frames: 5903256
          TX bytes: 75689      frames: 425      dropframes:  5561702
NewBridge : dest : Br1
          Retry: 10    QoS: default   Encaps: llc/snap  Fcs: off
          Connection State: not-connectedPort: (Unassigned) PortState: forwarding
=>
```

RELATED COMMANDS:

bridge ifattach	Attach a bridge interface.
bridge ifdetach	Detach a bridge interface.
bridge ifdelete	Delete a bridge interface.
bridge ifconfig	Configure a bridge interface.
bridge iflist	Show current bridge configuration.

bridge ifattach

Attach (i.e. connect) a bridge interface.

SYNTAX:

bridge ifattach	intf = <ifname>
------------------------	------------------------------

<i>intf</i>	The name of the bridge interface to attach.	REQUIRED
-------------	---	----------

EXAMPLE:

```
=>bridge iflist
OBC      : Internal
          Connection State: connected    Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82843610   frames: 341554  dropframes: 0
eth0     : Internal
          Connection State: connected    Port: eth0     PortState: forwarding
          RX bytes: 156472129   frames: 5903256
          TX bytes: 75689      frames: 425      dropframes: 5561702
NewBridge : dest : Br1
          Retry: 10   QoS: default   Encaps: llc/snap  Fcs: off
          Connection State: not-connectedPort: (Unassigned) PortState: forwarding
=>bridge ifattach intf=NewBridge
=>bridge iflist
OBC      : Internal
          Connection State: connected    Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82843610   frames: 341554  dropframes: 0
eth0     : Internal
          Connection State: connected    Port: eth0     PortState: forwarding
          RX bytes: 156472129   frames: 5903256
          TX bytes: 75689      frames: 425      dropframes: 5561702
NewBridge : dest : Br1
          Retry: 10   QoS: default   Encaps: llc/snap  Fcs: off
Connection State: connected    Port: wan0     PortState: forwarding
          RX bytes: 75      frames: 12
          TX bytes: 30246     frames: 91      dropframes: 0
=>
```

RELATED COMMANDS:

bridge ifadd	Create a bridge interface.
bridge ifdetach	Detach a bridge interface.
bridge ifdelete	Delete a bridge interface.
bridge ifconfig	Configure a bridge interface.
bridge iflist	Show current bridge configuration.

bridge ifconfig

Configure a bridge interface.

SYNTAX:

bridge ifconfig	<i>intf = <ifname></i> <i>[dest = <ifname>]</i> <i>[qos = <string>]</i> <i>[encaps = <{llc/snap vcmux}>]</i> <i>[fcs = <{off on}>]</i> <i>[portstate = <{disabled learning forwarding}>]</i> <i>[retry = <number {0-65535}>]</i>	
<i>intf</i>	The name of the bridge interface to configure.	REQUIRED
<i>[dest]</i>	The destination for this interface. Typically a phonebook entry. This parameter needs only to be specified in case of an interface created without specified destination.	OPTIONAL
<i>[qos]</i>	The name of a configured Quality Of Service book entry. This parameter never needs to be specified.	OPTIONAL
<i>[encaps]</i>	The type of encapsulation to be used for this bridge interface. Choose between: <ul style="list-style-type: none">▪ llc/snap▪ vcmux	OPTIONAL
<i>[fcs]</i>	Whether or not to include the Ethernet FCS in the packet header on the WAN side. Choose between: <ul style="list-style-type: none">▪ off▪ on	OPTIONAL
<i>[portstate]</i>	The bridge portstate for this interface. Choose between: <ul style="list-style-type: none">▪ disabled▪ learning▪ forwarding	OPTIONAL
<i>[retry]</i>	A number between 0 and 65535. Represents the number of WAN connection setup retries before giving up. By default the retry value is 10.	OPTIONAL

EXAMPLE:

```
=>bridge iflist intf=NewBridge
NewBridge : dest : Br1
    Retry: 10   QoS: default   Encaps: llc/snap   Fcs: off
    Connection State: connected   Port: wan0   PortState: forwarding
    RX bytes: 75           frames: 12
    TX bytes: 30246        frames: 91       dropframes: 0
=>bridge ifconfig intf=NewBridge encaps=vcmux retry=15
=>bridge iflist intf=NewBridge
NewBridge : dest : Br1
    Retry: 15   OoS: default   Encaps: vcmux      Fcs: off
    Connection State: connected   Port: wan0   PortState: forwarding
    RX bytes: 83           frames: 13
    TX bytes: 30740        frames: 102      dropframes: 0
=>
```

RELATED COMMANDS:

bridge ifadd	Create a bridge interface.
bridge ifattach	Attach a bridge interface.
bridge ifdetach	Detach a bridge interface.
bridge ifdelete	Delete a bridge interface.
bridge iflist	Show current bridge configuration.

bridge ifdelete

Delete a bridge interface.

bridge ifdelete	intf = <ifname>
------------------------	------------------------------

<i>intf</i>	The name of the interface name to delete.	REQUIRED
-------------	---	----------

EXAMPLE:

```
=>bridge iflist
OBC      : Internal
          Connection State: connected    Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82768372   frames: 341221  dropframes:  0
eth0     : Internal
          Connection State: connected    Port: eth0     PortState: forwarding
          RX bytes: 156344216   frames: 5899238
          TX bytes: 75689      frames: 425      dropframes:  5558017
NewBridge : dest : Br1
          Retry: 10      QoS: default    Encaps: llc/snap  Fcs: off
          Connection State: not-connectedPort: (Unassigned) PortState: forwarding
=>bridge ifdelete intf=NewBridge
=>bridge iflist
OBC      : Internal
          Connection State: connected    Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82843610   frames: 341554  dropframes:  0
eth0     : Internal
          Connection State: connected    Port: eth0     PortState: forwarding
          RX bytes: 156472129   frames: 5903256
          TX bytes: 75689      frames: 425      dropframes:  5561702
=>
```

RELATED COMMANDS:

bridge ifadd	Create a bridge interface.
bridge ifattach	Attach a bridge interface.
bridge ifconfig	Configure a bridge interface.
bridge ifdetach	Detach a bridge interface.
bridge iflist	Show current bridge configuration.

bridge ifdetach

Detach (i.e. disconnect) a bridge interface.

SYNTAX:

bridge ifdetach	intf = <ifname>
------------------------	------------------------------

<i>intf</i>	The name of the bridge interface to detach.	REQUIRED
-------------	---	----------

EXAMPLE:

```
=>bridge iflist intf=NewBridge
NewBridge : dest : Br1
    Retry: 10    QoS: default    Encaps: llc/snap    Fcs: off
    Connection State: connected    Port: wan0    PortState: forwarding
    RX bytes: 75          frames: 12
    TX bytes: 30246        frames: 91        dropframes: 0
=>bridge ifattach intf=NewBridge
=>bridge iflist intf=NewBridge
NewBridge : dest : Br1
    Retry: 10    QoS: default    Encaps: llc/snap    Fcs: off
    Connection State: not-connected Port: (Unassigned)    PortState: forwarding
=>
```

RELATED COMMANDS:

bridge ifadd	Create a bridge interface.
bridge ifattach	Attach a bridge interface.
bridge ifconfig	Configure a bridge interface.
bridge ifdelete	Delete a bridge interface.
bridge iflist	Show current bridge configuration.

bridge iflist

Show the current state of all or the selected bridge interfaces.

SYNTAX:

bridge iflist	[intf = <ifname>]
----------------------	--------------------------------

[intf]	The name of the bridge interface to show the configuration of.	OPTIONAL
	If not specified all bridge interfaces are shown.	

EXAMPLE OUTPUT:

```
=>bridge iflist
OBC      : Internal
          Connection State: connected    Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82768372   frames: 341221  dropframes:  0
eth0     : Internal
          Connection State: connected    Port: eth0      PortState: forwarding
          RX bytes: 156344216   frames: 5899238
          TX bytes: 75689      frames: 425      dropframes:  5558017
NewBridge : dest : Br1
          Retry: 15   QoS: default   Encaps: vcmux      Fcs: off
          Connection State: connected    Port: wan0      PortState: forwarding
          RX bytes: 83        frames: 13
          TX bytes: 30740      frames: 102      dropframes:  0
=>
```

DESCRIPTION:

'RX bytes' indicates the number of Received bytes, 'TX bytes' the number of Transmitted bytes.
OBC is short for On Board Controller and indicates the physical bridge port.

RELATED COMMANDS:

bridge ifadd	Create a bridge interface.
bridge ifattach	Attach a created bridge interface.
bridge ifconfig	Configure a bridge interface.
bridge ifdelete	Delete a bridge interface.
bridge ifdetach	Detach a bridge interface.

bridge load

Load saved (or default) bridge configuration.

Execute **bridge flush** prior to **bridge load**.

SYNTAX:

bridge load	[defaults = <yes no>]
--------------------	------------------------------------

[defaults]	Load factory defaults (yes) or saved configuration (no). Not specifying this parameter loads the saved configuration	OPTIONAL
---------------------	---	----------

EXAMPLE:

```
=>bridge iflist
OBC      : Internal
          Connection State: connected      Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82768372    frames: 341221  dropframes: 0
eth0     : Internal
          Connection State: connected      Port: eth0      PortState: forwarding
          RX bytes: 156344216   frames: 5899238
          TX bytes: 75689      frames: 425      dropframes: 5558017
=>bridge ifadd intf=Br1 dest=Br1
=>bridge save
=>bridge flush
=>bridge iflist
OBC      : Internal
          Connection State: connected      Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82908667    frames: 341735   dropframes: 0
eth0     : Internal
          Connection State: connected      Port: eth0      PortState: forwarding
          RX bytes: 156553257   frames: 5904070
          TX bytes: 75689      frames: 425      dropframes: 5562335
=>bridge load defaults=no
=>bridge iflist
OBC      : Internal
          Connection State: connected      Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82768372    frames: 341221  dropframes: 0
eth0     : Internal
          Connection State: connected      Port: eth0      PortState: forwarding
          RX bytes: 156344216   frames: 5899238
          TX bytes: 75689      frames: 425      dropframes: 5558017
Br1     : dest : Br1
          Retry: 10   QoS: default   Encaps: llc/snap   Fcs: off
          Connection State: connected      Port: wan0  PortState: forwarding
          RX bytes: 75      frames: 12
          TX bytes: 30246     frames: 91      dropframes: 0
=>
```

RELATED COMMANDS:

bridge flush	Flush complete bridge configuration.
bridge save	Save current bridge configuration.

bridge macadd

Add a static MAC address to the filtering database. Allows to manually add static addresses, which should normally be dynamically discovered by the bridge itself.

SYNTAX:

bridge macadd	<i>intf = <ifname></i>
	<i>hwaddr = <hardware-address></i>

<i>intf</i>	The name of the bridge interface to add the MAC address for.	REQUIRED
<i>hwaddr</i>	The MAC address of the new entry.	REQUIRED

EXAMPLE:

```
=>bridge maclist
00:90:d0:01:02:03 -- static, OBC
ff:ff:ff:ff:ff:ff -- static, OBC
01:80:c2:00:00:00 -- static, OBC
01:80:c2:00:00:01 -- static, OBC
...
01:80:c2:00:00:10 -- static, OBC
00:01:42:5f:7d:81 -- dynamic, eth0, 597 seconds
00:50:8b:31:cc:aa -- dynamic, eth0, 513 seconds
08:00:20:c1:9a:12 -- dynamic, eth0, 600 seconds
...
=>bridge macadd intf=eth0 hwaddr=00:80:9f:01:23:45
=>bridge maclist
00:90:d0:01:02:03 -- static, OBC
ff:ff:ff:ff:ff:ff -- static, OBC
01:80:c2:00:00:00 -- static, OBC
01:80:c2:00:00:01 -- static, OBC
...
01:80:c2:00:00:10 -- static, OBC
00:80:9f:01:23:45 -- permanent, OBC
00:01:42:5f:7d:81 -- dynamic, eth0, 598 seconds
00:50:8b:31:cc:aa -- dynamic, eth0, 379 seconds
08:00:20:c1:9a:12 -- dynamic, eth0, 600 seconds
00:08:c7:c3:5f:fc -- dynamic, eth0, 215 seconds
...
=>
```

RELATED COMMANDS:

bridge macdelete	Delete a MAC address entry.
bridge maclist	Show current filtering database.

bridge macdelete

Remove a MAC address from the filtering database.

SYNTAX:

bridge macdelete	hwaddr = <hardware-address>
-------------------------	--

hwaddr	The MAC address of the entry to delete.	REQUIRED
--------	---	----------

EXAMPLE:

```
=>bridge maclist
00:90:d0:01:02:03 -- static, OBC
ff:ff:ff:ff:ff:ff -- static, OBC
01:80:c2:00:00:00 -- static, OBC
01:80:c2:00:00:01 -- static, OBC
...
01:80:c2:00:00:10 -- static, OBC
00:80:9f:01:23:45 -- permanent, OBC
00:01:42:5f:7d:81 -- dynamic, eth0, 597 seconds
00:50:8b:31:cc:aa -- dynamic, eth0, 513 seconds
08:00:20:c1:9a:12 -- dynamic, eth0, 600 seconds
...
=>bridge macdelete hwaddr=00:80:9f:01:23:45
=>bridge maclist
00:90:d0:01:02:03 -- static, OBC
ff:ff:ff:ff:ff:ff -- static, OBC
01:80:c2:00:00:00 -- static, OBC
01:80:c2:00:00:01 -- static, OBC
...
01:80:c2:00:00:10 -- static, OBC
00:01:42:5f:7d:81 -- dynamic, eth0, 598 seconds
00:50:8b:31:cc:aa -- dynamic, eth0, 379 seconds
08:00:20:c1:9a:12 -- dynamic, eth0, 600 seconds
00:08:c7:c3:5f:fc -- dynamic, eth0, 215 seconds
...
=>
```

RELATED COMMANDS:

bridge macadd	Add a static MAC address entry.
bridge maclist	Show current filtering database.

bridge maclist

Show current MAC address filtering database.

SYNTAX:

```
bridge maclist
```

EXAMPLE:

```
=>bridge maclist
=>bridge maclist
00:90:d0:01:02:03 -- static, OBC
ff:ff:ff:ff:ff:ff -- static, OBC
01:80:c2:00:00:00 -- static, OBC
01:80:c2:00:00:01 -- static, OBC
...
01:80:c2:00:00:10 -- static, OBC
00:80:9f:24:ab:cf -- static, OBC
00:01:42:5f:7d:81 -- dynamic, eth0, 598 seconds
00:50:8b:31:cc:aa -- dynamic, eth0, 379 seconds
08:00:20:c1:9a:12 -- dynamic, eth0, 600 seconds
00:08:c7:c3:5f:fc -- dynamic, eth0, 215 seconds
08:00:20:a8:f4:34 -- dynamic, eth0, 600 seconds
08:00:20:83:b7:26 -- dynamic, eth0, 600 seconds
00:10:83:1b:13:18 -- dynamic, eth0, 599 seconds
...
=>
```

RELATED COMMANDS:

bridge macadd
bridge macdelete

Add a static MAC address entry.
Delete a MAC address entry.

bridge save

Save current bridge configuration.

SYNTAX:

```
bridge save
```

EXAMPLE:

```
=>bridge iflist
OBC      : Internal
          Connection State: connected    Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82768372   frames: 341221  dropframes: 0
eth0     : Internal
          Connection State: connected    Port: eth0     PortState: forwarding
          RX bytes: 156344216   frames: 5899238
          TX bytes: 75689      frames: 425      dropframes: 5558017
=>bridge ifadd intf=Brl dest=Brl
=>bridge save
=>bridge flush
=>bridge iflist
OBC      : Internal
          Connection State: connected    Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82908667   frames: 341735   dropframes: 0
eth0     : Internal
          Connection State: connected    Port: eth0     PortState: forwarding
          RX bytes: 156553257   frames: 5904070
          TX bytes: 75689      frames: 425      dropframes: 5562335
=>bridge load defaults=no
=>bridge iflist
OBC      : Internal
          Connection State: connected    Port: OBC      PortState: forwarding
          RX bytes: 75783      frames: 572
          TX bytes: 82768372   frames: 341221  dropframes: 0
eth0     : Internal
          Connection State: connected    Port: eth0     PortState: forwarding
          RX bytes: 156344216   frames: 5899238
          TX bytes: 75689      frames: 425      dropframes: 5558017
Brl     : dest : Brl
          Retry: 10   QoS: default   Encaps: llc/snap  Fcs: off
          Connection State: connected    Port: wan0     PortState: forwarding
          RX bytes: 75      frames: 12
          TX bytes: 30246     frames: 91      dropframes: 0
=>
```

RELATED COMMANDS:

bridge flush

Flush complete bridge configuration.

bridge load

Load saved or default bridge configuration.

4 CIP Commands

cip (to access the CIP level)
cip flush
cip ifadd
cip ifdelete
cip iflist
cip load
cip pvcadd
cip pvcdelete
cip pvclist
cip save

cip flush

Flush complete CIP configuration.

The flush command does not impact previously saved configurations.

SYNTAX:

```
cip flush
```

EXAMPLE:

```
=>cip iflist
cip0      addr = 172.16.0.5    mask = 255.255.255.0
          UNI address = A0:*.04
          inarp_reqs_in = 0      inarp_repl_in = 0      inarp_inv_in = 0
          inarp_reqs_out = 0     inarp_repl_out = 0     inarp_inv_out= 0
=>cip flush
=>cip iflist
=>
```

RELATED COMMANDS:

cip load	Load saved or default CIP configuration.
cip save	Save current CIP configuration.

cip ifadd

Create a CIP interface at the local side of the Logical IP Subnet (LIS).

SYNTAX:

cip ifadd	addr = <ip-address>
	[netmask = <ip-mask (dotted or cidr)>]
	[uniaddr = <portspec:address[.selector]>]

addr	The CIP interface's local IP address in the LIS.	REQUIRED
netmask	The LIS's subnetmask.	OPTIONAL
uniaddr	The UNI-address/port specification for incoming connections, e.g. 'A0:*.04': ADSL port, any address, selector 3. Only applicable in an SVC environment.	OPTIONAL

EXAMPLE:

```
=>cip iflist
cip1      addr = 172.16.0.5    mask = 255.255.255.0
          UNI address = A0:*.04
          inarp_reqs_in = 0    inarp_repl_in = 0    inarp_inv_in = 0
          inarp_reqs_out = 0   inarp_repl_out = 0   inarp_inv_out= 0
=>cip ifadd addr=172.16.1.1 netmask=255.255.255.0
=>cip iflist
cip1      addr = 172.16.0.5    mask = 255.255.255.0
          UNI address = A0:*.04
          inarp_reqs_in = 0    inarp_repl_in = 0    inarp_inv_in = 0
          inarp_reqs_out = 0   inarp_repl_out = 0   inarp_inv_out= 0
cip0      addr = 172.16.1.1    mask = 255.255.255.0
          UNI address = A0:*.03
          inarp_reqs_in = 0    inarp_repl_in = 0    inarp_inv_in = 0
          inarp_reqs_out = 0   inarp_repl_out = 0   inarp_inv_out= 0
=>
```

RELATED COMMANDS:

cip ifdelete	Delete a CIP interface.
cip ifadd	Show current CIP configuration.

cip ifdelete

Delete a CIP interface at the local side of the Logical IP Subnet (LIS).

SYNTAX:

cip ifdelete	addr = <ip-address>
---------------------	----------------------------------

addr	The CIP interface's local IP address in the LIS.	REQUIRED
------	--	----------

EXAMPLE:

```
=>cip iflist
cip0      addr = 172.16.1.1    mask = 255.255.255.0
          UNI address = A0:*.03
          inarp_reqs_in = 0     inarp_repl_in = 0     inarp_inv_in = 0
          inarp_reqs_out = 0    inarp_repl_out = 0    inarp_inv_out= 0
cip1      addr = 172.16.0.5    mask = 255.255.255.0
          UNI address = A0:*.04
          inarp_reqs_in = 0     inarp_repl_in = 0     inarp_inv_in = 0
          inarp_reqs_out = 0    inarp_repl_out = 0    inarp_inv_out= 0
=>cip ifdelete addr=172.16.1.1
=>cip iflist
cip1      addr = 172.16.0.5    mask = 255.255.255.0
          UNI address = A0:*.04
          inarp_reqs_in = 0     inarp_repl_in = 0     inarp_inv_in = 0
          inarp_reqs_out = 0    inarp_repl_out = 0    inarp_inv_out= 0
=>
```

RELATED COMMANDS:

cip ifadd	Create a CIP interface.
cip iflist	Show current CIP configuration.

cip iflist

Show current CIP configuration.

SYNTAX:

```
cip iflist
```

EXAMPLE OUTPUT:

```
=>cip iflist
cip0      addr = 172.16.1.1    mask = 255.255.255.0
          UNI address = A0:*.03
          inarp_reqs_in = 0     inarp_repl_in = 0     inarp_inv_in = 0
          inarp_reqs_out = 0    inarp_repl_out = 0    inarp_inv_out = 0
cip1      addr = 172.16.0.5    mask = 255.255.255.0
          UNI address = A0:*.04
          inarp_reqs_in = 0     inarp_repl_in = 0     inarp_inv_in = 0
          inarp_reqs_out = 0    inarp_repl_out = 0    inarp_inv_out = 0
=>
```

DESCRIPTION:

inarp_reqs_in/inarp_reqs_out : Incoming/outgoing inverse ARP requests

inarp_repl_in/inarp_repl_out : Incoming/outgoing inverse ARP replies

inarp_inv_in/inarp_inv_out : Incoming/outgoing invalid inverse ARP messages

EXAMPLE INPUT/OUTPUT: EVOLUTION OF ARP REQUESTS IN A NETWORKED ENVIRONMENT:

```
=>cip iflist
cip0      addr = 200.200.200.138 mask = 255.255.255.0
          UNI address = A0:*.03
          inarp_reqs_in = 18   inarp_repl_in = 75   inarp_inv_in = 0
          inarp_reqs_out = 18   inarp_repl_out = 75   inarp_inv_out = 0
=>cip iflist
cip0      addr = 200.200.200.138 mask = 255.255.255.0
          UNI address = A0:*.03
          inarp_reqs_in = 22   inarp_repl_in = 75   inarp_inv_in = 0
          inarp_reqs_out = 22   inarp_repl_out = 75   inarp_inv_out = 0
=>cip iflist
cip0      addr = 200.200.200.138 mask = 255.255.255.0
          UNI address = A0:*.03
          inarp_reqs_in = 22   inarp_repl_in = 76   inarp_inv_in = 0
          inarp_reqs_out = 22   inarp_repl_out = 76   inarp_inv_out = 0
=>
```

RELATED COMMANDS:

cip ifadd	Create a CIP interface.
cip ifdelete	Delete a CIP interface.

cip load

Load saved (or default) CIP configuration.

Execute **cip flush** prior to **cip load**.

SYNTAX:

cip load	<i>[defaults = <yes/no>]</i>
-----------------	------------------------------------

<i>[defaults]</i>	Load factory defaults (yes) or saved configuration (no).	OPTIONAL
	Not specifying this parameter loads the saved configuration	

EXAMPLE:

```
=>cip iflist
cip0      addr = 172.16.1.1    mask = 255.255.255.0
          UNI address = A0:*.03
          inarp_reqs_in = 0     inarp_repl_in = 0     inarp_inv_in = 0
          inarp_reqs_out = 0    inarp_repl_out = 0    inarp_inv_out= 0
cip1      addr = 172.16.0.5    mask = 255.255.255.0
          UNI address = A0:*.04
          inarp_reqs_in = 0     inarp_repl_in = 0     inarp_inv_in = 0
          inarp_reqs_out = 0    inarp_repl_out = 0    inarp_inv_out= 0
=>cip save
=>cip flush
=>cip iflist
=>cip load defaults=yes
=>cip iflist
cip0      addr = 172.16.1.1    mask = 255.255.255.0
          UNI address = A0:*.03
          inarp_reqs_in = 0     inarp_repl_in = 0     inarp_inv_in = 0
          inarp_reqs_out = 0    inarp_repl_out = 0    inarp_inv_out= 0
=>cip flush
=>cip iflist
=>cip load defaults=no
=>cip iflist
cip0      addr = 172.16.1.1    mask = 255.255.255.0
          UNI address = A0:*.03
          inarp_reqs_in = 0     inarp_repl_in = 0     inarp_inv_in = 0
          inarp_reqs_out = 0    inarp_repl_out = 0    inarp_inv_out= 0
cip1      addr = 172.16.0.5    mask = 255.255.255.0
          UNI address = A0:*.04
          inarp_reqs_in = 0     inarp_repl_in = 0     inarp_inv_in = 0
          inarp_reqs_out = 0    inarp_repl_out = 0    inarp_inv_out= 0
=>
```

RELATED COMMANDS:

cip flush	Flush complete CIP configuration.
cip save	Save current CIP configuration.

cip pvcadd

Create a PVC ARP entry for destinations which are not RFC 1577/RFC2225 compliant.

SYNTAX:

cip pvcadd	dest = <phonebookname>
	[destaddr = <ip-address>]
	[mtu = <number {273–20000}>]

dest	The ATM address (hardware address) of the destination host. Typically a phonebook name.	REQUIRED
[destaddr]	The IP address of the destination host.	OPTIONAL
[mtu]	A number between 273 and 20000 (bytes). Represents the maximum AAL5 packet size for this connection. By default the mtu is 9180 bytes.	OPTIONAL

EXAMPLE:

```
=>phonebook list
Name      Type    Use   Address
Br1       bridge  1     8.35
Br2       bridge  1     8.36
Br3       bridge  1     8.37
Br4       bridge  0     8.38
RELAY_PPP1 ppp    0     8.48
RELAY_PPP2 ppp    0     8.49
RELAY_PPP3 ppp    0     8.50
RELAY_PPP4 ppp    0     8.51
PPP1      ppp    1     8.64
PPP2      ppp    1     8.65
PPP3      ppp    1     8.66
DHCP_SPOOF ppp    1     8.67
CIPPVC1   cip    0     8.80
CIPPVC2   cip    0     8.81
CIPPVC3   cip    0     8.82
CIPPVC4   cip    0     8.83
=>cip pvclist
=>cip pvcadd dest CIPPVC1 destaddr 172.16.1.2 mtu 546
=>cip pvclist
CIPPVC1   atmport = 0          vpi   = 8      vci   = 80      dest_ip = 172.16.1.2
          encaps   = llc        mtu   = 546
=>
```

RELATED COMMANDS:

cip pvcdelete

Delete a PVC ARP entry.

cip pvclist

Show current PVC ARP entries.

cip pvcdelete

Delete a PVC ARP entry.

SYNTAX:

cip pvcdelete	dest = <phonebookname>
----------------------	-------------------------------------

dest	Typically a phonebook entry name. Represents the ATM address (hardware address) or name of the entry to delete.	REQUIRED
------	---	----------

EXAMPLE:

```
=>cip pvclist
CIPPVC1      atmport = 0          vpi   = 8      vci   = 80      dest_ip = 172.16.1.2
           encaps  = llc        mtu   = 546
=>cip pvcdelete dest=CIPPVC1
=>cip pvclist
=>
```

RELATED COMMANDS:

cip pvcadd	Create a PVC ARP entry.
cip pvclist	Show current PVC ARP entries.

cip pvclist

Show current PVC ARP entries.

SYNTAX:

```
cip pvclist
```

EXAMPLE OUTPUT:

```
=>cip pvclist
CIPPVC1      atmport = 0          vpi    = 8       vci    = 80      dest_ip = 172.16.1.2
              encaps   = llc        mtu    = 546
=>
```

EXAMPLE INPUT/OUTPUT IN A NETWORKED ENVIRONMENT:

```
=>cip iflist
cip0      addr = 200.200.200.138    mask = 255.255.255.0
          UNI address = A0:*.03
          inarp_reqs_in = 0      inarp_repl_in = 75      inarp_inv_in = 0
          inarp_reqs_out = 0     inarp_repl_out = 75      inarp_inv_out = 0
=>cip pvclist
699      atmport = 0      vpi    = 6       vci    = 99      dest_ip = 172.16.1.3
          encaps   = llc        mtu    = 9180
8.50     atmport = 0      vpi    = 8       vci    = 50      dest_ip = 200.200.200.14
          encaps   = llc        mtu    = 9180
=>
```

RELATED COMMANDS:

cip pvcdelete	Delete a PVC ARP entry.
cip pvcadd	Create a PVC ARP entry.

cip save

Save current CIP configuration.

SYNTAX:

cip save

EXAMPLE:

=>cip iflist	addr = 172.16.1.1 mask = 255.255.255.0
cip0	UNI address = A0:*.03
	inarp_reqs_in = 0 inarp_repl_in = 0 inarp_inv_in = 0
	inarp_reqs_out = 0 inarp_repl_out = 0 inarp_inv_out = 0
cip1	addr = 172.16.0.5 mask = 255.255.255.0
	UNI address = A0:*.04
	inarp_reqs_in = 0 inarp_repl_in = 0 inarp_inv_in = 0
	inarp_reqs_out = 0 inarp_repl_out = 0 inarp_inv_out = 0
=>cip save	
=>cip flush	
=>cip iflist	
=>cip load defaults=no	
=>cip iflist	
cip0	addr = 172.16.1.1 mask = 255.255.255.0
	UNI address = A0:*.03
	inarp_reqs_in = 0 inarp_repl_in = 0 inarp_inv_in = 0
	inarp_reqs_out = 0 inarp_repl_out = 0 inarp_inv_out = 0
cip1	addr = 172.16.0.5 mask = 255.255.255.0
	UNI address = A0:*.04
	inarp_reqs_in = 0 inarp_repl_in = 0 inarp_inv_in = 0
	inarp_reqs_out = 0 inarp_repl_out = 0 inarp_inv_out = 0
=>	

RELATED COMMANDS:

cip flush

Flush complete CIP configuration.

cip load

Load saved or default CIP configuration.

5 Config Commands

config (to access the Config level)
config erase
config flush
config load
config reset
config save

config erase

Physically remove all saved configurations.

SYNTAX:

```
config erase
```

EXAMPLE:

```
=>config erase
```

RELATED COMMANDS:

config flush	Flush complete runtime configuration.
config load	Load complete saved or default configuration.
config reset	Flush current and optionally restore default configuration.
config save	Save complete runtime configuration.

config flush

Flush complete current configuration without affecting saved configurations.

This combines all flush commands: **atmf flush**, **bridge flush**, **cip flush**, **config flush**, **dhcp client flush**, **dhcp server flush**, **dns flush**, **firewall flush**, **firewall rule flush**, **mer flush**, **nat flush**, **phonebook flush**, **ppp flush**, **pptp flush**, **qosbook flush**, **system flush** and optionally **ip flush**.

SYNTAX:

config flush	[flush_ip = <{no yes}>]
---------------------	--------------------------------------

[flush_ip]	Keep current IP configuration (yes) or not (no). Not keeping the IP settings could cause lost IP connectivity in the LAN. By default IP settings are preserved.	OPTIONAL
---------------------	--	----------

EXAMPLE:

```
=>ip rtlist
  Destination      Source      Gateway      Intf      Mtrc
  10.0.0.0/24      10.0.0.0/24  10.0.0.140  eth0      0
  172.16.0.5/32    0.0.0.0/0   172.16.0.5   cip1      0
  0.0.0.140/32     0.0.0.0/0   10.0.0.140  eth0      0
  127.0.0.1/32     0.0.0.0/0   127.0.0.1    loop      0
  10.0.0.0/24      0.0.0.0/0   10.0.0.140  eth0      0
  172.16.0.0/24    0.0.0.0/0   172.16.0.5   cip1      1
=>config flush flush_ip=no
=>ip rtlist
  Destination      Source      Gateway      Intf      Mtrc
  10.0.0.0/24      10.0.0.0/24  10.0.0.140  eth0      0
  10.0.0.140/32    0.0.0.0/0   10.0.0.140  eth0      0
  127.0.0.1/32     0.0.0.0/0   127.0.0.1    loop      0
  10.0.0.0/24      0.0.0.0/0   10.0.0.140  eth0      0
=>config flush flush_ip=yes
#####
 ALL TCP/IP CONNECTIVITY IS LOST #####
#
```

RELATED COMMANDS:

config erase	Physically remove all saved configurations.
config load	Load complete saved or default configuration.
config reset	Flush current and optionally restore default configuration.
config save	Save current runtime configuration.

config load

Load complete saved or default configuration. Execute **config flush** prior to **config load**.

In case the saved configuration is loaded (defaults=no) this combines all load commands: **atmf load**, **bridge load**, **cip load**, **dhcp client load**, **dhcp server load**, **dns load**, **firewall load**, **firewall rule load**, **mer load**, **nat load**, **phonebook load**, **ppp load**, **pptp load**, **qosbook load**, **system load** and optionally **ip load**.

SYNTAX:

config load	<i>[load_ip = <{no yes}>]</i>
	<i>[defaults = {yes no}]</i>

<i>[load_ip]</i>	Load IP settings (yes) or not (no). Not keeping the IP settings could cause lost IP connectivity in the LAN.	OPTIONAL
<i>[defaults]</i>	Load default configuration (yes) or saved configuration (no). Not specifying this parameter loads the saved configuration	OPTIONAL

EXAMPLE:

```
=>ip rtlist
Destination      Source        Gateway      Intf      Mtrc
10.0.0.0/24      10.0.0.0/24  10.0.0.140  eth0      0
172.16.0.5/32    0.0.0.0/0   172.16.0.5   cip1     0
0.0.0.140/32     0.0.0.0/0   10.0.0.140  eth0     0
127.0.0.1/32     0.0.0.0/0   127.0.0.1   loop     0
10.0.0.0/24      0.0.0.0/0   10.0.0.140  eth0     0
172.16.0.0/24    0.0.0.0/0   172.16.0.5  cip1     1
=>config flush flush_ip=no
=>ip rtlist
Destination      Source        Gateway      Intf      Mtrc
10.0.0.0/24      10.0.0.0/24  10.0.0.140  eth0      0
10.0.0.140/32    0.0.0.0/0   10.0.0.140  eth0     0
127.0.0.1/32     0.0.0.0/0   127.0.0.1   loop     0
10.0.0.0/24      0.0.0.0/0   10.0.0.140  eth0     0
=>config load load_ip=yes
=>ip rtlist
Destination      Source        Gateway      Intf      Mtrc
10.0.0.0/24      10.0.0.0/24  10.0.0.140  eth0      0
10.0.0.140/32    0.0.0.0/0   10.0.0.140  eth0     0
172.16.0.5/32    0.0.0.0/0   172.16.0.5  cip1     0
127.0.0.1/32     0.0.0.0/0   127.0.0.1   loop     0
10.0.0.0/24      0.0.0.0/0   10.0.0.140  eth0     0
172.16.0.0/24    0.0.0.0/0   172.16.0.5  cip1     1
=>
```

RELATED COMMANDS:

config erase	Physically remove all saved configurations.
config flush	Flush complete runtime configuration.
config reset	Flush current and optionally restore default configuration.
config save	Save current runtime configuration.

config reset

Flush current runtime configuration and restore factory default configuration. Optionally the runtime, saved IP configuration can be preserved.

SYNTAX:

config reset	[keep_ip = <{no yes}>]
---------------------	-------------------------------------

[keep_ip]	Keep IP settings (yes) or not (no). Not keeping the IP settings could cause lost IP connectivity in the LAN.	OPTIONAL
-----------	---	----------

EXAMPLE:

```
=>dns list
Domain: business.lan
Nr.      Hostname          IP Address
0       SpeedTouch         *.*.*.*
1       TestHost           10.0.0.140
2       HTTP_Server        10.0.0.8
3       FTP_Server         10.0.0.7
Total Table Size: 73 entries
Amount used: 4 (5%)
=>dns save
=>config reset
=>dns list
Domain: lan
Nr.      Hostname          IP Address
0       SpeedTouch         *.*.*.*
Total Table Size: 73 entries
Amount used: 1 (1%)
=>config flush
=>config load
=>dns list
Domain: business.lan
Nr.      Hostname          IP Address
0       SpeedTouch         *.*.*.*
1       TestHost           10.0.0.140
2       HTTP_Server        10.0.0.8
3       FTP_Server         10.0.0.7
Total Table Size: 73 entries
Amount used: 4 (5%)
=>
```

RELATED COMMANDS:

config erase	Physically remove all saved configurations.
config flush	Flush complete current configuration.
config load	Load complete saved or default configuration.
config save	Save current runtime configuration.

config save

Save all existing configurations and modifications entered by the user.

This combines all save commands: **atmf save**, **bridge save**, **cip save**, **config save**, **dhcp client save**, **dhcp server save**, **dns save**, **firewall chain save**, **firewall save**, **ip save**, **mer save**, **nat save**, **phonebook save**, **ppp save**, **pptp save**, **qosbook save**, **system save**.

SYNTAX:

```
config save
```

EXAMPLE:

```
=>config save  
=>
```

RELATED COMMANDS:

config erase	Physically remove all saved configurations.
config flush	Flush complete current configuration.
config load	Load complete saved or default configuration.
config reset	Flush current and optionally restore default configuration.

6 DHCP Commands

dhcp (to access the DHCP level)
dhcp client (to access the DHCP Client level)
 dhcp client clear
 dhcp client config
 dhcp client flush
 dhcp client ifadd
 dhcp client ifattach
 dhcp client ifconfig
 dhcp client ifdelete
 dhcp client iflist
 dhcp client ifrelease
 dhcp client ifrenew
 dhcp client load
 dhcp client save
 dhcp client stats
dhcp server (to access the DHCP Server level)
 dhcp server add
 dhcp server client
 dhcp server clrstats
 dhcp server config
 dhcp server delete
 dhcp server flush
 dhcp server list
 dhcp server load
 dhcp server policy
 dhcp server save
 dhcp server spoof
 dhcp server start

dhcp server stats
dhcp server status
dhcp server stop
dhcp server troff
dhcp server tron

dhcp client clear

Clear DHCP client statistics.

SYNTAX:

dhcp client clear

EXAMPLE:

```
=>dhcp client stats
DHCP client statistics:
Corrupted packet recv      :          0
OFFERs recv                :          0
ACKs recv                  :          0
NAKs recv                  :          0
Pure BOOTP REPLIES         :          0
Other message types        :          0
DISCOVERs sent           :      253
REQUESTs sent           :          9
DECLINEs sent               :          0
RELEASEs sent               :          0
INFORMs sent                :          0
Number of dynamic interfaces: 1
Memory usage:
Table size of dyn leases: 19,  in use: 1, free: 94 %
=>dhcp client clear
=>dhcp client stats
DHCP client statistics:
Corrupted packet recv      :          0
OFFERs recv                :          0
ACKs recv                  :          0
NAKs recv                  :          0
Pure BOOTP REPLIES         :          0
Other message types        :          0
DISCOVERs sent           :          0
REQUESTs sent           :          0
DECLINEs sent               :          0
RELEASEs sent               :          0
INFORMs sent                :          0
Number of dynamic interfaces: 1
Memory usage:
Table size of dyn leases: 19,  in use: 1, free: 94 %
=>
```

RELATED COMMANDS:

dhcp client stats

Show DHCP client statistics.

dhcp client config

Show/set DHCP client configuration.

SYNTAX:

dhcp client config [trace = <{off on}>]
--

[trace]	Enable tracing (on) or not (off).	OPTIONAL
---------	-----------------------------------	----------

EXAMPLE:

=> dhcp client config tracing:off => dhcp client config trace=on => dhcp client config tracing:on =>
--

RELATED COMMANDS:

dhcp client ifconfig	Configure a DHCP lease created for a specific interface.
-----------------------------	--

dhcp client flush

Flush complete DHCP client configuration and dynamic interfaces.
The flush command does not impact previously saved configurations.

SYNTAX:

```
dhcp client flush
```

EXAMPLE:

```
=>dhcp client iflist
NewMer      : [SELECTING]
    flags= uc
        IP address   : 10.0.0.10
        HW address   : 0:90:d0:01:47:de
        DHCP server   : 255.255.255.255
        hostname     : NewLease
        req.leasetime= 10800 s
        trying to get a lease for 8 min, 32 sec
        transmission of DISCOVER in 57 sec
        retransmission timeout: 64
        nbr of retransmissions: 14
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>dhcp client flush
=>dhcp client iflist
No dynamic interfaces defined.
=>
```

RELATED COMMANDS:

dhcp client load

Load saved or default DHCP client configuration and dynamic interfaces.

dhcp client save

Save current DHCP client configuration and dynamic interfaces.

dhcp client ifadd

Create a DHCP lease for a specific interface.

SYNTAX:

dhcp client ifadd	intf = <interface name>
--------------------------	--------------------------------------

intf	The name of an existing interface, e.g. created via mer ifadd .	REQUIRED
------	--	----------

EXAMPLE:

```
=>dhcp client iflist
No dynamic interfaces defined.
=>dhcp client ifadd intf=NewMer
=>dhcp client iflist
NewMer      : [INIT]
            flags= uc
            IP address   : 0.0.0.0
            HW address   : 00:90:d0:01:47:de
            DHCP server  : 255.255.255.255
Number of leases: 1
Total size of table: 19,  in use: 1, free: 94 %
=>
```

RELATED COMMANDS:

dhcp client ifattach	Attach a DHCP lease to an interface.
dhcp client ifconfig	Configure a DHCP lease created for a specific interface.
dhcp client ifdelete	Delete a dynamic interface.
dhcp client iflist	Show all dynamic interfaces.

dhcp client ifattach

Attach a DHCP lease to a dynamic interface. Firstly create the interface with the **dhcp client ifadd** command.

SYNTAX:

dhcp client ifattach intf = <interface name>

intf	The name of the dynamic interface.	REQUIRED
------	------------------------------------	----------

EXAMPLE:

```
=>dhcp client iflist
NewMer : [INIT]
    flags= uc
    IP address : 0.0.0.0
    HW address : 00:90:d0:01:47:de
    DHCP server : 255.255.255.255
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>dhcp client ifattach intf=NewMer
=>dhcp client iflist
NewMer : [SELECTING]
    flags= uc
    IP address : 10.0.0.10
    HW address : 0:90:d0:01:47:de
    DHCP server : 255.255.255.255
    hostname : NewLease
    req.leasetime= 10800 s
    trying to get a lease for 8 min, 32 sec
    transmission of DISCOVER in 57 sec
    retransmission timeout: 64
    nbr of retransmissions: 14
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>
```

RELATED COMMANDS:

dhcp client ifadd

Create a DHCP lease for a specific interface.

dhcp client ifconfig

Configure a DHCP lease created for a specific interface.

dhcp client ifrelease

Release a lease attached to a dynamic interface.

dhcp client ifconfig

Show/set the configuration of DHCP lease created for a specific interface.

Execute the **dhcp client ifrelease** command prior to configuring it.

SYNTAX:

dhcp client ifconfig	<i>intf = <interface name></i>
	<i>[clientid = <client-id>]</i>
	<i>[hostname = <hostname>]</i>
	<i>[addr = <ip-address>]</i>
	<i>[leasetime = <number>]</i>
	<i>[addrtrans = <{none pat}>]</i>
	<i>[dns = <{off on}>]</i>
	<i>[gateway = <{off on}>]</i>

<i>intf</i>	The name of the dynamic interface to be configured.	REQUIRED
<i>[clientid]</i>	The client identity to be associated with the lease.	OPTIONAL
<i>[hostname]</i>	The host name of the client to be associated with the lease.	OPTIONAL
<i>[addr]</i>	The preferred dynamic IP address.	OPTIONAL
<i>[leasetime]</i>	A number between 0 and 1814400 (seconds). Represents the preferred time the client wants to use an address. By default the leasetime is 7200 seconds (2 hours). Specifying –1 makes the lease permanent.	OPTIONAL
<i>[addrtrans]</i>	Automatically enable address translation for this dynamic interface (pat) or not (none).	OPTIONAL
<i>[dns]</i>	Request (and accept) DNS server IP addresses (on) or not (off).	OPTIONAL
<i>[gateway]</i>	Request (and accept) gateway IP addresses (on) or not (off).	OPTIONAL

EXAMPLE:

```
=>dhcp client iflist
NewMer : [INIT]
    flags= uc
    IP address : 0.0.0.0
    HW address : 00:90:d0:01:47:de
    DHCP server : 255.255.255.255
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>dhcp client ifconfig intf=NewMer hostname=NewLease addr=10.0.0.10 leasetime=10800
=>dhcp client iflist
NewMer : [INIT]
    flags= uc
    IP address : 10.0.0.10
    HW address : 00:90:d0:01:47:de
    DHCP server : 255.255.255.255
    hostname : NewLease
    req.leasetime= 10800 s
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>
```

RELATED COMMANDS:**dhcp client ifadd**

Create a DHCP lease for a specific interface.

dhcp client ifdelete

Delete a dynamic interface.

dhcp client iflist

Show all dynamic interfaces.

dhcp client ifrelease

Release a lease attached to a dynamic interface.

dhcp client ifdelete

Delete a dynamic interface.

SYNTAX:

dhcp client ifdelete	intf = <interface name>
-----------------------------	--------------------------------------

<i>intf</i>	The name of the dynamic interface.	REQUIRED
-------------	------------------------------------	----------

EXAMPLE:

```
=>dhcp client iflist
NewMer    : [SELECTING]
  flags= uc
  IP address   : 10.0.0.10
  HW address   : 0:90:d0:01:47:de
  DHCP server   : 255.255.255.255
  hostname     : NewLease
  req.leasetime= 10800 s
  trying to get a lease for 8 min, 32 sec
  transmission of DISCOVER in 57 sec
  retransmission timeout: 64
  nbr of retransmissions: 14
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>dhcp client ifdelete intf NewMer
=>dhcp client iflist
No dynamic interfaces defined.
=>
```

RELATED COMMANDS:

dhcp client ifadd	Create a DHCP lease for a specific interface.
dhcp client ifattach	Attach a DHCP lease to an interface.
dhcp client ifconfig	Configure a DHCP lease created for a specific interface.
dhcp client iflist	Show all dynamic interfaces.
dhcp client ifrelease	Release a lease attached to a dynamic interface.

dhcp client iflist

Show all dynamic interfaces.

SYNTAX:

```
dhcp client iflist
```

EXAMPLE:

```
=>dhcp client iflist
NewMer : [INIT]
          flags= uc
          IP address : 0.0.0.0
          HW address : 0:90:d0:01:47:de
          DHCP server : 255.255.255.255
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>
```

EXAMPLE INPUT/OUTPUT IN A NETWORKED ENVIRONMENT:

The **SpeedTouch™ Pro with Firewall** is configured as DHCP client on its Ethernet interface eth0.

```
=>dhcp client iflist
eth0 : [BOUND]
          flags= uc
          IP address : 10.0.0.3
          HW address : 00:90:d0:01:47:f1
          DHCP server : 10.10.1.1
          lease renewal in      5 days, 1 h, 26 min, 45 sec
          lease rebinding in    8 days, 20 h, 34 min, 15 sec
          lease expires in     10 days, 2 h, 56 min, 45 sec
Number of leases: 1
Total size of table: 18, in use: 1, free: 94 %
=>dhcp client iflist
eth0 : [BOUND]
          flags= uc
          IP address : 10.0.0.3
          HW address : 00:90:d0:01:47:f1
          DHCP server : 10.10.1.1
          lease renewal in      5 days, 1 h, 25 min, 27 sec
          lease rebinding in    8 days, 20 h, 32 min, 57 sec
          lease expires in     10 days, 2 h, 55 min, 27 sec
Number of leases: 1
Total size of table: 18, in use: 1, free: 94 %
=>
```

RELATED COMMANDS:

dhcp client ifadd

Create a DHCP lease for a specific interface.

dhcp client ifdelete

Delete a dynamic interface.

dhcp client ifrelease

Release a lease attached to a dynamic interface.

SYNTAX:

dhcp client ifrelease intf = <interface name>
--

<i>intf</i>	The name of the dynamic interface.	REQUIRED
-------------	------------------------------------	----------

EXAMPLE:

```
=>dhcp client iflist
NewMer    : [SELECTING]
  flags= uc
  IP address   : 10.0.0.10
  HW address   : 0:90:d0:01:47:de
  DHCP server   : 255.255.255.255
  hostname     : NewLease
  req.leasetime= 10800 s
  trying to get a lease for 8 min, 32 sec
  transmission of DISCOVER in 57 sec
  retransmission timeout: 64
  nbr of retransmissions: 14
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>dhcp client ifattach intf=NewMer
=>dhcp client iflist
NewMer    : [INIT]
  flags= uc
  IP address   : 0.0.0.0
  HW address   : 00:90:d0:01:47:de
  DHCP server   : 255.255.255.255
  hostname     : NewLease
  req.leasetime= 10800 s
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>
```

EXAMPLE INPUT/OUTPUT IN A NETWORKED ENVIRONMENT:

The **SpeedTouch™ Pro with Firewall** is configured as DHCP client on its Ethernet interface eth0.

```
=>dhcp client iflist
eth0      : [BOUND]
          flags= uc
          IP address   : 10.0.0.3
          HW address   : 00:90:d0:01:47:f1
          DHCP server   : 10.10.1.1
          lease renewal in 5 days, 58 min, 48 sec
          lease rebinding in 8 days, 20 h, 6 min, 18 sec
          lease expires in 10 days, 2 h, 28 min, 48 sec
Number of leases: 1
Total size of table: 18, in use: 1, free: 94 %
=>dhcp client stats
DHCP client statistics:
Corrupted packet recv   : 0
DECLINEs sent           : 0
RELEASEs sent           : 0
INFORMs sent            : 0
Number of dynamic interfaces: 1
Memory usage:
Table size of dyn leases: 19, in use: 1, free: 94 %
=>dhcp client ifrelease intf=eth0
=>(CTRL + Q)
=>STATE ACTIVATE !
STATE IDLE !
STATE ACTIVATE !
dhcc: intf 1 releases 10.0.0.3 to server 10.10.1.1.
dhcc: 10.0.0.3 deleted: ok.
STATE IDLE !
STATE ACTIVATE !
.....
dhcc: intf 1 in init state.
n_send() broadcast triggered; To be verified
dhcc: broadcast discover on intf 1.
=>(CTRL + S)
=>dhcp client stats
DHCP client statistics:
Corrupted packet recv   : 0
DECLINEs sent           : 0
RELEASEs sent           : 1
INFORMs sent            : 0
Number of dynamic interfaces: 1
Memory usage:
Table size of dyn leases: 18, in use: 1, free: 94 %
=>
```

RELATED COMMANDS:

dhcp client ifattach
dhcp client ifconfig
dhcp client ifdelete

Attach a DHCP lease to an interface.
 Configure a DHCP lease created for a specific interface.
 Delete a dynamic interface.

dhcp client ifrenew

Renew the lease of a dynamic interface.

SYNTAX:

dhcp client ifrenew intf = <interface name>
--

<i>intf</i>	The name of the dynamic interface.	REQUIRED
-------------	------------------------------------	----------

EXAMPLE:

```
=>dhcp client iflist
NewMer    : [BOUNDED]
  flags = uc
  IP address   : 10.0.0.10
  HW address   : 00:90:d0:01:47:de
  DHCP server   : 255.255.255.255
  hostname     : NewLease
  req.leasetime= 10800s
  lease renewal in 5 days, 58 min, 48 sec
  lease rebinding in 8 days, 20 h, 6 min, 18 sec
  lease expires in 10 days, 2 h, 28 min, 48 sec
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>dhcp client ifrenew intf=NewMer
=>dhcp client iflist
NewMer    : [RENEWING]
  flags = uc
  IP address   : 10.0.0.10
  HW address   : 00:90:d0:01:47:de
  DHCP server   : 255.255.255.255
  hostname     : NewLease
  req.leasetime= 10800 s
  trying to get a lease for 12 sec
  transmission of DISCOVER in 24 sec
  retransmission timeout: 64
  nbr of retransmissions: 11
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>
```

EXAMPLE INPUT/OUTPUT IN A NETWORKED ENVIRONMENT:

The **SpeedTouch™ Pro with Firewall** is configured as DHCP client on its Ethernet interface eth0.

```
=>dhcp client stats
DHCP client statistics:
Corrupted packet recv      :          0
OFFERs recv                :          0
ACKs recv                  :          0
NAKs recv                  :          0
Pure BOOTP REPLIES         :          0
Other message types        :          0
DISCOVERs sent             :          0
REQUESTs sent              :          0
DECLINEs sent               :          0
RELEASEs sent               :          1
INFORMs sent                :          0
Number of dynamic interfaces: 1
Memory usage:
Table size of dyn leases: 18, in use: 1, free: 94 %
=>dhcp client ifrenew intf=eth0
=>dhcp client stats
DHCP client statistics:
Corrupted packet recv      :          0
OFFERs recv                :          1
ACKs recv                  :          1
NAKs recv                  :          0
Pure BOOTP REPLIES         :          0
Other message types        :          0
DISCOVERs sent             :          1
REQUESTs sent              :          1
DECLINEs sent               :          0
RELEASEs sent               :          1
INFORMs sent                :          0
Number of dynamic interfaces: 1
Memory usage:
Table size of dyn leases: 19, in use: 1, free: 94 %
=>(CTRL + Q)
.....
STATE IDLE !
STATE ACTIVATE !
dhcc: intf 1 renews lease 10.0.0.3.
dhcc: intf 1 requests 10.0.0.3 from 10.10.1.1
dhcc: 10.10.1.1 acks 10.0.0.3 to intf 1.
dhcc: lease 10.0.0.3 bound to intf 1.
STATE IDLE !
STATE ACTIVATE !
.....
=>(CTRL + S)
```

RELATED COMMANDS:

dhcp client ifadd

Create a DHCP lease for a specific interface.

dhcp client ifattach

Attach a DHCP lease to an interface.

dhcp client load

Load saved DHCP client configuration and dynamic interfaces.

Execute **dhcp client flush** prior to **dhcp client load**.

SYNTAX:

dhcp client load

EXAMPLE:

```
=>dhcp client iflist
NewMer      : [SELECTING]
    flags = uc
    IP address   : 10.0.0.10
    HW address   : 00:90:d0:01:47:de
    DHCP server   : 255.255.255.255
    hostname     : NewLease
    req.leasetime= 10800s
    trying to get a lease for 8 min, 32 sec
    transmission of DISCOVER in 57 sec
    retransmission timeout: 64
    nbr of retransmissions: 14
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>dhcp client save
=>dhcp client flush
=>dhcp client iflist
No dynamic interfaces defined.
=>dhcp client load
=>dhcp client iflist
NewMer      : [REBOOTING]
    flags = uc
    IP address   : 10.0.0.10
    HW address   : 00:90:d0:01:47:de
    DHCP server   : 255.255.255.255
    hostname     : NewLease
    req.leasetime= 10800s
    trying to get a lease for 2 sec
    transmission of REQUEST in 2 sec
    retransmission timeout: 4
    retransmissions left before reinitializing : 2
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>
```

RELATED COMMANDS:

dhcp client flush

Delete all dynamic interfaces.

dhcp client save

Save current DHCP client configuration and dynamic interfaces.

dhcp client save

Save current DHCP client configuration and dynamic interfaces.

SYNTAX:

```
dhcp client save
```

EXAMPLE:

```
=>dhcp client iflist
NewMer      : [SELECTING]
    flags = uc
        IP address      : 10.0.0.10
        HW address      : 00:90:d0:01:47:de
        DHCP server     : 255.255.255.255
        hostname        : NewLease
        req.leasetime= 10800s
        trying to get a lease for 8 min, 32 sec
        transmission of DISCOVER in 57 sec
        retransmission timeout: 64
        nbr of retransmissions: 14
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>dhcp client save
=>dhcp client flush
=>dhcp client iflist
No dynamic interfaces defined.
=>dhcp client load
=>dhcp client iflist
NewMer      : [REBOOTING]
    flags = uc
        IP address      : 10.0.0.10
        HW address      : 00:90:d0:01:47:de
        DHCP server     : 255.255.255.255
        hostname        : NewLease
        req.leasetime= 10800s
        trying to get a lease for 2 sec
        transmission of REQUEST in 2 sec
        retransmission timeout: 4
        retransmissions left before reinitializing : 2
Number of leases: 1
Total size of table: 19, in use: 1, free: 94 %
=>
```

RELATED COMMANDS:

dhcp client flush
dhcp client load

Flush complete DHCP client configuration and dynamic interfaces.
Load saved or default DHCP client configuration and dynamic interfaces.

dhcp client stats

Show DHCP client statistics.

SYNTAX:

```
dhcp client stats
```

EXAMPLE:

```
=>dhcp client stats
DHCP client statistics:
Corrupted packet recv      :          0
OFFERs recv                :          1
ACKs recv                  :          1
NAKs recv                  :          0
Pure BOOTP REPLIES         :          0
Other message types        :          0
DISCOVERs sent           :    244
REQUESTs sent           :          9
DECLINEs sent               :          0
RELEASEs sent               :          0
INFORMs sent                :          0
Number of dynamic interfaces: 1
Memory usage:
Table size of dyn leases: 19,   in use: 1, free: 94 %
=>
```

RELATED COMMANDS:

dhcp client clear Clear DHCP client statistics.

dhcp server add

Assign a static IP address to a host in the local network. This address is allocated on a permanent basis, and is excluded from the pool of addresses used by the **SpeedTouch™ Pro with Firewall** DHCP server.

SYNTAX:

```
dhcp server add    clientid = <client-id>
                      addr = <ip-address>
                      [leasetime = <number>]
                      [hostname = <hostname>]
```

<i>clientid</i>	The DHCP client's MAC address.	REQUIRED
<i>addr</i>	The IP address for this DHCP host.	REQUIRED
[<i>leasetime</i>]	A number between 0 and 1814400 (seconds). Represents the preferred time the client wants to use an address. By default the leasetime is 7200 seconds (2 hours). Specifying -1 makes the lease permanent.	OPTIONAL
[<i>hostname</i>]	The hostname to add to the local DNS table for this host.	OPTIONAL

EXAMPLE:

```
=>dhcp server list
Leases:
Lease 0: 01:00:A0:24:AE:66:E1
      Hostname = Default
      ip address : 10.0.0.8
      expires in : 1 h, 16 min, 20 sec
      lease is being used.
Total size of table: 36, in use: 1 free: 97 %
=>dhcp server add clientid=01:23:45:67:89:ab addr=10.0.0.1 leasetime=60 hostname>NewLease
=>dhcp server list
Leases:
Lease 0: 01:00:A0:24:AE:66:E1
      Hostname = Default
      ip address : 10.0.0.8
      expires in : 1 h, 15 min, 32 sec
      lease is being used.
Lease 1: 01:23:45:67:89:AB
      Hostname = NewLease
      ip address : 10.0.0.1
      expires in : 23 sec
      lease is being used.
Total size of table: 36, in use: 2 free: 94 %
=>
```

RELATED COMMANDS:

dhcp server delete	Delete a DHCP lease.
dhcp server list	Show current DHCP leases.

dhcp server client

Set the AutoDHCP client time-out in startup phase. Only applicable in AutoDHCP mode (See **dhcp server policy** command).

SYNTAX:

dhcp server client timeout = <number>

<i>timeout</i>	A number between 0 and 1814400 (seconds). Represents the time to look for another DHCP server. Specifying '-1' will make the timeout infinite: the SpeedTouch™ Pro with Firewall will remain client. By default the timeout is 20 seconds.	REQUIRED
----------------	--	----------

EXAMPLE:

```
=>dhcp server status
DHCP Server Status:      Running
Current configuration:
    Address Range: 10.0.0.1 ... 10.255.255.254
.....
Start-up client parameters:
    Timeout: 20 sec
Tracing: off
Memory usage:
    Leases: total: 36, in use: 7 free: 80 %
=>dhcp server client timeout=15
=>dhcp server status
DHCP Server Status:      Running
Current configuration:
    Address Range: 10.0.0.1 ... 10.255.255.254
.....
Start-up client parameters:
    Timeout: 15 sec
Tracing: off
Memory usage:
    Leases: total: 36, in use: 7 free: 80 %
=>
```

RELATED COMMANDS:

dhcp server policy	Set DHCP server policy.
dhcp server start	Start DHCP server.
dhcp server status	Show current DHCP server configuration.
dhcp server stop	Stop DHCP server.

dhcp server clrstats

Clear SpeedTouch™ Pro with Firewall DHCP server statistics.

SYNTAX:

dhcp server clrstats

EXAMPLE:

<pre>=>dhcp server stats DHCP server statistics: Corrupted packet recv : 0 DISCOVER : 9575 REQUEST : 121 DECLINE : 0 RELEASE : 0 INFORM : 13 Pure BOOTP REQUESTS : 2 Other message types : 0 OFFERs sent : 9552 ACKs sent : 121 NAKs sent : 0 Lease table got full : no Ping table got full : no Second DHCP server seen : no =>dhcp server clrstats =>dhcp server stats DHCP server statistics: Corrupted packet recv : 0 DISCOVER : 0 REQUEST : 0 DECLINE : 0 RELEASE : 0 INFORM : 0 Pure BOOTP REQUESTS : 0 Other message types : 0 OFFERs sent : 0 ACKs sent : 0 NAKs sent : 0 Lease table got full : no Ping table got full : no Second DHCP server seen : no =></pre>
--

RELATED COMMANDS:

dhcp server stats

Show DHCP server statistics.

dhcp server config

Set **SpeedTouch™ Pro with Firewall** DHCP server configuration.

Execute **dhcp server status** to see the actual status and configuration.

SYNTAX:

dhcp server config	<i>[beginrange = <ip-address>] [endrange = <ip-address>] [netmask = <ip-address>] [leasetime = <number>] [gateway = <ip-address 0>] [dnsaddr = <ip-address>]</i>
---------------------------	--

beginrange	The lowest IP address in the DHCP address range to use for leasing. Default value of this parameter is 10.0.0.1.	OPTIONAL
endrange	The highest IP address in the DHCP address range to use for leasing. Default value of this parameter is 10.255.255.254.	OPTIONAL
netmask	The applicable netmask for the DHCP leases.	OPTIONAL
leasetime	A number between 0 and 1814400 (seconds). Represents the time for which a client can use its dynamically allocated IP address. By default the leasetime is 2 hours (7200 seconds). Specifying –1 makes the lease permanent.	OPTIONAL
gateway	The IP address of the gateway for DHCP clients.	OPTIONAL
dnsaddr	The IP address of the DNS server for DHCP clients. Entering '0' sets the SpeedTouch™ Pro with Firewall as DNS server.	OPTIONAL

EXAMPLE:

```
=>dhcp server status
DHCP Server Status:      Running
Current configuration:
    Address Range:  10.0.0.1 ... 10.255.255.254
    Netmask:255.0.0.0
    Lease time: 10800 seconds
    Gateway (default router): 10.0.0.138
    DNS server: 10.0.0.1
    Domain name: lan
Policies:
    Verify first: no
    Trust client: yes
    Spoofing: no
    Start as client:yes
Spoofing parameters:
    Failure timeout (!DoD): 4 sec
    Failure lease time (!DoD): 60 sec
    Temp. lease time (DoD): 10 sec
Start-up client parameters:
    Timeout: 15 sec
Tracing:off
Memory usage:
    Leases: total: 36, in use: 7 free: 80 %
=>dhcp server config beginrange=172.16.0.2endrange=172.16.0.122netmask=255.0.0.0
    leasetime=21600 gateway=172.16.0.1 dnsaddr=172.16.0.254
=>dhcp server status
DHCP Server Status:      Running
Current configuration:
    Address Range: 172.16.0.2 ... 172.16.0.122
    Netmask:255.0.0.0
    Lease time: 21600 seconds
    Gateway (default router): 172.16.0.1
    DNS server: 172.16.0.254
    Domain name: lan
Policies:
    Verify first: no
    Trust client: yes
    Spoofing: no
    Start as client:yes
Spoofing parameters:
    Failure timeout (!DoD): 4 sec
    Failure lease time (!DoD): 60 sec
    Temp. lease time (DoD): 10 sec
Start-up client parameters:
    Timeout: 15 sec
Tracing:off
Memory usage:
    Leases: total: 36, in use: 7 free: 80 %
=>
```

RELATED COMMANDS:

dhcp server status Show current DHCP server configuration.

dhcp server delete

Delete a DHCP lease.

SYNTAX:

```
dhcp server delete index = <number>
```

index	The index number of the entry to be deleted.	REQUIRED
	Execute dhcp server list to see a list of the index numbers of all current DHCP leases.	

EXAMPLE:

```
=>dhcp server list
Leases:
Lease 0: 01:00:A0:24:AE:66:E1
    Hostname = Default
    ip address : 10.0.0.8
    expires in : 1 h, 16 min, 20 sec
    lease is being used.
Lease 1: 01:23:45:67:89:AB
    Hostname = NewLease
    ip address : 10.0.0.1
    expires in : 23 sec
    lease is being used.
Total size of table: 36, in use: 2 free: 94 %
=>dhcp server delete index=1
=>dhcp server list
Leases:
Lease 0: 01:00:A0:24:AE:66:E1
    Hostname = Default
    ip address : 10.0.0.8
    expires in : 1 h, 15 min, 32 sec
    lease is being used.
Total size of table: 36, in use: 1 free: 97 %
=>
```

RELATED COMMANDS:

dhcp server add	Add a DHCP lease manually.
dhcp server list	Show current DHCP leases.

dhcp server flush

Flush complete DHCP server configuration and dynamic leases.

The flush command does not impact previously saved configurations.

SYNTAX:

dhcp server flush

EXAMPLE:

```
=>dhcp server list
Leases:
Lease 2: 01:52:41:53:20:A0:1B:A7:EB:AD:3C:C0:01:01:00:00:00
    ip address: 10.0.7.79
    expires in: 11 sec
    lease is not being used.
Lease 1: 01:52:41:53:20:20:4D:0D:CB:03:40:C0:01:01:00:00:00
    ip address: 10.0.7.62
    Spoofed lease from 2: DHCP_SPOOF
    Assigned (temporary) private ip address.
    expires in: 1 min, 39 sec
    lease is not being used.
Lease 0: 01:00:A0:24:AE:66:E1
    Hostname = Default
    ip address : 10.0.0.8
    expires in : 1 h, 16 min, 20 sec
    lease is being used.
Lease 3: 01:23:55:67:89:AB
    Hostname = Tempo
    ip address : 10.0.0.1
    never expires!
    lease is not being used.
Total size of table: 36, in use: 4 free: 89 %
=>dhcp server flush
=>dhcp server list
No active leases
Total size of table: 36, in use: 0 free: 100 %
=>
```

RELATED COMMANDS:

dhcp server load	Load saved or default DHCP server configuration and permanent leases.
dhcp server save	Save current DHCP server configuration and permanent leases.

dhcp server list

List current DHCP leases, indicated by their index number.

SYNTAX:

dhcp server list

EXAMPLE OUTPUT:

=> dhcp server list
Leases:
Lease 2: 01:52:41:53:20:50:6D:C0:40:02:32:C0:01:01:00:00:00 ip address: 10.0.7.142 expires in: 3 sec lease is not being used.
Lease 3: 01:52:41:53:20:A0:1B:A7:EB:AD:3C:C0:01:01:00:00:00 ip address: 10.0.7.143 expires in: 17 sec lease is not being used.
Lease 5: 01:52:41:53:20:F0:90:8F:09:E1:35:BE:01:01:00:00:00 ip address: 10.0.7.144 expires in: 55 sec lease is not being used.
Lease 6: 01:52:41:53:20:30:F4:89:5F:9B:44:C0:01:01:00:00:00 ip address: 10.0.7.145 expires in: 1 min, 6 sec lease is not being used.
Lease 1: 01:52:41:53:20:20:4D:0D:CB:03:40:C0:01:01:00:00:00 ip address: 10.0.7.62 Spoofed lease from 2: DHCP_SPOOF Assigned (temporary) private ip address. expires in: 1 min, 57 sec lease is not being used.
Lease 0: 01:00:A0:24:AE:66:E1 Hostname= Default ip address: 10.0.0.8 expires in: 1 h, 17 min, 21 sec lease is being used.
Lease 4: 01:23:55:67:89:AB Hostname = Tempo ip address : 10.0.0.1 never expires! lease is not being used.
Total size of table: 36, in use: 7 free: 80 %
=>

RELATED COMMANDS:

dhcp server add	Add a DHCP lease manually.
dhcp server delete	Delete a DHCP lease.
dhcp server flush	Delete complete DHCP server configuration and dynamic leases.

dhcp server load

Load saved (or default) DHCP server configuration and permanent leases.

SYNTAX:

dhcp server load	[defaults = <yes no>]
-------------------------	------------------------------------

[defaults]	Load factory defaults (yes) or saved configuration (no). Not specifying this parameter loads the saved configuration.	OPTIONAL
------------	--	----------

EXAMPLE:

```
=>dhcp server list
Leases:
Lease 1: 01:52:41:53:20:20:4D:0D:CB:03:40:C0:01:01:00:00:00
    ip address: 10.0.7.62
    Spoofed lease from 2: DHCP_SPOOF
    Assigned (temporary) private ip address.
    expires in: 1 min, 57 sec
    lease is being used.
Lease 0: 01:00:A0:24:AE:66:E1
    Hostname= Default
    ip address: 10.0.0.8
    expires in: 1 h, 17 min, 21 sec
    lease is being used.
Lease 4: 01:23:55:67:89:AB
    Hostname = Tempo
    ip address : 10.0.0.1
    never expires!
    lease is being used.
Total size of table: 36, in use: 3 free: 92 %
=>dhcp server save
=>dhcp server flush
=>dhcp server load
=>dhcp server list
Leases:
Lease 4: 01:23:55:67:89:AB
    Hostname = Tempo
    ip address : 10.0.0.1
    never expires!
    lease is not being used.
Total size of table: 36, in use: 1 free: 97 %
=>
```

RELATED COMMANDS:

dhcp server flush	Flush current DHCP server configuration and dynamic leases.
dhcp server load	Load saved or default DHCP server configuration and permanent leases.

dhcp server policy

Set **SpeedTouch™ Pro with Firewall** DHCP server policy.

SYNTAX:

dhcp server policy	<i>[verifyfirst = <yes no>] [trustclient = <yes no>] [spoofing = <yes no>] [client = <yes no>]</i>
---------------------------	--

<i>[verifyfirst]</i>	Probe the network for conflicting IP addresses before giving a suggested IP address to the requesting DHCP client (yes) or not (no).	OPTIONAL
<i>[trustclient]</i>	Take the IP address suggested by a DHCP client into account (yes) or not (no).	OPTIONAL
<i>[spoofing]</i>	Allow a remote DHCP server to hand out IP addresses negotiated by PPP on WAN side (yes) or not (no). DHCP spoofing is used to relay local DHCP requests to an external PPP connection having a specific IP address negotiation mechanism. DHCP replies are in turn generated by the DHCP server based on the IP address information received by the PPP link.	OPTIONAL
<i>[client]</i>	Allow the SpeedTouch™ Pro with Firewall DHCP server to present itself as DHCP client (AutoDHCP mode) at boot time and probe for another DHCP server on the network for some time before starting the DHCP server (yes) or immediately start the DHCP server (no).	OPTIONAL

EXAMPLE:

```
=>dhcp server status
DHCP Server Status:      Running
Current configuration:
.....
Policies:
    Verify first: no
    Trust client: yes
    Spoofing: no
    Start as client:yes
.....
=>dhcp server policy verifyfirst=yes trustclient=no spoofing=yes client=no
=>dhcp server status
DHCP Server Status:      Running
Current configuration:
.....
Policies:
    Verify first:yeso
    Trust client: no
    Spoofing: yes
    Start as client:no
.....
=>
```

RELATED COMMANDS:

dhcp server status Show current DHCP server configuration.

dhcp server save

Save complete **SpeedTouch™ Pro with Firewall** DHCP server configuration and permanent DHCP leases.

SYNTAX:

```
dhcp server save
```

EXAMPLE:

```
=>dhcp server list
Leases:
Lease 0: 01:00:A0:24:AE:66:E1
    Hostname= Default
    ip address: 10.0.0.8
    expires in: 1 h, 57 min, 9 sec
    lease is being used.
Lease 1: 01:23:55:67:89:AB
    Hostname= Tempo
    ip address: 10.0.0.1
    never expires!
    lease is not being used.
Total size of table: 36, in use: 2 free: 94 %
=>dhcp server save
=>dhcp server flush
=>dhcp server list
No active leases
Total size of table: 36, in use: 0 free: 100 %
=>dhcp server load defaults=no
=>dhcp server list
Leases:
Lease 0: 01:00:A0:24:AE:66:E1
    Hostname= Default
    ip address: 10.0.0.8
    expires in: 1 h, 58 min, 55 sec
    lease is being used.
Lease 1: 01:23:55:67:89:AB
    Hostname= Tempo
    ip address: 10.0.0.1
    never expires!
    lease is not being used.
Total size of table: 36, in use: 2 free: 94 %
=>
```

RELATED COMMANDS:

dhcp server flush
dhcp server load

Flush complete DHCP server configuration and dynamic leases
Load saved or default DHCP server configuration and permanent leases.

dhcp server spoof

Set DHCP spoofing parameters. Only applicable in case of a PPP-to-DHCP Spoofing connection.
(See **dhcp server policy** command).

SYNTAX:

dhcp server spoof	[failtime = <number>]
	[errorlt = <number>]
	[dodlt = <number>]

[failtime]	A number between 0 and 1814400 (seconds). Represents the time to wait for a PPP link to successfully negotiate an IP address. This parameter determines how long the SpeedTouch™ Pro with Firewall should try to set up a PPP connection before returning to normal DHCP mode, i.e. in case the PPP connection cannot be established within the time lapse determined by failtime, the SpeedTouch™ Pro with Firewall DHCP server will allocate an local private IP address to the DHCP client. By default the failtime is 4 seconds.	OPTIONAL
[errorlt]	A number between 0 and 1814400 (seconds). Represents the leasetime of the private address issued when a PPP link fails. In case the PPP link fails after failtime has elapsed, this parameter determines how long the private DHCP lease must be maintained before retrying to set up the PPP link again. By default the error lease time is 60 seconds.	OPTIONAL
[dodlt]	A number between 0 and 1814400 (seconds). Represents the leasetime of the temporary private IP address in case of a dial-on-demand PPP link. In case of a dial-on-demand PPP link, this parameter determines the interval at which the temporary DHCP lease must be maintained before checking whether a public IP address negotiated by a triggered PPP link is available. By default the dial-on-demand lease time is 10 seconds.	OPTIONAL

EXAMPLE:

```
=>dhcp server status
DHCP Server Status: Running
Current configuration:
.....
Spoofing parameters:
    Failure timeout (!DoD): 4 sec
    Failure lease time (!DoD): 60 sec
    Temp. lease time (DoD): 10 sec
.....
=>dhcp server spoof failtime=8 errorlt=120 dodlt=20
=>dhcp server status
DHCP Server Status: Running
Current configuration:
.....
Spoofing parameters:
    Failure timeout (!DoD): 8 sec
    Failure lease time (!DoD): 120 sec
    Temp. lease time (DoD): 20 sec
.....
=>
```

RELATED COMMANDS:

dhcp server policy
dhcp server status

Set DHCP server policy.
Show current DHCP server configuration.

dhcp server start

Start SpeedTouch™ Pro with Firewall DHCP server.

SYNTAX:

```
dhcp server start
```

EXAMPLE:

```
=>dhcp server status  
DHCP Server Status: Stopped  
Current configuration:  
.....  
=>dhcp server start  
=>dhcp server status  
DHCP Server Status: Searching for server...  
Current configuration:  
.....  
=>  
=>dhcp server status  
DHCP Server Status: Running  
Current configuration:  
.....  
=>
```

RELATED COMMANDS:

dhcp server status	Show current DHCP server configuration.
dhcp server stop	Stop DHCP server.

dhcp server stats

Show SpeedTouch™ Pro with Firewall DHCP server statistics.

SYNTAX:

```
dhcp server stats
```

EXAMPLE OUTPUT:

```
=>dhcp server stats
DHCP server statistics:
Corrupted packet recv      :          0
DISCOVER                   :      9575
REQUEST                    :       121
DECLINE                    :          0
RELEASE                    :          0
INFORM                     :        13
Pure BOOTP REQUESTS       :          2
Other message types       :          0
OFFERs sent                :      9552
ACKs sent                  :       121
NAKs sent                  :          0
Lease table got full     : no
Ping table got full      : no
Second DHCP server seen   : no
=>
```

DESCRIPTION:

<i>Corrupted packet recv</i>	Indicates the number of corrupted packets (not complaint to RFC2131) were received from the LAN.
<i>DISCOVER</i>	Indicates the number of DHCP server discovery packets were received from the LAN. These broadcasts are sent by potential DHCP clients to locate available DHCP servers.
<i>REQUEST</i>	Indicates the number of DHCP address lease requests were received from the LAN.
<i>DECLINE</i>	Indicates the number of DHCP address lease requests that were declined.
<i>RELEASE</i>	Indicates the number of DHCP address release requests that were received from DHCP clients.
<i>INFORM</i>	Indicates the number of information requests that were received from DHCP clients.
<i>Pure BOOTP requests</i>	Indicates the number of BOOTP requests that were received from the LAN.
<i>OFFERs sent</i>	Indicates the number of IP address offers were sent in reply to DHCP requests.

ACKs sent	Indicates the number of ACKnowledgement replies were sent to successfully configured DHCP clients.
NAKs sent	Indicates the number of Not-Acknowledgement replies were sent to wrongly configured DHCP clients.
Lease table got full	Indicates whether the maximum number of DHCP leases is reached or not.
Ping table got full	Indicates whether the history list of IP address pings got full or not. These pings are sent by the SpeedTouch™ Pro with Firewall DHCP server to verify whether the IP address is already in use on the LAN or not. (dhcp server policy verifyfirst=yes)
Second DHCP server seen	Indicates whether a concurrent DHCP server was found on the LAN or not.

RELATED COMMANDS:

dhcp server clrstats Clear DHCP server statistics.

dhcp server status

Show current DHCP server configuration.

SYNTAX:

```
dhcp server status
```

EXAMPLE:

```
=>dhcp server status
DHCP Server Status: Client
Current configuration:
    Address Range: 10.0.0.1 ... 10.255.255.254
    Netmask:255.0.0.0
    Lease time: 7200 seconds
    Gateway (default router): 10.0.0.1 (auto)
    DNS server: 10.0.0.1 (auto)
    Domain name: office.lan
Policies:
    Verify first: no
    Trust client: yes
    Spoofing: no
    Start as client:yes
Spoofing parameters:
    Failure timeout (!DoD): 4 sec
    Failure lease time (!DoD): 60 sec
    Temp. lease time (DoD): 10 sec
Start-up client parameters:
    Timeout: 20 sec
Tracing:off
Memory usage:
    Leases: total: 36, in use: 7 free: 80 %
=>
```

RELATED COMMANDS:

dhcp server stop	Stop DHCP server.
dhcp server start	Start DHCP server.
dhcp server policy	Set DHCP server policy.
dhcp server spoofing	Set spoofing parameters.

dhcp server stop

Stop SpeedTouch™ Pro with Firewall DHCP server.

SYNTAX:

```
dhcp server stop
```

EXAMPLE:

```
=>dhcp server status
DHCP Server Status: Running
Current configuration:
.....
=>dhcp server stop
=>dhcp server status
DHCP Server Status: Stopped
Current configuration:
.....
=>
```

RELATED COMMANDS:

dhcp server start

Start DHCP server.

dhcp server status

Show current DHCP server configuration.

dhcp server troff

Disable verbose console logging. No debug traces are generated anymore.

SYNTAX:

```
dhcp server troff
```

EXAMPLE:

```
=>dhcp server status
DHCP Server Status:      Running
Current configuration:
.....
Tracing:on
.....
=>dhcp server troff
=>dhcp server status
DHCP Server Status:      Running
Current configuration:
.....
Tracing:off
.....
=>
```

RELATED COMMANDS:

dhcp server status

Show current DHCP server configuration.

dhcp server tron

Enable verbose console logging.

dhcp server tron

Enable verbose console logging. Debug traces are generated.

SYNTAX:

```
dhcp server tron
```

EXAMPLE:

```
=>dhcp server status
DHCP Server Status:      Running
Current configuration:
.....
Tracing:off
.....
=>dhcp server tron
=>dhcp server status
DHCP Server Status:      Running
Current configuration:
.....
Tracing:on
.....
=>
```

RELATED COMMANDS:

dhcp server status
dhcp server troff

Show current DHCP server configuration
Disable verbose console logging.

7 DNS Commands

dns (to access the DNS level)
dns add
dns clear
dns clrstats
dns delete
dns domain
dns flush
dns fwdadd
dns fwddel
dns fwdlist
dns fwdtable
dns list
dns load
dns nslookup
dns save
dns start
dns stats
dns status
dns stop
dns toutfwd
dns troff
dns tron

dns add

Add a static DNS entry for IP hosts who do not reveal their hostname in the DHCP request, or even worse, not support DHCP.

SYNTAX:

dns add	hostname = <string>
	[addr = <ip-address>]

hostname The name of the IP host (without the (sub)domain name). **REQUIRED**

[addr] The IP address of the host (without mask). **OPTIONAL**
In case this parameter is not specified the hostname applies to the
SpeedTouch™ Pro with Firewall itself.

EXAMPLE:

```
=>dns list
Domain: business.lan
Nr.      Hostname          IP Address
0       SpeedTouch         *.*.*.*
1       TestHost           10.0.0.140
2       HTTP_Server        10.0.0.8
Total Table Size: 73 entries
Amount used: 3 (4%)
=>dns add hostname=FTP_Server addr=10.0.0.7
=>dns list
Domain: business.lan
Nr.      Hostname          IP Address
0       SpeedTouch         *.*.*.*
1       TestHost           10.0.0.140
2       HTTP_Server        10.0.0.8
3       FTP_Server         10.0.0.7
Total Table Size: 73 entries
Amount used: 4 (5%)
=>
```

RELATED COMMANDS:

dns list	List current DNS entries.
dns delete	Delete a DNS entry.

dns clear

Delete current DNS entries.

SYNTAX:

```
dns clear
```

EXAMPLE:

```
=>dns list
Domain: business.lan
Nr.      Hostname          IP Address
0       SpeedTouch        *.*.*.*
1       TestHost           10.0.0.140
2       HTTP_Server        10.0.0.8
3       FTP_Server         10.0.0.7
Total Table Size: 73 entries
Amount used: 4 (5%)
=>dns clear
=>dns list
Domain: business.lan
Nr.      Hostname          IP Address
Total Table Size: 73 entries
Amount used: 0 (0%)
=>
```

RELATED COMMANDS:

dns list List current DNS entries.

dns clrstats

Clear DNS statistics.

SYNTAX:

dns clrstats

EXAMPLE:

```
=>dns stats
DNS Statistics:
Corrupted packets recv      :          0
Local questions resolved    :          0
Local neg answers sent      :          4
Total DNS packets fwd       :          0
External answers recv       :          0
Fwd table full, discard    :          0
Spurious answers            :          0
Unknown query types         :          0

Total number of packets received :          4

=>dns clrstats
DNS statistics cleared.
=>dns stats
DNS Statistics:
Corrupted packets recv      :          0
Local questions resolved    :          0
Local neg answers sent      :          0
Total DNS packets fwd       :          0
External answers recv       :          0
Fwd table full, discard    :          0
Spurious answers            :          0
Unknown query types         :          0

Total number of packets received :          0

=>
```

RELATED COMMANDS:

dns stats Show DNS server/forwarder statistics.

dns delete

Delete a DNS entry.

SYNTAX:

dns delete	index = <number>
-------------------	-------------------------------

index	The index number of the entry to be deleted. Execute dns list to see a list of the index numbers of all current DNS entries.	REQUIRED
-------	--	----------

EXAMPLE:

```
=>dns list
Domain: business.lan
Nr.      Hostname          IP Address
0       SpeedTouch        *.*.*.*
1       TestHost           10.0.0.140
2       HTTP_Server        10.0.0.8
3       FTP_Server          10.0.0.7
Total Table Size: 73 entries
Amount used: 4 (5%)
=>dns delete index=2
=>dns list
Domain: business.lan
Nr.      Hostname          IP Address
0       SpeedTouch        *.*.*.*
1       TestHost           10.0.0.140
3       FTP_Server          10.0.0.7
Total Table Size: 73 entries
Amount used: 3 (4%)
=>
```

RELATED COMMANDS:

dns add	Add a static DNS entry.
dns list	List current DNS entries.

dns domain

Set local DNS (sub)domain name.

SYNTAX:

dns domain	domain = <string>
-------------------	--------------------------------

<i>domain</i>	The local DNS (sub)domain name.	REQUIRED
---------------	---------------------------------	----------

EXAMPLE:

```
=>dns list
Domain: business.lan
Nr.      Hostname          IP Address
0       SpeedTouch         *.*.*.*
1       TestHost           10.0.0.140
2       HTTP_Server        10.0.0.8
3       FTP_Server         10.0.0.7
Total Table Size: 73 entries
Amount used: 4 (5%)
=>dns domain domain=office.home.lan
=>dns list
Domain: office.home.lan
Nr.      Hostname          IP Address
0       SpeedTouch         *.*.*.*
1       TestHost           10.0.0.140
2       HTTP_Server        10.0.0.8
3       FTP_Server         10.0.0.7
Total Table Size: 73 entries
Amount used: 4 (5%)
```

RELATED COMMANDS:

dns list	List current DNS entries.
-----------------	---------------------------

dns flush

Flush complete **SpeedTouch™ Pro with Firewall** DNS server/forwarder configuration and static entries.

The flush command does not impact previously saved configurations.

SYNTAX:

```
dns flush
```

EXAMPLE:

```
=>dns list
Domain: office.home.lan
Nr.      Hostname          IP Address
4*      Z7V1D8            10.0.0.29
0       SpeedTouch         *.*.*.*
1       TestHost           10.0.0.140
2       Default            10.0.0.8
3       ftpserver          172.16.0.1
Total Table Size: 73 entries
Amount used: 5 (6%)
=>dns flush
=>dns list
Domain: lan
Nr.      Hostname          IP Address
3*      Z7V1D8            10.0.0.29
Total Table Size: 73 entries
Amount used: 1 (1%)
=>
```

RELATED COMMANDS:

dns save

Save current DNS server/forwarder configuration and static entries.

dns load

Load saved or default DNS server/forwarder configuration and static entries.

dns fwdadd

Add a DNS forwarding entry. The entries in the forwarding list determine which DNS server should be used for which PC. If an identification cannot be established within the local LAN, the request is forwarded to another DNS server, on another network (Internet/LAN to LAN connection). The connection is negotiated within a PPP link.

SYNTAX:

dns fwdadd	<i>dns = <ip-address></i>
	<i>src = <ip-address></i>
	<i>mask = <ip-mask (dotted or cidr)></i>
	<i>[direct = <number>]</i>

<i>dns</i>	The IP address of the (remote) DNS server.	REQUIRED
<i>src</i>	The source IP address (pool) of the host(s) using this DNS server.	REQUIRED
<i>mask</i>	The appropriate source IP (sub)netmask.	REQUIRED
<i>[direct]</i>	Determines whether DNS replies are sent directly back to the client (1) or relayed by the SpeedTouch™ Pro with Firewall DHCP server's DNS forwarder (0) in case of PPP-to-DHCP spoofing connections.	OPTIONAL

EXAMPLE:

```
=>dns fwdlist
DNS forwarding servers:
DNS           SRC          MASK          Direct
10.0.0.138    10.0.0.2    255.255.255.0  yes
=>dns fwdadd dns=10.0.0.138 src=10.0.0.3 mask=24 direct=1
Dns forwarding server added.
=>dns fwdlist
DNS forwarding servers:
DNS           SRC          MASK          Direct
10.0.0.138    10.0.0.2    255.255.255.0  yes
10.0.0.138    10.0.0.3    255.255.255.0  yes
=>
```

RELATED COMMANDS:

dns fwddelete	Delete a DNS forwarding entry.
dns fwlist	Show current DNS forwarding entries.

dns fwddelete

Delete a DNS forwarding entry.

SYNTAX:

dns fwddelete	src = <ip-address>
	mask = <ip-mask (dotted or cidr)>
	[dns = <ip-address>]

src	The source IP address (pool) of the hosts to remove the entry for.	REQUIRED
mask	The source IP (sub)netmask.	REQUIRED
[dns]	The IP address of the (remote) DNS server (in case of multiple DNS server entries).	OPTIONAL

EXAMPLE:

```
=>dns fwdlist
DNS forwarding servers:
DNS           SRC          MASK          Direct
10.0.0.138    10.0.0.0    255.255.255.0  yes
192.6.11.150  192.6.11.0  255.255.255.0  yes
=>dns fwddelete src=192.6.11.0 mask=24 dns=192.6.11.150
Dns forwarding server deleted.
=>dns fwdlist
DNS forwarding servers:
DNS           SRC          MASK          Direct
10.0.0.138    10.0.0.0    255.255.255.0  yes
=>
```

RELATED COMMANDS:

dns fwdadd	Add a DNS forwarding entry.
dns fwlist	Show current DNS forwarding entries.

dns fwdlist

Show current DNS forwarding entries.

SYNTAX:

```
dns fwdlist
```

EXAMPLE OUTPUT:

```
=>dns fwdlist
DNS forwarding servers:
DNS           SRC          MASK        Direct
10.0.0.138   10.0.0.0    255.255.255.0  yes
192.6.11.150 192.6.11.0  255.255.255.0  yes
=>
```

RELATED COMMANDS:

dns fwdadd	Add a DNS forwarding entry.
dns fwdelete	Delete a DNS forwarding entry.
dns fwtable	Show DNS forwarding table.

dns fwtable

Show DNS forwarding table, i.e. list all currently unresolved DNS requests.

SYNTAX:

```
dns fwtable
```

EXAMPLE OUTPUT:

```
=>dns fwtable
Forwarding table:
Nr.  Ip Address      (port#):id(hex) (expiry)      dns server      tries
0    10.10.10.12     (54751):8331   (13 sec)      10.10.10.112    1
Timeout: 15 seconds
Table size: 10
amount of table used: 1 (10%)
=>
```

RELATED COMMANDS:

dns fwdlist Show current DNS forwarding entries.

dns list

Show current DNS entries.

SYNTAX:

```
dns list
```

EXAMPLE OUTPUT:

```
=>dns list
Domain: office.home.lan
Nr.      Hostname          IP Address
4*      Z7V1D8            10.0.0.29
0       SpeedTouch         *.*.*.*
1       TestHost           10.0.0.140
2       Default             10.0.0.8
3       ftpserver          172.16.0.1
Total Table Size: 73 entries
Amount used: 5 (6%)
=>
```

EXAMPLE INPUT/OUTPUT IN A NETWORKED ENVIRONMENT:

The **SpeedTouch™ Pro with Firewall** is configured as DNS server.

```
=>dns list
Domain: SpeedLAN.local
Nr.      Hostname          IP Address
0       SpeedTouch         *.*.*.*
1       Server             10.10.1.1
2       Client              10.0.0.3
Total Table Size: 73 entries
Amount used: 3 (4%)
=>
```

RELATED COMMANDS:

dns add Add a static DNS entry.

dns delete Delete a DNS entry (via its index number).

dns load

Load saved or default **SpeedTouch™ Pro with Firewall** DNS server/forwarder configuration and static DNS entries.

Execute **dns flush** prior to **dns load**.

SYNTAX:

dns load	[defaults = <yes no>]
-----------------	------------------------------------

[defaults]	Load factory defaults (yes) or saved configuration (no). Not specifying this parameter loads the saved configuration	OPTIONAL
-------------------	---	----------

EXAMPLE:

```
=>dns list
Domain: office.home.lan
Nr.      Hostname          IP Address
4*      Z7V1D8            10.0.0.29
0       SpeedTouch         *.*.*.*
1       TestHost           10.0.0.140
2       Default            10.0.0.8
Total Table Size: 73 entries
Amount used: 4 (5%)
=>dns save
=>dns flush
=>dns list
Domain: office.home.lan
Nr.      Hostname          IP Address
Total Table Size: 73 entries
Amount used: 0 (0%)
=>dns load defaults=yes
=>dns list
Domain: lan
Nr.      Hostname          IP Address
0       SpeedTouch         *.*.*.*
Total Table Size: 73 entries
Amount used: 1 (1%)
=>dns load defaults=no
=>dns flush
=>dns list
Domain: office.home.lan
Nr.      Hostname          IP Address
4*      Z7V1D8            10.0.0.29
0       SpeedTouch         *.*.*.*
1       TestHost           10.0.0.140
2       Default            10.0.0.8
Total Table Size: 73 entries
Amount used: 4 (5%)
=>
```

RELATED COMMANDS:

dns flush	Flush complete DNS server/forwarder configuration and static entries.
------------------	---

dns save	Save current DNS server/forwarder configuration and static entries
-----------------	--

dns nslookup

Search the hostname (via a known IP address) or the IP address (via a known hostname) of a DNS host.

SYNTAX:

dns nslookup	lookup = <string>
---------------------	--------------------------------

<i>lookup</i>	The DNS hostname or IP address to query.	REQUIRED
---------------	--	----------

EXAMPLE:

```
=>dns list
Domain: office.home.lan
Nr.      Hostname          IP Address
4*      Z7V1D8            10.0.0.29
0       SpeedTouch        *.*.*.*
1       TestHost          10.0.0.140
2       Default           10.0.0.8
3       ftpserver         172.16.0.1
Total Table Size: 73 entries
Amount used: 5 (6%)
=>dns nslookup lookup=TestHost
Name:   TestHost
Address: 10.0.0.140
=>dns nslookup lookup=10.0.0.29
Name:   Z7V1D8
Address: 10.0.0.29
=>
```

RELATED COMMANDS:

dns list	List current DNS entries.
-----------------	---------------------------

dns save

Save current **SpeedTouch™ Pro with Firewall** DNS server/forwarder configuration and static entries.

SYNTAX:

```
dns save
```

EXAMPLE:

```
=>dns fwdlist
DNS forwarding servers:
DNS          SRC          MASK          Direct
10.0.0.138   10.0.0.2    255.255.255.0  yes
10.0.0.138   10.0.0.4    255.255.255.0  no
10.0.0.138   10.0.0.3    255.255.255.0  yes
=>dns save
=>dns flush
=>dns fwdlist
DNS forwarding servers:
DNS          SRC          MASK          Direct
=>dns load
=>dns fwdlist
DNS forwarding servers:
DNS          SRC          MASK          Direct
10.0.0.138   10.0.0.2    255.255.255.0  yes
10.0.0.138   10.0.0.4    255.255.255.0  no
10.0.0.138   10.0.0.3    255.255.255.0  yes
=>
```

RELATED COMMANDS:

dns flush

Flush complete DNS server/forwarder configuration and dynamic entries.

dns load

Load saved or default DNS server/forwarder configuration and static entries.

dns start

Start SpeedTouch™ Pro with Firewall DNS server/forwarder.

SYNTAX:

```
dns start
```

EXAMPLE:

```
=>dns status
DNS server status: Stopped
DNS table size : 73, in use: 4, free: 94 %
DNS forwarding table size : 10, in use: 0, free:100 %
DNS forwarding dns servers table size : 25, in use: 4, free: 84 %
No dns cache.
Tracing: off
=>dns start
DNS server started.
=>dns status
DNS server status: Started
DNS table size : 73, in use: 4, free: 94 %
DNS forwarding table size : 10, in use: 0, free:100 %
DNS forwarding dns servers table size : 25, in use: 4, free: 84 %
No dns cache.
Tracing: off
=>
```

RELATED COMMANDS:

dns status

Show DNS server/forwarder configuration.

dns stop

Stop DNS server/forwarder.

dns stats

Show **SpeedTouch™ Pro with Firewall** DNS server/forwarder statistics.

SYNTAX:

dns stats

EXAMPLE INPUT/OUTPUT IN A NETWORKED ENVIRONMENT:

The **SpeedTouch™ Pro with Firewall** is configured as DNS server.

```
=>dns list
Domain: SpeedLAN.local
Nr.      Hostname          IP Address
0       SpeedTouch         *.*.*.*
1       Server            10.10.1.1
2       Client            10.0.0.3

Total Table Size: 73 entries
Amount used: 3 (4%)
=>dns stats
DNS Statistics:
Corrupted packets recv      :      0
Local questions resolved   :      1
Local neg answers sent      :      0
Total DNS packets fwd       :      0
External answers recv       :      0
Fwd table full, discard    :      0
Spurious answers           :      0
Unknown query types        :      0
Total number of packets received   :      1
=>(Ping Client.SpeedLAN.local)
=>(CTRL + Q)
dnssd: Internet class type A request received from 10.10.1.1.
dnssd: Client.SpeedLAN.local found in local database.
dnssd: Client.SpeedLAN.local resolved into 10.0.0.3.
=>(Ping Server.SpeedLAN.local)
dnssd: Internet class type A request received from 10.10.1.1.
dnssd: Server.SpeedLAN.local found in local database.
dnssd: Server.SpeedLAN.local resolved into 10.0.0.3.
=>(CTRL + S)
=>dns stats
DNS Statistics:
Corrupted packets recv      :      0
Local questions resolved   :      3
Local neg answers sent      :      0
Total DNS packets fwd       :      0
External answers recv       :      0
Fwd table full, discard    :      0
Spurious answers           :      0
Unknown query types        :      0
Total number of packets received   :      3
=>
```

RELATED COMMANDS:

dns clrstats

Clear DNS server/forwarder statistics.

dns status

Show SpeedTouch™ Pro with Firewall DNS server/forwarder configuration.

SYNTAX:

```
dns status
```

EXAMPLE OUTPUT:

```
=>dns status
DNS server status: Stopped
DNS table size : 73, in use: 4, free: 94 %
DNS forwarding table size : 10, in use: 0, free:100 %
DNS forwarding dns servers table size : 25, in use: 4, free: 84 %
No dns cache.
Tracing: off
=>
```

RELATED COMMANDS:

dns flush

Flush complete DNS server/forwarder configuration and dynamic entries.

dns load

Load saved or default DNS server/forwarder configuration and static entries.

dns save

Save current DNS server/forwarder configuration and static entries.

dns stop

Stop **SpeedTouch™ Pro with Firewall** DNS server/forwarder.

SYNTAX:

<i>dns stop</i>

EXAMPLE:

<pre>=>dns status <u>DNS server status: Started</u> DNS table size : 73, in use: 4, free: 94 % DNS forwarding table size : 10, in use: 0, free:100 % DNS forwarding dns servers table size : 25, in use: 4, free: 84 % No dns cache. Tracing: off =>dns stop DNS server stopped. =>dns status <u>DNS server status: Stopped</u> DNS table size : 73, in use: 4, free: 94 % DNS forwarding table size : 10, in use: 0, free:100 % DNS forwarding dns servers table size : 25, in use: 4, free: 84 % No dns cache. Tracing: off =></pre>

RELATED COMMANDS:

dns status

Show DNS server/forwarder configuration.

dns start

Start DNS server/forwarder.

dns toutfwd

Set DNS forwarding timeout.

SYNTAX:

dns toutfwd	timeout = <number>
--------------------	---------------------------------

timeout	A number (seconds). Represents the query forwarding timeout. This parameter determines how long the SpeedTouch™ Pro with Firewall DNS server should try to contact a (remote) DNS server before (temporarily) declaring the DNS requests unresolved. By default the timeout is 15 seconds.	REQUIRED
----------------	--	----------

EXAMPLE:

```
=>dns fwdtable
Forwarding table:
Nr.  Ip Address      (port#):id(hex) (expiry)      dns server      tries
0    10.10.10.12     (54751):8331   (13 sec)      10.10.10.112    1
Timeout: 15 seconds
Table size: 10
amount of table used: 1 (10%)
=>dns toutfwd timeout=20
Current timeout: 15 seconds
Timeout set to: 20 seconds
=>dns fwdtable
Forwarding table:
Nr.  Ip Address      (port#):id(hex) (expiry)      dns server      tries
0    10.10.10.12     (54751):8331   (13 sec)      10.10.10.112    1
Timeout: 20 seconds
Table size: 10
amount of table used: 1 (10%)
=>
```

RELATED COMMANDS:

dns fwdtable	Show DNS forwarding table.
dns fwlist	Show current DNS forwarding entries..
dns fwdadd	Add a DNS forwarding entry.
dns fwddelete	Delete a DNS forwarding entry.

dns troff

Disable verbose console messaging. No debug traces are generated.

SYNTAX:

<i>dns troff</i>

EXAMPLE:

<pre>=>dns status <u>DNS server status: Started</u> DNS table size : 73, in use: 4, free: 94 % DNS forwarding table size : 10, in use: 0, free:100 % DNS forwarding dns servers table size : 25, in use: 4, free: 84 % No dns cache. Tracing: on =>dns troff =>dns status <u>DNS server status: Started</u> DNS table size : 73, in use: 4, free: 94 % DNS forwarding table size : 10, in use: 0, free:100 % DNS forwarding dns servers table size : 25, in use: 4, free: 84 % No dns cache. <u>Tracing: off</u> =></pre>
--

RELATED COMMANDS:

dns fwdtable
dns fwdlist
dns status
dns tron

Show DNS forwarding table.
Show current DNS forwarding entries..
Show DNS server/forwarder configuration.
Enable verbose console messaging.

dns tron

Enable verbose console messaging. Debug traces are generated.

SYNTAX:

<i>dns tron</i>

EXAMPLE:

```
=>dns status
DNS server status: Started
DNS table size : 73, in use: 4, free: 94 %
DNS forwarding table size : 10, in use: 0, free:100 %
DNS forwarding dns servers table size : 25, in use: 4, free: 84 %
No dns cache.

Tracing: off
=>dns tron
Tracing on.
=>dns status
DNS server status: Started
DNS table size : 73, in use: 4, free: 94 %
DNS forwarding table size : 10, in use: 0, free:100 %
DNS forwarding dns servers table size : 25, in use: 4, free: 84 %
No dns cache.

Tracing: on
=>(CTRL + Q)
dnsd: Internet class type A request received from 10.0.0.10.
dnsd: aa.aa.be is outside our domain: forward.
dnsd: forwarding request from 10.0.0.10 (1318,0x0001) to 138.203.68.61
    (try=1): 'reply to ant' mode.
dnsd: Internet class type A request received from 10.0.0.10.
dnsd: aa.aa.be is outside our domain: forward.
dnsd: forwarding request from 10.0.0.10 (1318,0x0001) to 138.203.68.11
    (try=2): 'reply to ant' mode.
dnsd: forward answer from 138.203.68.11 to 10.0.0.10 (1318,0001).
dnsd: Internet class type A request received from 10.0.0.10.
dnsd: aa.aa.be.lan unknown: return error.
.....
=>(CTRL + S)
```

RELATED COMMANDS:

<i>dns fwdtable</i>	Show DNS forwarding table.
<i>dns fwdlist</i>	Show current DNS forwarding entries..
<i>dns status</i>	Show DNS server/forwarder configuration.
<i>dns troff</i>	Disable verbose console messaging.

8 Firewall Commands

firewall (to access the Firewall level)

firewall assign

firewall flush

firewall list

firewall load

firewall match

firewall save

firewall troff

firewall tron

firewall chain (to access the Firewall Chain level)

firewall chain create

firewall chain delete

firewall chain list

firewall chain load

firewall chain save

firewall rule (to access the Firewall Rule level)

firewall rule clear

firewall rule create

firewall rule delete

firewall rule flush

firewall rule list

firewall rule stats

firewall assign

Assign a chain to an entry point. An entry point, also referred to as hook or a Packet Interception Point (PIP) is the location where packets are intercepted to be compared against a chain of rules

SYNTAX:

firewall assign	hook = <{input sink forward source output}>
	chain = <string>

hook	The entry point's name to assign a chain to. Choose between: <ul style="list-style-type: none">▪ input : The point off all incoming traffic. At this point it can be determined whether the packet is allowed to reach the SpeedTouch™ Pro with Firewall IP router or local host.▪ sink : The point off all traffic destined to the SpeedTouch™ Pro with Firewall IP router itself. At this point it can be determined whether the packet is allowed to address the local host.▪ forward : The point off all traffic to be forwarded by the SpeedTouch™ Pro with Firewall IP router. At this point it can be determined whether the packet is allowed to be handled, i.e. routed.▪ source : The point off all traffic sourced by the SpeedTouch™ Pro with Firewall IP router. At this point it can be determined whether the packet is allowed to leave the local host.▪ output : The point off all outgoing traffic. At this point it can be determined whether the packet is allowed to leave the SpeedTouch™ Pro with Firewall IP router or local host.	REQUIRED
chain	The name of the chain to use.	REQUIRED

EXAMPLE:

```
=>firewall list
assign hook=sink chain=sink
assign hook=forward chain=forward
assign hook=source chain=source
=>firewall chain create chain Telnet
=>firewall assign hook=sink chain=Telnet
=>firewall list
assign hook=sink chain=Telnet
assign hook=forward chain=forward
assign hook=source chain=source
=>
```

RELATED COMMANDS:

firewall chain create	Create a chain.
firewall chain list	Show a list of all current chains.

firewall flush

Flush all associations between a hook and its chain(s). The chain itself is not removed. The flush command does not impact previously saved configurations.

SYNTAX:

firewall flush	[hook = <{input sink forward source output}>]
-----------------------	--

[hook]	the name of the hook to clear. Choose between: <ul style="list-style-type: none">▪ input▪ sink▪ forward▪ source▪ output. In case this parameter is not specified all hooks are cleared.	OPTIONAL
--------	--	----------

EXAMPLE:

```
=>firewall list
assign hook=sink    chain=sink
assign hook=forward chain=forward
assign hook=source   chain=source
=>firewall flush hook=sink
=>firewall list
assign hook=forward chain=forward
assign hook=source   chain=source
=>firewall flush
=>firewall list
=>
```

RELATED COMMANDS:

firewall assign	Assign a chain to an entry point.
------------------------	-----------------------------------

firewall list

Show association(s) between all hooks and their chain(s) or of one specified hook

SYNTAX:

firewall list	[hook = <{input sink forward source output}>]
----------------------	--

[hook]	the name of the hook to show the associations for. Choose between: <ul style="list-style-type: none">▪ input▪ sink▪ forward▪ source▪ output. In case this parameter is not specified the associations for all hooks are shown.	OPTIONAL
---------------	---	----------

EXAMPLE INPUT/OUTPUT:

```
=>firewall list
assign hook=sink    chain=sink
assign hook=forward chain=forward
assign hook=source  chain=source
=>firewall list hook=input
=>firewall list hook=forward
assign hook=forward chain=forward
=>
```

RELATED COMMANDS:

firewall assign
firewall flush

Assign a chain to an entry point.
Clear associations for all or a selected entry point(s).

firewall load

Load saved (or default) firewall configuration.

Execute **firewall flush** prior to **firewall load**.

SYNTAX:

firewall load	<i>[file = <string>]</i> <i>[defaults = <yes no>]</i>
----------------------	--

<i>[file]</i>	The name of the firewall configuration to be loaded. Not specifying this parameter loads the default configuration	OPTIONAL
---------------	---	----------

<i>[defaults]</i>	Load factory defaults (yes) or saved configuration (no). Not specifying this parameter loads the saved configuration	OPTIONAL
-------------------	---	----------

EXAMPLE:

```
=>firewall list
assign hook=sink chain=sink
assign hook=forward chain=forward
assign hook=source chain=source
=>firewall save
=>firewall flush
=>firewall list
=>firewall load
=>firewall list
assign hook=sink chain=sink
assign hook=forward chain=forward
assign hook=source chain=source
=>
```

RELATED COMMANDS:

firewall save	Save current firewall configuration.
firewall flush	Clear associations for all or a selected entry point(s).

firewall match

Match a specified IP packet. Used to match an IP packet against a chain in order to determine what the reaction of the firewall would be.

This command can be considered as being the same as the **firewall rule create** command, but without the action to be taken.

SYNTAX:

firewall match	<code>chain = <string></code> <code>[srcintf = <string>]</code> <code>[src = <ip-address>]</code> <code>[srcbridgeport = <number>]</code> <code>[dstintf = <string>]</code> <code>[dst = <ip-address>]</code> <code>[tos = <number>]</code> <code>[prot = <{tcp udp icmp protocol}>]</code> <code>[syn = <yes no>]</code> <code>[urg = <yes no>]</code> <code>[ack = <yes no>]</code> <code>[srcport = <{ftp ftp-data telnet mail smtp dns domain tftp port}>]</code> <code>[dstport = <{ftp ftp-data telnet mail smtp dns domain tftp port}>]</code> <code>[icmptype = <{echo-reply destination-unreachable source-quench </code> <code> redirect echo-request router-advertisement </code> <code> router-solicitation time-exceeded parameter-problems </code> <code> timestamp-request timestamp-reply </code> <code> information-request information-reply </code> <code> address-mask-request address-mask-reply </code> <code> icmpnumber}>]</code> <code>[icmpcode = <number{0-15}>]</code>
-----------------------	--

<code>chain</code>	The name of the chain to match the packet against.	REQUIRED
<code>[srcintf]</code>	The name of the interface the virtual packet arrived on.	OPTIONAL
<code>[src]</code>	The source IP address the virtual packet is coming from.	OPTIONAL
<code>[srcbridgeport]</code>	A number between 0 and 6. Represents the bridge port the virtual packet arrived on. Execute bridge iflist for a list of available bridge ports.	OPTIONAL
<code>[dstintf]</code>	The name of the interface the virtual packet is going to.	OPTIONAL
<code>[dst]</code>	The destination IP address the virtual packet is going to.	OPTIONAL
<code>[tos]</code>	A number between 0 and 255. Represents the Type Of Service specification which should be expected [or NOT expected] in the IP packet. The Type of Service numbering specification is in accordance to the latest version of RFC1700: Assigned numbers.	OPTIONAL

[prot]	The protocol (name or number) in the virtual IP packet. Choose between: <ul style="list-style-type: none">▪ <i>tcp</i>▪ <i>udp</i>▪ <i>icmp</i> Or specify the protocol number in accordance to the latest version of RFC1700: Assigned numbers.	OPTIONAL
[syn]	Set the TCP SYN flag (yes) or not (no).	OPTIONAL
[urg]	Set the TCP URG flag (yes) or not (no).	OPTIONAL
[ack]	Set the TCP ACK flag (yes) or not (no).	OPTIONAL
[srcport]	The TCP/UDP port the virtual packet is coming from. Choose between: <ul style="list-style-type: none">▪ <i>ftp</i>▪ <i>ftp-data</i>▪ <i>telnet</i>▪ <i>mail</i>▪ <i>smtp</i>▪ <i>dns</i>▪ <i>domain</i>▪ <i>tftp</i> Or specify the port number in accordance to the latest version of RFC1700: Assigned numbers.	OPTIONAL
[dstport]	The TCP/UDP port the virtual packet is going to. Choose between: <ul style="list-style-type: none">▪ <i>ftp</i>▪ <i>ftp-data</i>▪ <i>telnet</i>▪ <i>mail</i>▪ <i>smtp</i>▪ <i>dns</i>▪ <i>domain</i>▪ <i>tftp</i> Or specify the port number in accordance to the latest version of RFC1700: Assigned numbers.	OPTIONAL

[icmp-type]	The ICMP (Internet Control Message Protocol) type (name or number) OPTIONAL of the virtual packet. Choose between: <ul style="list-style-type: none">▪ echo-reply▪ destination-unreachable▪ source-quench▪ redirect▪ echo-request▪ router-advertisement▪ router-solicitation▪ time-exceeded▪ parameter-problems▪ timestamp-request▪ timestamp-reply▪ information-request▪ information-reply▪ address-mask-request▪ address-mask-reply Or specify the ICMP type number in accordance to the latest version of RFC1700: Assigned numbers.
[icmp-code]	A number between 0 and 15. OPTIONAL Represents the ICMP code of the virtual packet as specified in the latest version of RFC1700: Assigned number.

EXAMPLE INPUT/OUTPUT:

```
=>firewall rule list chain=Telnet
:firewall rule create chain=Telnet index=0 srcintfgrp=lan src=10.0.0.0/8
dst=200.200.200.1/32 prot=tcp srcport=1024 srcportend=65535 dstport=telnet
action=accept
:firewall rule create chain=Telnet index=1 srcintfgrp=wan src=200.200.200.1/32
dst=10.0.0.0/8 prot=tcp srcport=telnet dstport=1024 dstportend=65535
action=accept
:firewall rule create chain=Telnet index=2
action=drop
=>firewall match chain=Telnet src=200.200.200.1 dst=10.0.0.1 ack srcport=23 dstport=1023
Packet was ACCEPTED
=>
```

RELATED COMMANDS:

firewall rule create Create a firewall rule.

firewall save

Save all modifications entered by : **firewall assign**.

This command only saves the association between hook(s) and chain(s), set by the **firewall assign** command, not the information about chains, rules and their parameters .

SYNTAX:

firewall save	[file = <string>]
----------------------	--------------------------------

[file]	A name for the current firewall configuration file to be saved. The name is limited to 9 characters.	OPTIONAL
	This parameter allows multiple firewall configurations to be saved under different names.	
	In case this parameter is not specified the configuration is saved as single configuration.	

EXAMPLE:

```
=>firewall list
assign hook=sink    chain=sink
assign hook=forward chain=forward
assign hook=source   chain=source
=>firewall assign hook input chain Test
=>firewall list
assign hook=input chain=Test
assign hook=sink    chain=sink
assign hook=forward chain=forward
assign hook=source   chain=source
=>firewall save file=TestCnfg
=>firewall flush
=>firewall list
=>firewall load file=TestCnfg
=>firewall list
assign hook=input chain=Test
assign hook=sink    chain=sink
assign hook=forward chain=forward
assign hook=source   chain=source
=>
```

RELATED COMMANDS:

firewall load	Load a saved or default firewall configuration.
firewall flush	Clear associations for all or a selected entry point(s).
firewall chain save	Save current chain(s) configuration.

firewall troff

Disable verbose console messaging.

SYNTAX:

```
firewall troff
```

EXAMPLE:

```
=>firewall troff
```

RELATED COMMANDS:

firewall tron Enable verbose console messaging.

firewall tron

Enable verbose console messaging.

SYNTAX:

```
firewall tron
```

EXAMPLE:

```
=>firewall tron
```

RELATED COMMANDS:

firewall troff	Disable verbose console messaging.
-----------------------	------------------------------------

firewall chain create

Create a new chain.

SYNTAX:

```
firewall chain create chain = <string>
```

<i>chain</i>	The name of the chain to create.	REQUIRED
--------------	----------------------------------	----------

EXAMPLE:

```
=>firewall chain list  
Tempo, source, forward, sink  
=>firewall chain create chain=Telnet  
=>firewall chain list  
Telnet, Tempo, source, forward, sink  
=>
```

RELATED COMMANDS:

firewall assign	Assign a chain to an entry point.
firewall chain delete	Delete a chain.
firewall chain list	Show a list of all current chains.

firewall chain delete

Delete a chain.

SYNTAX:

```
firewall chain delete chain = <string>
```

chain The name of the chain to be deleted.

REQUIRED

EXAMPLE:

```
=>firewall chain list  
Telnet, Tempo, source, forward, sink  
=>firewall chain list  
Telnet, Tempo, source, forward, sink  
=>firewall chain delete chain=Tempo  
=>firewall chain list  
Telnet, source, forward, sink  
=>
```

RELATED COMMANDS:

RELATED COMMANDS:

firewall assign	Assign a chain to an entry point.
firewall chain create	Create a chain.
firewall chain list	Show a list of all chains.

firewall chain list

Show a list of all current chains.

SYNTAX:

```
firewall chain list
```

EXAMPLE INPUT/OUTPUT:

```
=>firewall chain list
source, forward, sink
=>firewall chain create chain Telnet
=>firewall chain list
Telnet, source, forward, sink
=>firewall chain list
Telnet, source, forward, sink
=>
```

RELATED COMMANDS:

firewall assign	Assign a chain to an entry point.
firewall chain create	Create a chain.
firewall chain delete	Delete a chain.

firewall chain load

Load saved or default chain(s) configuration (with related rules).

SYNTAX:

firewall chain load	<i>[file = <string>] [defaults = <yes no>]</i>
----------------------------	--

<i>[file]</i>	The name of the chain configuration to be loaded. Not specifying this parameter loads the default configuration	OPTIONAL
---------------	--	----------

<i>[defaults]</i>	Load factory defaults (yes) or saved configuration (no). Not specifying this parameter loads the saved configuration	OPTIONAL
-------------------	---	----------

EXAMPLE:

=>firewall flush =>firewall load =>firewall chain list source, forward, sink =>firewall flush => firewall chain load file TelConfig =>firewall chain list sink, forward, source, <u>Telnet</u> =>
--

RELATED COMMANDS:

firewall assign	Assign a chain to an entry point.
firewall chain create	Create a chain.
firewall chain delete	Delete a chain.
firewall chain list	Show a list of all current chains.
firewall chain save	Save current chain(s) configuration.

firewall chain save

Save all modifications entered by : **firewall chain create**, **firewall chain delete** .

This command saves the information about chains, rules and their parameters. This is different from **firewall save** which saves only the association between hook(s) and chain(s), set by the **firewall assign** command.

SYNTAX:

```
firewall chain save [file = <string>]
```

[file]	A name for the current chain configuration file to be saved. The name is limited to 9 characters. This parameter allows multiple chain configurations to be saved under different names. In case this parameter is not specified the configuration is saved as single configuration.	OPTIONAL
--------	---	----------

EXAMPLE:

```
=>firewall flush
=>firewall chain load file TelConfig
=>firewall chain list
Telnet, source, forward, sink
=>firewall chain create chain NewTel
=>firewall chain list
NewTel, Telnet, source, forward, sink
=>firewall chain save file NewTelcnf
=>firewall flush
=>firewall chain load file NewTelcnf
=>firewall chain list
sink, forward, source, Telnet, NewTel
=>
```

RELATED COMMANDS:

firewall assign	Assign a chain to an entry point.
firewall chain create	Create a chain.
firewall chain delete	Delete a chain.
firewall chain list	Show a list of all current chains.
firewall chain load	Load saved or default chain configuration(s).

firewall rule clear

Clear statistics for a given rule.

SYNTAX:

firewall rule clear	<i>[chain = <string>]</i>
	<i>[index = <number>]</i>

<i>[chain]</i>	The name of the chain in which the rule is to be found.	OPTIONAL
<i>[index]</i>	The index number (determined by the position) of the rule in the chain	OPTIONAL

EXAMPLE:

```
=>firewall rule stats
ChainTelnet, index0, packets 0, bytes 0
ChainTelnet, index1, packets 0, bytes 0
ChainTelnet, index2, packets 0, bytes 0
Chainsource, index0, packets 203, bytes 15229
Chainsource, index1, packets 0, bytes 0
Chainsource, index2, packets 0, bytes 0
Chainforward, index0, packets 0, bytes 0
Chainsink, index0, packets 202, bytes 10159
Chainsink, index1, packets 0, bytes 0
Chainsink, index2, packets 0, bytes 0
=>firewall rule clear chain=source index=0
=>firewall rule stats
ChainTelnet, index0, packets 0, bytes 0
ChainTelnet, index1, packets 0, bytes 0
ChainTelnet, index2, packets 0, bytes 0
Chainsource, index0, packets 11, bytes 559
Chainsource, index1, packets 0, bytes 0
Chainsource, index2, packets 0, bytes 0
Chainforward, index0, packets 0, bytes 0
Chainsink, index0, packets 409, bytes 21535
Chainsink, index1, packets 0, bytes 0
Chainsink, index2, packets 0, bytes 0
=>
```

RELATED COMMANDS:

firewall rule create	Create a rule.
firewall rule delete	Delete a specified rule in a chain.
firewall rule flush	Delete all rules in a chain.
firewall rule list	Show a list of all (or a specified) chains' rules.
firewall rule stats	Show statistics for all (or a specified) chains' rules.

firewall rule create

Create a rule.

SYNTAX:

```
firewall rule create chain = <string>
[index = <number>]
[srcintf [!] = <string>]
[srcintfgrp [!] = <{wan|local|lan}>]
[srcbridgeport [!] = <number>]
[src [!] = <ip-address>]
[srcmsk = <ip-mask(dotted or cidr)>]
[dstintf [!] = <string>]
[dstintfgrp [!] = <{wan|local|lan}>]
[dst [!] = <ip-address>]
[dstmsk = <ip-mask(dotted or cidr)>]
[tos [!] = <number{1-255}>]
[prot [!] = <{tcp|udp|icmp|protocol}>]
[syn <yes|no>]
[urg <yes|no>]
[ack <yes|no>]
[srcport [!] = <{ftp|ftp-data|telnet|mail|smtp|dns|domain|tftp|port}>]
[srcportend = <{ftp|ftp-data|telnet|mail|smtp|dns|domain|tftp|port}>]
[dstport [!] = <{ftp|ftp-data|telnet|mail|smtp|dns|domain|tftp|port}>]
[dstportend = <{ftp|ftp-data|telnet|mail|smtp|dns|domain|tftp|port}>]
[icmptype [!] = <{echo-reply|destination-unreachable|source-quench|
    redirect|echo-request|router-advertisement|
    router-solicitation|time-exceeded|parameter-problems|
    timestamp-request|timestamp-reply|
    information-request|information-reply|
    address-mask-request|address-mask-reply|
    icmpnumber}>]
[icmpcode [!] = <number{0-15}>]
[icmpcodeend = <number{0-15}>]
[clink = <string>]
action = <{accept|deny|drop|count}>
```

chain	The name of the chain to insert the rule in.	REQUIRED
[index]	The number of the rule before which the new rule must be added.	OPTIONAL
[srcintf]	The name of the interface the packet should [or should NOT] arrive on to make this rule apply. (NOT applicable if used in a chain assigned to the output hook)	OPTIONAL
[srcintfgrp]	The interface group the packet should [or should NOT] arrive on. Choose between: <ul style="list-style-type: none">▪ wan▪ local▪ lan (NOT applicable if used in a chain assigned to the output hook)	OPTIONAL

[srcbridgeport]	A number between 0 and 6. Represents the bridge port the virtual packet should [or should NOT] arrive on. Execute bridge iflist for a list of available bridge ports.	OPTIONAL
[src]	The source IP address (range) the packet should [or should NOT] come from. (Supports cidr notation).	OPTIONAL
[srcmsk]	The source IP address mask defining the range (see src).	OPTIONAL
[dstintf]	The name of the interface the packet should [or should NOT] be going to. (NOT applicable if used in a chain assigned to the input hook)	OPTIONAL
[dstintfgrp]	The interface group the packet should [or should NOT] be going to. Choose between: <ul style="list-style-type: none">▪ wan▪ local▪ lan (NOT applicable if used in a chain assigned to the input hook)	OPTIONAL
[dst]	The destination IP address (range) the packet should [or should NOT] be going to. (supports cidr notation).	OPTIONAL
[dstmsk]	The destination IP address mask defining the range (see dst).	OPTIONAL
[tos]	A number between 0 and 255. Represents the Type Of Service specification which should be expected [or NOT expected] in the IP packet. The Type of Service numbering specification is in accordance to the latest version of RFC1700: Assigned numbers.	OPTIONAL
[prot]	The protocol (name or number) in the IP packet expected [or NOT expected] in the IP packet. Choose between: <ul style="list-style-type: none">▪ tcp▪ udp▪ icmp Or specify the protocol number in accordance to the latest version of RFC1700: Assigned numbers.	OPTIONAL
[syn]	Expect TCP SYN flag set (yes) or not (no). In combination with TCP ACK this allows selection of incoming versus outgoing TCP connections.	OPTIONAL
[urg]	Expect TCP URG flag set (yes) or not (no).	OPTIONAL
[ack]	Expect TCP ACK flag set (yes) or not (no).	OPTIONAL

[srcport]	The TCP/UDP port (or beginning of range) the packet should [or should NOT] be from. Choose between: <ul style="list-style-type: none">▪ ftp▪ ftp-data▪ telnet▪ mail▪ smtp▪ dns▪ domain▪ tftp Or specify the port number in accordance to the latest version of RFC1700: Assigned numbers.	OPTIONAL
[srcportend]	The source TCP/UDP port range end (inclusive). (Only applicable for ranges)	OPTIONAL
[dstport]	The TCP/UDP port (or beginning of range) the packet should [or should NOT] be going to. Choose between: <ul style="list-style-type: none">▪ ftp▪ ftp-data▪ telnet▪ mail▪ smtp▪ dns▪ domain▪ tftp Or specify the port number in accordance to the latest version of RFC1700: Assigned numbers.	OPTIONAL
[dstportend]	The destination TCP/UDP port range end (inclusive). (Only applicable for ranges)	OPTIONAL
[icmptype]	The expected [or NOT expected] ICMP type (name or number) of the packet. Choose between: <ul style="list-style-type: none">▪ echo-reply▪ destination-unreachable▪ source-quench▪ redirect▪ echo-request▪ router-advertisement▪ router-solicitation▪ time-exceeded▪ parameter-problems▪ timestamp-request▪ timestamp-reply▪ information-request▪ information-reply▪ address-mask-request▪ address-mask-reply Or specify the ICMP type number in accordance to the latest version of RFC1700: Assigned numbers.	OPTIONAL

[icmpcode]	A number between 0 and 15. Represents the expected [or NOT expected] ICMP code (or beginning of range) of the packet as specified in the latest version of RFC1700: Assigned number.	OPTIONAL
[icmpcodeend]	A number between 0 and 15. Represents the ICMP code range end. Only applicable for ranges.	OPTIONAL
[clink]	The name of the chain to be parsed when this rule applies. (action is ignored).	OPTIONAL
action	Action to be taken when this rule applies. Choose between: <ul style="list-style-type: none">▪ accept : the packet may pass.▪ deny : ICMP error destination unreachable. An error message is sent back to the sender.▪ drop : packet disappears. It is silently dropped, that is, without sending an error message to the sender.▪ count : update of statistics. Has no influence on the packet.	REQUIRED

EXAMPLE:

```
=>firewall rule list chain=Telnet
=>firewall rule create chain=telnet src=10.0.0.0/8 dst=200.200.200.1 srcintfgrp=lan
  prot=tcp srcport=1024 srcportend=65535dstport=23
  action=accept
=>firewall rule create chain=telnet src=200.200.200.1 dst=10.0.0.0/8 srcintfgrp=wlan
  prot=tcp srcport=23 dstport=1024 dstportend=65535
  action=accept
=>firewall rule create chain=telnet
  action=drop
=>firewall rule list chain=Telnet
:firewall rule create chain=Telnet index=0 srcintfgrp=lan src=10.0.0.0/8
  dst=200.200.200.1/32 prot=tcp srcport=1024 srcportend=65535dstport=telnet
  action=accept
:firewall rule create chain=Telnet index=1 srcintfgrp=wlan src=200.200.200.1/32
  dst=10.0.0.0/8 prot=tcp srcport=telnet dstport=1024 dstportend=65535
  action=accept
:firewall rule create chain=Telnet index=2
  action=drop
=>
```

RELATED COMMANDS:

firewall rule clear	Clear statistics of a given rule.
firewall rule delete	Delete a specified rule in a chain.
firewall rule flush	Delete all rules in a chain.
firewall rule list	Show a list of all (or a specified) chains' rules.
firewall rule stats	Show statistics for all (or a specified) chains' rules.

firewall rule delete

Delete a rule.

SYNTAX:

```
firewall rule delete chain = <string>
index = <number>
```

chain The name of the chain in which to delete the rule. REQUIRED

index The index number of the rule in the chain. REQUIRED
Execute **firewall rule list** first to determine the index number of the applicable rule.

EXAMPLE:

```
=>firewall rule list chain=Telnet
:firewall rule create chain=Telnet index=0 srcintfgrp=lan src=10.0.0.0/8
dst=200.200.200.1/32 prot=tcp srcport=1024 srcportend=65535dstport=telnet
action=accept
:firewall rule create chain=Telnet index=1 srcintfgrp=wan src=200.200.200.1/32
dst=10.0.0.0/8 prot=tcp srcport=telnet dstport=1024 dstportend=65535
action=accept
:firewall rule create chain=Telnet index=2 action=drop
=>firewall rule delete chain=Telnet index=1
=>firewall rule list chain=Telnet
:firewall rule create chain=Telnet index=0 srcintfgrp=lan src=10.0.0.0/8
dst=200.200.200.1/32 prot=tcp srcport=1024 srcportend=65535dstport=telnet
action=accept
:firewall rule create chain=Telnet index=1 action=drop
=>
```

RELATED COMMANDS:

firewall rule clear	Clear statistics of a given rule.
firewall rule create	Create a rule.
firewall rule flush	Delete all rules in a chain.
firewall rule list	Show a list of all (or a specified) chains' rules.
firewall rule stats	Show statistics for all (or a specified) chains' rules.

firewall rule flush

Flush all rules created for a chain(s). The chain itself is not removed. The flush command does not impact previously saved configurations.

SYNTAX:

firewall rule flush [chain = <string>]

[chain]	The name of the chain to empty. In case this parameter is not specified all rules for all chains are deleted.	OPTIONAL
---------	--	----------

EXAMPLE:

```
=>firewall rule list chain=Telnet
:firewall rule create chain=Telnet index=0 srcintfgrp=lan src=10.0.0.0/8
  dst=200.200.200.1/32 prot=tcp srcport=1024 srcportend=65535dstport=telnet
  action=accept
:firewall rule create chain=Telnet index=1 srcintfgrp=wan src=200.200.200.1/32
  dst=10.0.0.0/8 prot=tcp srcport=telnet dstport=1024 dstportend=65535
  action=accept
:firewall rule create chain=Telnet index=2 action=drop
=>firewall rule flush chain=Telnet
=>firewall rule list chain=Telnet
=>
```

RELATED COMMANDS:

firewall rule clear	Clear statistics of a given rule.
firewall rule create	Create a rule.
firewall rule delete	Delete a specified rule.
firewall rule list	Show a list of all (or a specified) chains' rules.
firewall rule stats	Show statistics for all (or a specified) chains' rules.

firewall rule list

Show a list of rules.

SYNTAX:

firewall rule list	[chain = <string>]
---------------------------	---------------------------------

[chain]	The name of the chain to list the rules of. In case this parameter is not specified all rules for all chains are shown.	OPTIONAL
---------	--	----------

EXAMPLE INPUT AND OUTPUT:

```
=>firewall rule list chain=Telnet
:firewall rule create chain=Telnet index=0 srcintfgrp=lan src=10.0.0.0/8
  dst=200.200.200.1/32 prot=tcp  srcport=1024 srcportend=65535dstport=telnet
  action=accept
:firewall rule create chain=Telnet index=1 srcintfgrp=wan src=200.200.200.1/32
  dst=10.0.0.0/8 prot=tcp  srcport=telnet dstport=1024 dstportend=65535
  action=accept
:firewall rule create chain=Telnet index=2 action=drop
=>firewall rule list
:firewall rule create chain=source index=0 dstintfgrp!=wan action=accept
:firewall rule create chain=source index=1 prot=udp  dstport=dns action=accept
:firewall rule create chain=source index=2 prot=udp  dstport=67 action=accept
:firewall rule create chain=source index=3 action=drop
:firewall rule create chain=forwardindex=0 srcintfgrp=wan dstintfgrp=wan action=drop
:firewall rule create chain=sink index=0 srcintf=eth0 srcbridgeport=1 action=accept
:firewall rule create chain=sink index=1 srcintfgrp!=wan action=accept
:firewall rule create chain=sink index=2 prot=udp  dstport=dns action=accept
:firewall rule create chain=sink index=3 prot=udp  dstport=68 action=accept
:firewall rule create chain=sink index=4 action=drop
:firewall rule create chain=Telnet index=0 srcintfgrp=lan src=10.0.0.0/8
  dst=200.200.200.1/32 prot=tcp  srcport=1024 srcportend=65535dstport=telnet
  action=accept
:firewall rule create chain=Telnet index=1 srcintfgrp=wan src=200.200.200.1/32
  dst=10.0.0.0/8 prot=tcp  srcport=telnet dstport=1024 dstportend=65535
  action=accept
:firewall rule create chain=Telnet index=2 action=drop
=>
```

RELATED COMMANDS:

firewall rule clear	Clear statistics of a given rule.
firewall rule create	Create a rule.
firewall rule delete	Delete a specified rule.
firewall rule flush	Delete all rules in a chain.
firewall rule stats	Show statistics for all (or a specified) chains' rules.

firewall rule stats

Show statistics, i. e. the number of packets and bytes which have passed the hooks.

SYNTAX:

firewall rule stats	[chain = <string>]
	[index = <number>]

[chain]	The name of the chain of which the statistics must be listed. In case this parameter is not specified the statistics for the rules applicable to all chains are shown.	OPTIONAL
[index]	The index number of the chain's rule of which the statistics must be listed. Execute firewall rule list first to determine the index number of the applicable rule. In case this parameter is not specified the statistics for all rules applicable to the specified chain are shown.	OPTIONAL

EXAMPLE OUTPUT:

```
=>firewall rule list chain=Test
:firewall rule create chain=Test index=0 srcintfgrp=lan src=200.200.0.1/32
  dst=200.200.0.2/32 prot=udp  srcport=0  srcportend=65535dstport=telnet
  action=deny
=>firewall rule clear
=>firewall rule stats
Chainsink, index0, packets 43, bytes 1743
Chainsink, index1, packets 0, bytes 0
Chainsink, index2, packets 0, bytes 0
Chainsink, index3, packets 0, bytes 0
Chainforward,index0, packets 0, bytes 0
Chainsource, index0, packets 43, bytes 1977
Chainsource, index1, packets 0, bytes 0
Chainsource, index2, packets 0, bytes 0
ChainTest, index0, packets 0, bytes 0
=>firewall rule stats
Chainsink, index0, packets 104, bytes 6143
Chainsink, index1, packets 0, bytes 0
Chainsink, index2, packets 0, bytes 0
Chainsink, index3, packets 0, bytes 0
Chainforward,index0, packets 0, bytes 0
Chainsource, index0, packets 43, bytes 1977
Chainsource, index1, packets 0, bytes 0
Chainsource, index2, packets 0, bytes 0
ChainTest, index0, packets 44, bytes 21032
=>
```

DESCRIPTION:

The statistics for the 'Test' chain are the result of sending udp packets to the **SpeedTouch™ Pro with Firewall**. The chain 'Test' is assigned to the hook 'input' and prohibits the sending of udp packets from one host to another.

EXAMPLE INPUT/OUTPUT IN A NETWORKED ENVIRONMENT:

The **SpeedTouch™ Pro with Firewall** is configured as DHCP client on its Ethernet interface eth0.

```
=>firewall rule list chain=Sending
:firewall rule create chain=Sending index=0 srcintfgrp=lan src=10.0.0.3/32
  dst=10.10.1.1/32 prot=icmp action=count
:firewall rule create chain=Sending index=1 srcintfgrp=lan src=10.10.1.1/32
  dst=10.0.0.3/32 prot=icmp action=count
=>firewall rule stats
Chainsource, index 0, packets 0, bytes 0
Chainsource, index 1, packets 0, bytes 0
Chainsource, index 2, packets 0, bytes 0
Chainsource, index 3, packets 0, bytes 0
Chainforward, index 0, packets 0, bytes 0
Chainsink, index 0, packets 0, bytes 0
Chainsink, index 1, packets 144, bytes 5844
Chainsink, index 2, packets 0, bytes 0
Chainsink, index 3, packets 0, bytes 0
Chainsink, index 4, packets 0, bytes 0
Chainsink, index 5, packets 0, bytes 0
Chainsending, index 0, packets 0, bytes 0
Chainsending, index 1, packets 0, bytes 0
=>firewall rule clear
=>(Ping from server 10.10.1.1 to client 10.0.0.3)
=>firewall rule stats
Chainsource, index 0, packets 0, bytes 0
Chainsource, index 1, packets 0, bytes 0
Chainsource, index 2, packets 0, bytes 0
Chainsource, index 3, packets 0, bytes 0
Chainforward, index 0, packets 0, bytes 0
Chainsink, index 0, packets 0, bytes 0
Chainsink, index 1, packets 42, bytes 1782
Chainsink, index 2, packets 0, bytes 0
Chainsink, index 3, packets 0, bytes 0
Chainsink, index 4, packets 0, bytes 0
Chainsink, index 5, packets 0, bytes 0
Chainsending, index 0, packets 4, bytes 240
Chainsending, index 1, packets 4, bytes 240
=>
```

RELATED COMMANDS:

firewall rule clear	Clear statistics of a given rule.
firewall rule create	Create a rule.
firewall rule delete	Delete a specified rule.
firewall rule flush	Delete all rules in a chain.
firewall rule list	Show a list of all (or a specified) chains' rules.

9 IP Commands

ip (to access the IP level)
ip apadd
ip apdelete
ip aplist
ip arpadd
ip arpdelete
ip arplist
ip config
ip flush
ip ifconfig
ip iflist
ip load
ip ping
ip rtadd
ip rtdelete
ip rtlist
ip save
ip sendto

ip apadd

Assign an IP address to an interface.

SYNTAX:

ip apadd	addr = <ip-address> [netmask = <ip-mask (dotted or cidr)>] intf = <interface name> [pointtopoint = <ip-address>] [broadcastip = <ip-address>] [addrtrans = <{none pat}>] [addroute = <{no yes}>] [type = <number>]	
addr	The new IP address to add.	REQUIRED
[netmask]	The subnetmask associated with this address.	OPTIONAL
intf	The interface name.	REQUIRED
[pointtopoint]	The remote IP address in case of a dedicated point-to-point link.	OPTIONAL
[broadcastip]	The broadcast IP address. For internal use only.	OPTIONAL
[addrtrans]	Indicates whether network address translation mode is allowed (pat) for this IP address or not (none).	OPTIONAL
[addroute]	Add typical net/subnet routes automatically according to the default (or specified) subnet mask (yes) or not (no).	OPTIONAL
[type]	The type of address classification. For internal use only.	OPTIONAL

EXAMPLE:

```
=>ip aplist
1   eth0      Type:Ethernet HWaddr 00:80:9f:24:ab:cf BRHWaddr ff:ff:ff:ff:ff:ff
    inet addr:10.10.10.147  Bcast: 10.10.10.255 Mask: 255.0.0.0
        UP RUNNING pat MTU:1500 ReasmMAX:65535 Group:2
        IPRX bytes:19791886 unicastpkts:11341 brcastpkts:290555
        IPTX bytes:839550 unicastpkts:11477 brcastpkts:0      droppkts:0
        HWRX bytes:0  unicastpkts:0      brcastpkts:0
        HWTX bytes:0  unicastpkts:0      brcastpkts:0      droppkts:0
0   loop      Type:0
    inet addr:127.0.0.1      Bcast:127.255.255.255 Mask:255.0.0.0
        UP RUNNING      MTU:1500 ReasmMAX:65535 Group:1
        IPRX bytes:116     unicastpkts:0      brcastpkts:2
        IPTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
        HWRX bytes:0      unicastpkts:0      brcastpkts:0
        HWTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
=>ip apadd addr=10.0.0.2 netmask=255.255.255.0 intf=eth0 addrtrans=pat addroute=yes
=>ip aplist
2   eth0      Type:Ethernet HWaddr 00:80:9f:24:ab:cf BRHWaddr ff:ff:ff:ff:ff:ff
    inet addr:10.0.0.2      Bcast: 10.0.0.255 Mask: 255.255.255.0
        UP RUNNING pat MTU:1500 ReasmMAX:65535 Group:2
        IPRX bytes:0  unicastpkts:0      brcastpkts:0
        IPTX bytes:0  unicastpkts:0      brcastpkts:0      droppkts:0
        HWRX bytes:0  unicastpkts:0      brcastpkts:0
        HWTX bytes:0  unicastpkts:0      brcastpkts:0      droppkts:0
1   eth0      Type:Ethernet HWaddr 00:80:9f:24:ab:cf BRHWaddr ff:ff:ff:ff:ff:ff
    inet addr:10.10.10.147  Bcast: 10.10.10.255 Mask: 255.0.0.0
        UP RUNNING pat MTU:1500 ReasmMAX:65535 Group:2
        IPRX bytes:19810763 unicastpkts:11515 brcastpkts:290669
        IPTX bytes:853114 unicastpkts:11662 brcastpkts:0      droppkts:0
        HWRX bytes:0  unicastpkts:0      brcastpkts:0
        HWTX bytes:0  unicastpkts:0      brcastpkts:0      droppkts:0
0   loop      Type:0
    inet addr:127.0.0.1      Bcast:127.255.255.255 Mask:255.0.0.0
        UP RUNNING      MTU:1500 ReasmMAX:65535 Group:1
        IPRX bytes:116     unicastpkts:0      brcastpkts:2
        IPTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
        HWRX bytes:0      unicastpkts:0      brcastpkts:0
        HWTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
=>
```

RELATED COMMANDS:**ip apdelete**

Remove an IP address from an interface.

ip aplist

Show current IP addresses.

ip apdelete

Remove an IP address from an interface.

SYNTAX:

ip apdelete	addr = <ip-address>
--------------------	----------------------------------

addr	The IP address to delete.	REQUIRED
-------------	---------------------------	----------

EXAMPLE:

```
=>ip aplist
2 eth0      Type:EthernetHWaddr 00:80:9f:24:ab:cf BRHWaddr ff:ff:ff:ff:ff:ff
    inet addr:10.0.0.2      Bcast: 10.0.0.255      Mask: 255.255.255.0
        UP RUNNING      pat MTU:1500 ReasmMAX:65535 Group:2
        IPRX bytes:0      unicastpkts:0      brcastpkts:0
        IPTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
        HWRX bytes:0      unicastpkts:0      brcastpkts:0
        HWTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
1 eth0      Type:EthernetHWaddr 00:80:9f:24:ab:cf BRHWaddr ff:ff:ff:ff:ff:ff
    inet addr:10.10.10.147     Bcast: 10.10.10.255      Mask: 255.0.0.0
        UP RUNNING      pat MTU:1500 ReasmMAX:65535 Group:2
        IPRX bytes:19791886  unicastpkts:11341 brcastpkts:290555
        IPTX bytes:839550  unicastpkts:11477 brcastpkts:0      droppkts:0
        HWRX bytes:0      unicastpkts:0      brcastpkts:0
        HWTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
0 loop      Type:0
    inet addr:127.0.0.1      Bcast:127.255.255.255      Mask:255.0.0.0
        UP RUNNING      MTU:1500 ReasmMAX:65535 Group:1
        IPRX bytes:116      unicastpkts:0      brcastpkts:2
        IPTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
        HWRX bytes:0      unicastpkts:0      brcastpkts:0
        HWTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
=>ip apdelete addr=10.0.0.2
=>ip aplist
1 eth0      Type:EthernetHWaddr 00:80:9f:24:ab:cf BRHWaddr ff:ff:ff:ff:ff:ff
    inet addr:10.10.10.147     Bcast: 10.10.10.255      Mask: 255.0.0.0
        UP RUNNING      pat MTU:1500 ReasmMAX:65535 Group:2
        IPRX bytes:19791886  unicastpkts:11341 brcastpkts:290555
        IPTX bytes:839550  unicastpkts:11477 brcastpkts:0      droppkts:0
        HWRX bytes:0      unicastpkts:0      brcastpkts:0
        HWTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
0 loop      Type:0
    inet addr:127.0.0.1      Bcast:127.255.255.255      Mask:255.0.0.0
        UP RUNNING      MTU:1500 ReasmMAX:65535 Group:1
        IPRX bytes:116      unicastpkts:0      brcastpkts:2
        IPTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
        HWRX bytes:0      unicastpkts:0      brcastpkts:0
        HWTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
=>
```

RELATED COMMANDS:

ip apadd	Add an IP address to an interface.
ip aplist	Show current IP addresses.

ip aplist

Show a list of all configured IP addresses.

SYNTAX:

```
ip aplist
```

EXAMPLE:

```
=>ip aplist
2   eth0      Type:EthernetHWaddr 00:80:9f:24:ab:cf BRHAddr ff:ff:ff:ff:ff:ff
      inet addr:10.0.0.2          Bcast: 10.0.0.255 Mask: 255.255.255.0
      UP RUNNING pat MTU:1500 ReasmMAX:65535 Group:2
      IPRX bytes:0      unicastpkts:0 brcastpkts:0
      IPTX bytes:0      unicastpkts:0 brcastpkts:0      dropkts:0
      HWRX bytes:0      unicastpkts:0 brcastpkts:0
      HWTX bytes:0      unicastpkts:0 brcastpkts:0      dropkts:0
1   eth0      Type:EthernetHWaddr 00:80:9f:24:ab:cf BRHAddr ff:ff:ff:ff:ff:ff
      inet addr:10.10.10.147    Bcast: 10.10.10.255 Mask: 255.0.0.0
      UP RUNNING pat MTU:1500 ReasmMAX:65535 Group:2
      IPRX bytes:19791886 unicastpkts:11341 brcastpkts:290555
      IPTX bytes:839550 unicastpkts:11477 brcastpkts:0      dropkts:0
      HWRX bytes:0      unicastpkts:0 brcastpkts:0
      HWTX bytes:0      unicastpkts:0 brcastpkts:0      dropkts:0
0   loop      Type:0
      inet addr:127.0.0.1      Bcast:127.255.255.255 Mask:255.0.0.0
      UP RUNNING      MTU:1500 ReasmMAX:65535 Group:1
      IPRX bytes:116      unicastpkts:0 brcastpkts:2
      IPTX bytes:0      unicastpkts:0 brcastpkts:0      dropkts:0
      HWRX bytes:0      unicastpkts:0 brcastpkts:0
      HWTX bytes:0      unicastpkts:0 brcastpkts:0      dropkts:0
=>
```

RELATED COMMANDS:

ip apadd	Add an IP address to an interface.
ip apdelete	Remove an IP address from an interface.

ip arpadd

Add a static entry to the **SpeedTouch™ Pro with Firewall** ARP cache.

SYNTAX:

ip arpadd	<i>intf = <interface name></i>
	<i>ip = <ip-address></i>
	<i>[hwaddr = <hardware-address>]</i>

<i>intf</i>	The interface name.	REQUIRED
<i>ip</i>	The IP address.	REQUIRED
<i>[hwaddr]</i>	The hardware address (e.g. the Ethernet MAC address).	OPTIONAL

EXAMPLE:

```
=>ip arplist
Intf      IP-address      HW-address      Type
eth0      10.0.0.1        00:01:42:5f:7d:81  DYNAMIC
eth0      10.0.0.8        00:a0:24:ae:66:e1  DYNAMIC
eth0      10.0.1.99       52:41:53:20:20:4d  STATIC
eth0      10.0.1.100      52:41:53:20:f0:90  STATIC
=>ip arpadd intf=eth0 ip=10.0.0.2 hwaddr=00:10:a4:d0:9a:db
=>ip arplist
Intf      IP-address      HW-address      Type
eth0      10.0.0.1        00:01:42:5f:7d:81  DYNAMIC
eth0      10.0.0.8        00:a0:24:ae:66:e1  DYNAMIC
eth0      10.0.1.99       52:41:53:20:20:4d  STATIC
eth0      10.0.1.100      52:41:53:20:f0:90  STATIC
eth0      10.0.0.2        00:10:a4:d0:9a:db  STATIC
=>
```

RELATED COMMANDS:

ip arpdelete	Delete an ARP entry.
ip arplist	Show current ARP cache.

ip arpdelete

Remove an entry from the **SpeedTouch™ Pro with Firewall** ARP cache.

SYNTAX:

ip arpdelete	intf = <interface name>
	ip = <ip-address>
	[hwaddr = <hardware-address>]

<i>intf</i>	The interface name.	REQUIRED
<i>ip</i>	The IP address.	REQUIRED
<i>[hwaddr]</i>	The hardware address.	OPTIONAL

EXAMPLE:

```
=>ip arplist
Intf      IP-address      HW-address      Type
eth0      10.0.0.1        00:01:42:5f:7d:81  DYNAMIC
eth0      10.0.0.8        00:a0:24:ae:66:e1  DYNAMIC
eth0      10.0.1.99       52:41:53:20:20:4d  STATIC
eth0      10.0.1.100      52:41:53:20:f0:90  STATIC
eth0      10.0.0.2        00:10:a4:d0:9a:db  STATIC
=>ip arpdelete intf=eth0 ip=10.0.0.2 hwaddr=00:10:a4:d0:9a:db
=>ip arplist
Intf      IP-address      HW-address      Type
eth0      10.0.0.1        00:01:42:5f:7d:81  DYNAMIC
eth0      10.0.0.8        00:a0:24:ae:66:e1  DYNAMIC
eth0      10.0.1.99       52:41:53:20:20:4d  STATIC
eth0      10.0.1.100      52:41:53:20:f0:90  STATIC
eth0      10.0.0.2        00:10:a4:d0:9a:db  STATIC
=>
```

RELATED COMMANDS:

ip arpadd	Add a static ARP entry.
ip arplist	Show current ARP cache.

ip arplist

Show the **SpeedTouch™ Pro with Firewall** ARP cache.

SYNTAX:

```
ip arplist
```

EXAMPLE OUTPUT:

=>ip arplist	IP-address	HW-address	Type
Intf			
eth0	10.0.0.1	00:01:42:5f:7d:81	DYNAMIC
eth0	10.0.0.8	00:a0:24:ae:66:e1	DYNAMIC
eth0	10.0.1.99	52:41:53:20:20:4d	STATIC
eth0	10.0.1.100	52:41:53:20:f0:90	STATIC
eth0	10.0.0.2	00:10:a4:d0:9a:db	STATIC
=>			

RELATED COMMANDS:

- | | |
|---------------------|--------------------------------------|
| ip arpadd | Add a static entry to the ARP cache. |
| ip arpdelete | Delete an entry from the ARP cache. |

ip config

Show/set global IP stack configuration options.

SYNTAX:

ip config	[forwarding = <{off on}>] [firewalling = <{off on}>] [redirects = <{off on}>] [sourcerouting = <{off on}>] [netbroadcasts = <{off on}>] [ttl = <number{0-255}>] [fraglimit = <number{1-1024}>] [defragmode = <{normal always nat}>] [addrcheck = <{off own static dynamic}>] [mssclamping = <{off on}>]	
[forwarding]	Disable (off) or enable (on) the IP routing functionality.	OPTIONAL
[firewalling]	Enable (on) or disable (off) IP firewalling (master switch). If applicable the CLI firewall level allows configuration of the SpeedTouch™ Pro with Firewall firewall. For security reasons this parameter is enabled per default. It is strongly recommended never to disable the SpeedTouch™ Pro with Firewall firewall.	OPTIONAL
[redirects]	Disable (off) or enable (on) the sending of ICMP redirect messages. A router can send a redirect message in case a shorter path than the path followed is discovered. For security reasons this parameter is disabled per default.	OPTIONAL
[sourcerouting]	Disallow (off) or allow (on) IP source routed packets. IP source routed packets are packets with the route to follow specified in the header. For security reasons this parameter is disabled per default.	OPTIONAL
[netbroadcasts]	Disallow (off) or allow (on) net directed broadcasts. This parameter is per default disabled. In case netbroadcasts are allowed no traces of netbroadcasts are generated.	OPTIONAL
[ttl]	A number between 0 and 255. Represents the default time-to-live (ttl) for locally generated IP packets. This parameter determines the number of hop-counts the IP packet may pass before it is dropped. Generally the time-to-live is 64 hop-counts. By limiting the time-to-live continuous circulation of IP packets on the network without ever reaching a destination is avoided.	OPTIONAL
[fraglimit]	A number between 1 and 1024. Represents the maximum number of IP packet fragments waiting for completion. Generally the fragmentation limit is 64. By limiting the fragmentation limit the depletion of the buffer is avoided.	OPTIONAL

[defragmode]	Define which packets are reassembled under which circumstances. Choose between: <ul style="list-style-type: none">▪ normal Packets to be forwarded will not be reassembled. Packets with local destination, i.e. destined for the SpeedTouch™ Pro with Firewall, are reassembled.▪ always Packets are always reassembled.▪ nat Same behaviour as normal except for packets to be forwarded through the NAT engine. Packets on which address translation is performed are reassembled as the NAT engine requires the entire packet.	OPTIONAL
[addrcheck]	Set the level of IP address checks. Choose between: <ul style="list-style-type: none">▪ off No address checking is performed. For advanced users only; in normal circumstances there should always be some kind of address checking.▪ own Minimum level of checking. Only the address configuration on the SpeedTouch™ Pro with Firewall is checked.▪ static Checking of the address configuration of the SpeedTouch™ Pro with Firewall and also of traffic: addresses of incoming packets; this checking is related to constants (e.g. an address may not be entirely composed of one's or zero's).▪ dynamic Besides the address configuration of the SpeedTouch™ Pro with Firewall itself, and besides the checking of traffic on a constants level, additional checking is performed on the IP addresses that are determined by the configuration, more specifically by the network.	OPTIONAL
[mssclamping]	Disable (off) or enable (on) mss clamping for low mtu interfaces. Mss clamping assures that the size of a TCP packet never exceeds the available mtu of the outgoing interface. It is recommended not to disable this parameter.	OPTIONAL

EXAMPLE:

```
=>ip config
Forwarding on
Firewalling off
Sendredirects off
SourceRouting on
NetBroadcasts off
Default TTL 128
Fraglimit 32 fragments
Fragcount currently 0 fragments
Defragment mode : always
Address checks : static
Mss clamping : on
=>ip config firewalling=on ttl=64 fraglimit=64 defragmode=nat
=>ip config
Forwarding on
Firewalling on
Sendredirects off
SourceRouting on
NetBroadcasts off
Default TTL 64
Fraglimit 64 fragments
Fragcount currently 0 fragments
Defragment mode : nat
Address checks : static
Mss clamping : on
=>
```

RELATED COMMANDS:

ip ifconfig Configure interface parameters.

ip flush

Flush complete IP configuration. Dynamic configurations (e.g. from PPP or CIP links) remain. The flush command does not impact previously saved configurations.

As an **ip flush** causes all local IP connectivity to be deleted, do not execute this command during an IP based local connection, e.g. a Telnet CLI session, or web based CLI access.

SYNTAX:

```
ip flush
```

EXAMPLE:

```
=>ip aplist
3    cipl      Type:ATM
      inet addr:172.16.0.5      Bcast:172.16.0.255      Mask:255.255.255.0
          UP RUNNING  pat  MTU:9180  ReasmMAX:65535  Group:0
          IPRX bytes:0      unicastpkts:0      brcastpkts:0
          IPTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
          HWRX bytes:0      unicastpkts:0      brcastpkts:0
          HWTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
2    eth0      Type:EthernetHWaddr 00:80:9f:24:ab:cf  BRHWaddr ff:ff:ff:ff:ff:ff
      inet addr:10.0.0.2      Bcast: 10.0.0.255      Mask: 255.255.255.0
          UP RUNNING  pat  MTU:1500  ReasmMAX:65535  Group:2
          IPRX bytes:0      unicastpkts:0      brcastpkts:0
          IPTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
          HWRX bytes:0      unicastpkts:0      brcastpkts:0
          HWTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
0    loop      Type:0
      inet addr:127.0.0.1      Bcast:127.255.255.255  Mask:255.0.0.0
          UP RUNNING  MTU:1500  ReasmMAX:65535  Group:1
          IPRX bytes:116     unicastpkts:0      brcastpkts:2
          IPTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
          HWRX bytes:0      unicastpkts:0      brcastpkts:0
          HWTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
=>ip flush
=>ip aplist
3    cipl      Type:ATM
      inet addr:172.16.0.5      Bcast:172.16.0.255      Mask:255.255.255.0
          UP RUNNING  pat  MTU:9180  ReasmMAX:65535  Group:0
          IPRX bytes:0      unicastpkts:0      brcastpkts:0
          IPTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
          HWRX bytes:0      unicastpkts:0      brcastpkts:0
          HWTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
0    loop      Type:0
      inet addr:127.0.0.1      Bcast:127.255.255.255  Mask:255.0.0.0
          UP RUNNING  MTU:1500  ReasmMAX:65535  Group:1
          IPRX bytes:116     unicastpkts:0      brcastpkts:2
          IPTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
          HWRX bytes:0      unicastpkts:0      brcastpkts:0
          HWTX bytes:0      unicastpkts:0      brcastpkts:0      droppkts:0
=>
```

RELATED COMMANDS:

ip load	Load saved or default IP configuration.
ip save	Save current IP configuration.

ip ifconfig

Configure interface parameters.

SYNTAX:

ip ifconfig	intf = <interface name> [mtu = <number{293–20000}>] [status = <{down up}>] [hwaddr = <hardware–address>] [group = <{wan local lan}>]
--------------------	---

<i>intf</i>	The IP interface name.	REQUIRED
<i>[mtu]</i>	A number between 293 and 20000. Represents the maximum transmission unit, i.e. the maximum packet size (including IP header) to use on this interface. The default value depends on the connection and packet service for which the interface was created.	OPTIONAL
<i>[status]</i>	The administrative status of the interface. Choose between: <ul style="list-style-type: none">▪ down▪ up	OPTIONAL
<i>[hwaddr]</i>	The hardware address (e.g. the Ethernet MAC address) of this interface.	OPTIONAL
<i>[group]</i>	The group this interface belongs to (e.g. for oriented firewalling).	OPTIONAL

EXAMPLE:

=>ip iflist	Interface GRP MTU RX TX TX-DROP STATUS HWADDR
0 loop	1 1500 116 0 0 UP
1 eth0	2 3000 21045795 1019664 0 UP 00:80:9f:24:ab:cf
2 NewMer	0 1500 0 0 0 UP 00:80:9f:24:ab:cf
5 cip0	0 9180 0 0 0 UP
=>ip ifconfig intf=eth0 mtu=1500	
=>ip iflist	Interface GRP MTU RX TX TX-DROP STATUS HWADDR
0 loop	1 1500 116 0 0 UP
1 eth0	2 1500 21054963 1025417 0 UP 00:80:9f:24:ab:cf
2 NewMer	0 1500 0 0 0 UP 00:80:9f:24:ab:cf
5 cip0	0 9180 0 0 0 UP
=>	

RELATED COMMANDS:

ip config

Show/set global IP stack configuration options.

ip iflist

Show all current interfaces.

SYNTAX:

```
ip iflist
```

EXAMPLE OUTPUT:

```
=>ip iflist
Interface   GRP    MTU     RX      TX      TX-DROP    STATUS     HWADDR
0  loop      1      1500    116     0        0          UP
1  eth0      2      3000   21045795 1019664    0          UP          00:80:9f:24:ab:cf
2  NewMer    0      1500    0        0        0          UP          00:80:9f:24:ab:cf
5  cip0      0      9180    0        0        0          UP
=>
```

RELATED COMMANDS:

ip ifconfig Configure interface parameters.

ip load

Load saved (or default) IP configuration.

Execute **ip flush** prior to **ip load**.

SYNTAX:

ip load	[defaults = <yes no>]
----------------	------------------------------------

[defaults]	Load factory defaults (yes) or saved configuration (no). Not specifying this parameter loads the saved configuration	OPTIONAL
-------------------	---	----------

EXAMPLE:

```
=>ip rtlist
  Destination      Source      Gateway      Intf      Mtrc
  192.16.11.0/24   192.16.11.0/24  192.16.11.140eth0  0
  172.16.1.1/32    0.0.0.0/0     172.16.1.1     cip0     0
  192.16.11.140/32 0.0.0.0/0     192.16.11.140eth0  0
  127.0.0.1/32    0.0.0.0/0     127.0.0.1      loop     0
  172.16.1.0/24    0.0.0.0/0     172.16.1.1     cip0     0
  192.16.11.0/24   0.0.0.0/0     192.16.11.140eth0  0
=>ip save
=>ip flush
=>ip rtlist
  Destination      Source      Gateway      Intf      Mtrc
  172.16.1.1/32    0.0.0.0/0     172.16.1.1     cip0     0
  127.0.0.1/32    0.0.0.0/0     127.0.0.1      loop     0
  172.16.1.0/24    0.0.0.0/0     172.16.1.1     cip0     0
=>ip load defaults=yes
=>ip rtlist
  Destination      Source      Gateway      Intf      Mtrc
  10.0.0.0/8        10.0.0.0/8    10.0.0.138    eth0     0
  255.255.255.255/32 0.0.0.0/0     10.0.0.138    eth0     0
  10.0.0.138/32    0.0.0.0/0     10.0.0.138    eth0     0
  172.16.1.1/32    0.0.0.0/0     172.16.1.1     cip0     0
  127.0.0.1/32    0.0.0.0/0     127.0.0.1      loop     0
  172.16.1.0/24    0.0.0.0/0     172.16.1.1     cip0     0
  10.0.0.0/8        0.0.0.0/0     10.0.0.138    eth0     0
  0.0.0.0/0         0.0.0.0/0     10.0.0.138    eth0     0
=>ip load
=>ip rtlist
  Destination      Source      Gateway      Intf      Mtrc
  192.16.11.0/24   192.16.11.0/24  192.16.11.140eth0  0
  172.16.1.1/32    0.0.0.0/0     172.16.1.1     cip0     0
  192.16.11.140/32 0.0.0.0/0     192.16.11.140eth0  0
  127.0.0.1/32    0.0.0.0/0     127.0.0.1      loop     0
  172.16.1.0/24    0.0.0.0/0     172.16.1.1     cip0     0
  192.16.11.0/24   0.0.0.0/0     192.16.11.140eth0  0
=>
```

RELATED COMMANDS:

ip flush	Flush complete IP configuration.
ip save	Save current IP configuration.

ip ping

Send ICMP ECHO_REQUEST packets.

SYNTAX:

ip ping	addr = <ip-address>
	[count = <number{1-1000000}>]
	[size = <number{1-20000}>]
	[interval = <number{100-1000000}>]
	[listen = <{off on}>]

addr	The destination IP address.	REQUIRED
[count]	A number between 1 and 1000000. Represents the number of pings to send.	OPTIONAL
[size]	A number between 1 and 20000 (bytes). Represents the size of the ping packet(s).	OPTIONAL
[interval]	A number between 100 and 10000000 (milliseconds). Represents the intermediate interval between two sent ICMP packets.	OPTIONAL
[listen]	Listen for incoming ICMP packets (on) or only send ICMP packets (off).	OPTIONAL

EXAMPLE:

```
=>ip ping addr=10.0.0.148 listen=off
=>ip ping addr=10.0.0.148 listen=on
9 bytes from 10.0.0.148: Echo Request
=>ip ping addr=10.0.0.148 count=15 listen=on
9 bytes from 10.0.0.148: Echo Request
=>
```

RELATED COMMANDS:

ip sendto Send UDP packets.

ip rtadd

Add a route to the **SpeedTouch™ Pro with Firewall** routing table.

SYNTAX:

```
ip rtadd      dst = <ip-address>
                [dstmksk = <ip-mask(dotted or cidr)>]
                [src = <ip-address>]
                [srcmsk = <ip-mask(dotted or cidr)>]
                [gateway = <ip-address>]
                [intf = <interface name>]
                [metric = <number{0-100}>]
                [type = <number>]
```

<i>dst</i>	The destination IP address(es) for this route. Supports cidr notation.	REQUIRED
[<i>dstmksk</i>]	The destination IP address mask.	OPTIONAL
[<i>src</i>]	The source IP address(es) allowed to use this route. Supports cidr notation.	OPTIONAL
[<i>srcmsk</i>]	The source IP address mask.	OPTIONAL
[<i>gateway</i>]	The IP address of the next hop. Must be directly connected. The parameters 'gateway' and 'intf' are mutually exclusive.	OPTIONAL
[<i>intf</i>]	Only for special interface routes : the outgoing IP interface name. The parameters 'gateway' and 'intf' are mutually exclusive.	OPTIONAL
[<i>metric</i>]	The metric for this route (currently not used).	OPTIONAL
[<i>type</i>]	Route classification. For internal use only.	OPTIONAL

EXAMPLE:

```
=>ip rtlist
  Destination      Source      Gateway      Intf      Mtrc
  10.0.0.0/24      10.0.0.0/24  10.0.0.140  eth0      0
  10.0.0.140/32    0.0.0.0/0    10.0.0.140  eth0      0
  127.0.0.1/32     0.0.0.0/0    127.0.0.1   loop      0
=>ip rtadd dst=10.10.0.0/24 src=10.0.0.0/24 gateway=10.0.0.140
=>ip rtlist
  Destination      Source      Gateway      Intf      Mtrc
  10.0.0.0/24      10.0.0.0/24  10.0.0.140  eth0      0
  10.10.0.0/24     10.0.0.0/24  10.0.0.140  eth0      0
  10.0.0.140/32    0.0.0.0/0    10.0.0.140  eth0      0
  127.0.0.1/32     0.0.0.0/0    127.0.0.1   loop      0
=>
```

RELATED COMMANDS:

ip rtdelete	Remove a route from the routing table.
ip rtlist	Show current routing table.

ip rtdelete

Delete a route from the **SpeedTouch™ Pro with Firewall** routing table.

SYNTAX:

ip rtdelete	dst = <ip-address> [dstmsk = <ip-mask(dotted or cidr)>] [src = <ip-address>] [srcmsk = <ip-mask(dotted or cidr)>] [gateway = <ip-address>] [intf = <interface name>]	
dst	The destination IP address(es) of the route. Supports cidr notation.	REQUIRED
[dstmsk]	The destination IP address mask.	OPTIONAL
[src]	The source IP address(es) of the route. Supports cidr notation.	OPTIONAL
[srcmsk]	The source IP address mask.	OPTIONAL
[gateway]	The IP address of the next hop. Must be directly connected. The parameters 'gateway' and 'intf' are mutually exclusive.	OPTIONAL
[intf]	Only for special interface routes : the outgoing IP interface name. The parameters 'gateway' and 'intf' are mutually exclusive.	OPTIONAL

EXAMPLE:

```
=>ip rtlist
Destination      Source        Gateway      Intf      Mtrc
10.0.0.0/24      10.0.0.0/24  10.0.0.140  eth0      0
10.10.0.0/24     10.0.0.0/24  10.0.0.140  eth0      0
10.0.0.140/32    0.0.0.0/0   10.0.0.140  eth0      0
127.0.0.1/32     0.0.0.0/0   127.0.0.1   loop      0
=>ip rtdelete dst=10.10.0.0/24 src=10.0.0.0/24 gateway=10.0.0.140
=>ip rtlist
Destination      Source        Gateway      Intf      Mtrc
10.0.0.0/24      10.0.0.0/24  10.0.0.140  eth0      0
10.0.0.140/32    0.0.0.0/0   10.0.0.140  eth0      0
127.0.0.1/32     0.0.0.0/0   127.0.0.1   loop      0
=>
```

RELATED COMMANDS:

ip rtadd	Add a route to the routing table.
ip rtlist	Show current routing table.

ip rtlist

Show current **SpeedTouch™ Pro with Firewall** routing table.

SYNTAX:

ip rtlist

EXAMPLE OUTPUT:

=>ip rtlist				
Destination	Source	Gateway	Intf	Mtrc
10.0.0.0/24	10.0.0.0/24	10.0.0.140	eth0	0
172.16.0.5/32	0.0.0.0/0	172.16.0.5	cip1	0
0.0.0.140/32	0.0.0.0/0	10.0.0.140	eth0	0
127.0.0.1/32	0.0.0.0/0	127.0.0.1	loop	0
10.0.0.0/24	0.0.0.0/0	10.0.0.140	eth0	0
172.16.0.0/24	0.0.0.0/0	172.16.0.5	cip1	1

RELATED COMMANDS:

ip rtadd	Add a route to the routing table.
ip rtdelete	Remove a route from the routing table.

ip save

Save current IP configuration.

SYNTAX:

ip save

EXAMPLE:

```
=>ip rtlist
  Destination      Source      Gateway      Intf      Mtrc
  192.16.11.0/24  192.16.11.0/24  192.16.11.140eth0  0
  172.16.1.1/32   0.0.0.0/0    172.16.1.1    cip0     0
  192.16.11.140/32 0.0.0.0/0   192.16.11.140eth0  0
  127.0.0.1/32   0.0.0.0/0    127.0.0.1    loop     0
  172.16.1.0/24   0.0.0.0/0    172.16.1.1    cip0     0
  192.16.11.0/24  0.0.0.0/0   192.16.11.140eth0  0
=>ip save
=>ip flush
=>ip rtlist
  Destination      Source      Gateway      Intf      Mtrc
  172.16.1.1/32   0.0.0.0/0    172.16.1.1    cip0     0
  127.0.0.1/32   0.0.0.0/0    127.0.0.1    loop     0
  172.16.1.0/24   0.0.0.0/0    172.16.1.1    cip0     0
=>ip load
=>ip rtlist
  Destination      Source      Gateway      Intf      Mtrc
  192.16.11.0/24  192.16.11.0/24  192.16.11.140eth0  0
  172.16.1.1/32   0.0.0.0/0    172.16.1.1    cip0     0
  192.16.11.140/32 0.0.0.0/0   192.16.11.140eth0  0
  127.0.0.1/32   0.0.0.0/0    127.0.0.1    loop     0
  172.16.1.0/24   0.0.0.0/0    172.16.1.1    cip0     0
  192.16.11.0/24  0.0.0.0/0   192.16.11.140eth0  0
=>
```

RELATED COMMANDS:

ip flush	Flush complete IP configuration.
ip load	Load saved or default IP configuration.

ip sendto

Send UDP packets.

SYNTAX:

ip sendto	addr = <ip-address> [count = <number{1-1000000}>] [size = <number{1-20000}>] [interval = <number{100-1000000}>] [listen = <{off on}>] [srcport = <number{1-65535}>] dstport = <number{1-65535}>	
addr	The destination IP address.	REQUIRED
[count]	A number between 1 and 1000000. Represents the number of UDP packets to send.	OPTIONAL
[size]	A number between 1 and 20000 (bytes). Represents the size of the ping packet(s).	OPTIONAL
[interval]	A number between 100 and 1000000 (milliseconds). Represents the intermediate interval between two sent UDP packets.	OPTIONAL
[listen]	Listen for incoming UDP packets (on) or only send UDP packets (off).	OPTIONAL
[srcport]	The UDP source port number to use.	OPTIONAL
dstport	The UDP destination port number to send to.	REQUIRED

EXAMPLE:

```
=>ip sendto addr=10.0.0.148 listen=on srcport=19 dstport=1025
=>ip sendto addr=10.0.0.148 listen=on srcport=19 dstport=1025
1 bytes from 10.0.0.148:1025
41
=>ip sendto addr=10.0.0.148 count=3 listen=on srcport=19 dstport=1025
1 bytes from 10.0.0.148:1025
41
1 bytes from 10.0.0.148:1025
41
1 bytes from 10.0.0.148:1025
41
=>
```

RELATED COMMANDS:

ip ping Send ICMP ECHO_REQUEST packets.

10 MER Commands

mer (to access the MER level)
mer flush
mer ifadd
mer ifattach
mer ifconfig
mer ifdelete
mer ifdetach
mer iflist
mer load
mer save

mer flush

Flush complete MER configuration.

The flush command does not impact previously saved configurations.

SYNTAX:

```
mer flush
```

EXAMPLE:

```
=>mer iflist
NewMer      : dest : Br3
                  Retry : 10    QoS : default   Encaps : llc/snap     Fcs : off
                  Connection State : connected
                  RX bytes: 0          frames: 0
                  TX bytes: 0          frames: 0          dropframes: 0
=>mer flush
=>mer iflist
=>
```

RELATED COMMANDS:

mer load

Load saved or default MER configuration.

mer save

Save current MER configuration.

mer ifadd

Create a new MER interface.

SYNTAX:

mer ifadd	[intf = <string>]
	[dest = <phonebook entry>]

[intf]	The name for the new MER interface. If not specified, the destination parameter must be specified. In this case the name of the destination will double as interface name.	OPTIONAL
[dest]	The destination for the new MER interface. Typically, an phonebook entry.	OPTIONAL

EXAMPLE:

```
=>mer iflist
NewMer   : dest : Br3
          Retry : 10   QoS : default   Encaps : llc/snap      Fcs : off
          Connection State : connected
          RX bytes: 0           frames: 0
          TX bytes: 0           frames: 0           dropframes: 0
=>phonebook list
Name      Type     Use   Address
Br1       bridge   1    8.35
Br2       bridge   1    8.36
CIPPPVC3  cip     1    8.82
CIPPPVC4  cip     1    8.83
=>mer ifadd intf=MoreMer dest=Br4
=>mer iflist
NewMer   : dest : Br3
          Retry : 10   QoS : default   Encaps : llc/snap      Fcs : off
          Connection State : connected
          RX bytes: 0           frames: 0
          TX bytes: 0           frames: 0           dropframes: 0
MoreMer   : dest : Br4
          Retry : 10   QoS : default   Encaps : llc/snap      Fcs : off
          Connection State : not-connected
=>
```

RELATED COMMANDS:

mer ifattach	Attach a MER interface.
mer ifconfig	Configure a MER interface.
mer ifdelete	Delete a MER interface.
mer ifdetach	Detach a MER interface.
mer iflist	Show current MER interfaces.

mer ifattach

Attach (i.e. connect) a MER interface.

SYNTAX:

mer ifattach	intf = <ifname>
---------------------	------------------------------

intf	The name of the MER interface to attach.	REQUIRED
-------------	--	----------

EXAMPLE:

```
=>mer iflist
NewMer      : dest : Br3
               Retry : 10   QoS : default   Encaps : llc/snap     Fcs : off
               Connection State : connected
               RX bytes: 0          frames: 0
               TX bytes: 0          frames: 0          dropframes: 0
MoreMer     : dest : Br4
               Retry : 10   QoS : default   Encaps : llc/snap     Fcs : off
               Connection State : not-connected
=>mer ifattach intf=MoreMer
=>mer iflist
NewMer      : dest : Br3
               Retry : 10   QoS : default   Encaps : llc/snap     Fcs : off
               Connection State : connected
               RX bytes: 0          frames: 0
               TX bytes: 0          frames: 0          dropframes: 0
MoreMer     : dest : Br4
               Retry : 10   QoS : default   Encaps : llc/snap     Fcs : off
               Connection State : connected
               RX bytes: 0          frames: 0
               TX bytes: 0          frames: 0          dropframes: 0
=>
```

RELATED COMMANDS:

mer ifadd	Create a new MER interface.
mer ifconfig	Configure a MER interface.
mer ifdelete	Delete a MER interface.
mer ifdetach	Detach a MER interface.
mer iflist	Show current MER interfaces.

mer ifconfig

Configure a MER interface.

SYNTAX:

mer ifconfig	intf = <ifname>
	[dest = <ifname>]
	[qos = <string>]
	[encaps = <{llc/snap vcmux}>]
	[retry = <number {0-65535}>]

intf	The name of the MER interface to configure.	REQUIRED
[dest]	The destination for this interface. Typically a phonebook entry. This parameter needs only to be specified in case of an interface created without specified destination.	OPTIONAL
[qos]	The name of a configured Quality Of Service book entry. This parameter never needs to be specified.	OPTIONAL
[encaps]	The type of encapsulation to be used for this bridge interface. Choose between: <ul style="list-style-type: none">▪ llc/snap▪ vcmux	OPTIONAL
[retry]	A number between 0 and 65535. Represents the number of WAN connection setup retries before giving up. By default the retry value is 10.	OPTIONAL

EXAMPLE:

```
=>mer iflist
MoreMer : dest : Br4
          Retry : 10   OoS : default   Encaps : vcmux   Fcs : off
          Connection State : connected
          RX bytes: 0           frames: 0
          TX bytes: 0           frames: 0       dropframes: 0
=>mer ifconfig intf=MoreMer encaps=llc/snap retry=15
=>mer iflist
MoreMer : dest : Br4
          Retry : 15   OoS : default   Encaps : llc/snap   Fcs : off
          Connection State : connected
          RX bytes: 0           frames: 0
          TX bytes: 0           frames: 0       dropframes: 0
=>
```

RELATED COMMANDS:

mer ifadd	Create a new MER interface.
mer ifattach	Attach a MER interface.
mer ifdelete	Delete a MER interface.
mer ifdetach	Detach a MER interface.
mer iflist	Show current MER interfaces.

mer ifdelete

Delete a MER interface.

SYNTAX:

<i>mer ifdelete</i>	<i>intf = <ifname></i>
----------------------------	-------------------------------------

<i>intf</i>	The name of the MER interface.	REQUIRED
-------------	--------------------------------	----------

EXAMPLE:

```
=>mer iflist
NewMer      : dest : Br3
              Retry : 10   QoS : default   Encaps : llc/snap     Fcs : off
              Connection State : connected
              RX bytes: 0          frames: 0
              TX bytes: 0          frames: 0          dropframes: 0
MoreMer     : dest : Br4
              Retry : 10   QoS : default   Encaps : llc/snap     Fcs : off
              Connection State : not-connected
=>mer ifdelete intf=MoreMer
=>mer iflist
NewMer      : dest : Br3
              Retry : 10   QoS : default   Encaps : llc/snap     Fcs : off
              Connection State : connected
              RX bytes: 0          frames: 0
              TX bytes: 0          frames: 0          dropframes: 0
=>
```

RELATED COMMANDS:

<i>mer ifadd</i>	Create a new MER interface.
<i>mer ifattach</i>	Attach a MER interface.
<i>mer ifconfig</i>	Configure a MER interface.
<i>mer ifdetach</i>	Detach a MER interface.
<i>mer iflist</i>	Show current MER interfaces.

mer ifdetach

Detach a MER interface.

SYNTAX:

mer ifdetach	intf = <ifname>
---------------------	------------------------------

<i>intf</i>	The name of the MER interface.	REQUIRED
-------------	--------------------------------	----------

EXAMPLE:

```
=>mer iflist
NewMer      : dest : Br3
              Retry : 10    QoS : default   Encaps : llc/snap     Fcs : off
              Connection State : connected
              RX bytes: 0           frames: 0
              TX bytes: 0           frames: 0           dropframes: 0
MoreMer     : dest : Br4
              Retry : 10    QoS : default   Encaps : llc/snap     Fcs : off
              Connection State : connected
              RX bytes: 0           frames: 0
              TX bytes: 0           frames: 0           dropframes: 0
=>mer ifdetach intf=MoreMer
=>mer iflist
NewMer      : dest : Br3
              Retry : 10    QoS : default   Encaps : llc/snap     Fcs : off
              Connection State : connected
              RX bytes: 0           frames: 0
              TX bytes: 0           frames: 0           dropframes: 0
MoreMer     : dest : Br4
              Retry : 10    QoS : default   Encaps : llc/snap     Fcs : off
              Connection State : not-connected
=>
```

RELATED COMMANDS:

mer ifadd	Create a new MER interface.
mer ifattach	Attach a MER interface.
mer ifconfig	Configure a MER interface.
mer ifdelete	Delete a MER interface.
mer iflist	Show current MER interfaces.

mer iflist

Show all or a specified MER interface(s).

SYNTAX:

<i>mer iflist</i>	<i>[intf = <ifname>]</i>
--------------------------	---------------------------------------

<i>[intf]</i>	The name of the MER interface. If not specified all MER interfaces are listed.	OPTIONAL
----------------------	---	----------

EXAMPLE OUTPUT:

```
=>mer iflist
NewMer    : dest : Br3
            Retry : 10   QoS : default   Encaps : llc/snap      Fcs : off
            Connection State : connected
            RX bytes: 0           frames: 0
            TX bytes: 0           frames: 0           dropframes: 0
MoreMer   : dest : Br4
            Retry : 10   QoS : default   Encaps : llc/snap      Fcs : off
            Connection State : connected
            RX bytes: 0           frames: 0
            TX bytes: 0           frames: 0           dropframes: 0
=>
```

RELATED COMMANDS:

<i>mer ifadd</i>	Create a new MER interface.
<i>mer ifattach</i>	Attach a MER interface.
<i>mer ifconfig</i>	Configure a MER interface.
<i>mer ifdelete</i>	Delete a MER interface.
<i>mer detach</i>	Detach a MER interface.

mer load

Load saved (or default) MER configuration.

Execute **mer flush** prior to **mer load**.

SYNTAX:

mer load	[defaults <yes no>]
-----------------	----------------------------------

[defaults]	Load factory defaults (yes) or saved configuration (no).	OPTIONAL
	Not specifying this parameter loads the saved configuration	

EXAMPLE:

```
=>mer iflist
NewMer    : dest : Br3
            Retry : 10   QoS : default   Encaps : llc/snap     Fcs : off
            Connection State : connected
            RX bytes: 0           frames: 0
            TX bytes: 0           frames: 0           dropframes: 0
MoreMer   : dest : Br4
            Retry : 10   QoS : default   Encaps : llc/snap     Fcs : off
            Connection State : not-connected

=>mer save
=>mer flush
=>mer iflist
=>mer load
=>mer iflist
NewMer    : dest : Br3
            Retry : 10   QoS : default   Encaps : llc/snap     Fcs : off
            Connection State : connected
            RX bytes: 0           frames: 0
            TX bytes: 0           frames: 0           dropframes: 0
MoreMer   : dest : Br4
            Retry : 10   QoS : default   Encaps : llc/snap     Fcs : off
            Connection State : not-connected
=>
```

RELATED COMMANDS:

mer flush	Flush complete MER configuration.
mer save	Save current MER configuration.

mer save

Save current MER configuration.

SYNTAX:

```
mer save
```

EXAMPLE:

```
=>mer iflist
NewMer   : dest : Br3
          Retry : 10   QoS : default   Encaps : llc/snap      Fcs : off
          Connection State : connected
          RX bytes: 0           frames: 0
          TX bytes: 0           frames: 0           dropframes: 0
MoreMer   : dest : Br4
          Retry : 10   QoS : default   Encaps : llc/snap      Fcs : off
          Connection State : not-connected
=>mer save
=>mer flush
=>mer iflist
=>mer load
=>mer iflist
NewMer   : dest : Br3
          Retry : 10   QoS : default   Encaps : llc/snap      Fcs : off
          Connection State : connected
          RX bytes: 0           frames: 0
          TX bytes: 0           frames: 0           dropframes: 0
MoreMer   : dest : Br4
          Retry : 10   QoS : default   Encaps : llc/snap      Fcs : off
          Connection State : not-connected
=>
```

RELATED COMMANDS:

mer flush	Flush complete MER configuration.
mer load	Load saved or default MER configuration.

11 NAT Commands

nat (to access the NAT level)
nat applist
nat bind
nat bindlist
nat create
nat defserver
nat delete
nat disable
nat enable
nat flush
nat list
nat load
nat save
nat unbind

nat applist

List available NAPT protocol helpers.

Certain protocols are ‘sensitive’ to NAPT in that they do not function properly when dealing with it. This list shows which ‘NAPT-sensitive’ applications are supported on the **SpeedTouch™ Pro with Firewall**, i.e. the inherent knowledge of the **SpeedTouch™ Pro with Firewall** on this matter.

SYNTAX:

```
nat applist
```

EXAMPLE OUTPUT:

```
->nat applist
Application Proto DefaultPort
H254      tcp    0
H323      tcp    1720
RAUDIO(PNA)  tcp    7070
RTSP      tcp    554
IRC       tcp    6667
FTP       tcp    21
=>
```

RELATED COMMANDS:

nat bind

Create a new helper/port binding.

nat bindlist

List current NAPT helper/port bindings.

nat unbind

Delete an existing helper/port binding.

nat bind

Create a new helper/port binding.

SYNTAX:

nat bind	application = <string>
	port = <TCP/UDP service name or port number>

<i>application</i>	The name of a NAPT application helper. The name must be spelled exactly as listed in the application list (nat applist).	REQUIRED
<i>port</i>	The port number this application handler should work on.	REQUIRED

EXAMPLE INPUT:

```
=>nat applist
Application Proto DefaultPort
H254      tcp    0
H323      tcp    1720
RAUDIO(PNA) tcp    7070
RTSP      tcp    554
IRC       tcp    6667
FTP       tcp    21
=>nat bindlist
Application Proto Port
H323      tcp    1720
FTP       tcp    21
RTSP      tcp    554
IRC       tcp    6667
RAUDIO(PNA) tcp    7070
=>nat bind application=RAUDIO(PNA) port=7071
=>nat bindlist
Application Proto Port
RAUDIO(PNA) tcp    7071
H323      tcp    1720
FTP       tcp    21
RTSP      tcp    554
IRC       tcp    6667
RAUDIO(PNA) tcp    7070
=>
```

RELATED COMMANDS:

- | | |
|---------------------|---|
| nat applist | List available NAPT protocol helpers. |
| nat bindlist | List current NAPT helper/port bindings. |
| nat unbind | Delete an existing helper/port binding. |

nat bindlist

List current NAPT helper/port bindings.

SYNTAX:

```
nat bindlist
```

EXAMPLE OUTPUT:

```
=>nat bindlist
Application Proto Port
RAUDIO(PNA)  tcp    7071
H323        tcp    1720
FTP          tcp    21
RTSP         tcp    554
IRC          tcp    6667
RAUDIO(PNA)  tcp    7070
=>
```

RELATED COMMANDS:

nat applist	List available NAPT protocol helpers.
nat bind	Create a new NAPT helper/port binding.
nat unbind	Delete an existing helper/port binding.

nat create

Create a static NAPT entry. Typically used to install specific servers behind the **SpeedTouch™ Pro with Firewall**'s NAPT device.

SYNTAX:

nat create	protocol = <IP protocol name or number> inside_addr = <ip-address> [inside_port = <TCP/UDP service name or port number>] outside_addr = <ip-address> [outside_port = <TCP/UDP service name or port number>]	
<i>protocol</i>	The IP protocol name (or number) of the incoming stream.	REQUIRED
<i>inside_addr</i>	The IP address of the local host (intended to receive the incoming traffic) behind the SpeedTouch™ Pro with Firewall 's NAPT device. Typically, a private IP address.	REQUIRED
<i>[inside_port]</i>	The port number of the application on the local host. Applicable for TCP and UDP protocols. All other protocols do not need a port to be specified.	OPTIONAL
<i>outside_addr</i>	The apparent host IP address this application is running on, i.e. the NAPT enabled WAN IP address of the SpeedTouch™ Pro with Firewall . Use '0' to create a template. Such template will then be valid for any of SpeedTouch™ Pro with Firewall 's NAPT enabled IP addresses, e.g. also dynamically assigned/negotiated IP addresses.	REQUIRED
<i>[outside_port]</i>	The apparent port number this application is running on. Applicable for TCP and UDP protocols. All other protocols do not need a port to be specified.	OPTIONAL

EXAMPLE:

```
=>nat list
=>ip aplist
1   eth0      Type:EthernetHWaddr 00:80:9f:24:ab:cf BRHWaddr ff:ff:ff:ff:ff:ff
    inet addr:10.10.10.147      Bcast: 10.10.10.255      Mask: 255.0.0.0
        UP RUNNING      pat MTU:1500      ReasmMAX:65535 Group:2
        IPRX bytes:19791886      unicastpkts:11341 broadcastpkts:290555
        IPTX bytes:839550      unicastpkts:11477 broadcastpkts:0      droppkts:0
        HWRX bytes:0      unicastpkts:0      broadcastpkts:0
        HWTX bytes:0      unicastpkts:0      broadcastpkts:0      droppkts:0
5   cip0      Type:ATM
    inet addr:172.16.0.5      Bcast: 127.16.0.255      Mask: 255.255.255.0
        UP RUNNING      MTU:1500      ReasmMAX:65535 Group:0
        IPRX bytes:0      unicastpkts:0      broadcastpkts:0
        IPTX bytes:0      unicastpkts:0      broadcastpkts:0      droppkts:0
        HWRX bytes:0      unicastpkts:0      broadcastpkts:0
        HWTX bytes:0      unicastpkts:0      broadcastpkts:0      droppkts:0
0   loop      Type:0
    inet addr:127.0.0.1      Bcast:127.255.255.255      Mask:255.0.0.0
        UP RUNNING      MTU:1500      ReasmMAX:65535 Group:1
        IPRX bytes:116      unicastpkts:0      broadcastpkts:2
        IPTX bytes:0      unicastpkts:0      broadcastpkts:0      droppkts:0
        HWRX bytes:0      unicastpkts:0      broadcastpkts:0
        HWTX bytes:0      unicastpkts:0      broadcastpkts:0      droppkts:0
=>nat enable addr=172.16.0.5 type=pat
=>nat create protocol=tcp inside_addr=10.0.0.1 inside_port=80 outside_addr=172.16.0.5
  outside_port=1080
=>nat list
Indx Prot Inside-addr:PortOutside-addr:Port Foreign-addr:Port Flgs Expir State Control
1     6     10.0.0.138:80    172.16.0.5:1080    0.0.0.0:0          19     8     9
=>
```

RELATED COMMANDS:

nat delete	Delete a static NAPT entry.
nat disable	Disable NAPT on the specified IP address.
nat enable	Enable NAPT on one of the devices own IP addresses.
nat list	List NAPT connection database.

nat defserver

Define the default server behind the **SpeedTouch™ Pro with Firewall** NAPT device that receives all (unknown) incoming packets.

In typical LAN configurations one local 'default' server will be responsible for all WAN-LAN mail, http, ftp, ... connectivity. This command allows to specify this server. For specific services, use the **nat create** command.

SYNTAX:

nat defserver	[addr = <ip-address>]
----------------------	------------------------------------

[addr]	The IP address of the server (on the 'inside') that will receive all (unknown) incoming packets.	OPTIONAL
	If not specified the current default server is shown.	

EXAMPLE INPUT/OUTPUT:

=> nat defserver
Default server is undefined
=> nat defserver addr=10.0.0.1
=> nat defserver
Default server is 10.0.0.1
=>

nat delete

Delete a static NAPT entry.

SYNTAX:

nat delete	protocol = <IP protocol name or number>
	inside_addr = <ip-address>
	[inside_port = <TCP/UDP service name or port number>]
	outside_addr = <ip-address>
	[outside_port = <TCP/UDP service name or port number>]

protocol	The IP protocol name (or number) of the NAT entry.	REQUIRED
inside_addr	The IP address of the NAT entry.	REQUIRED
[inside_port]	The port number of the NAT entry.	OPTIONAL
outside_addr	The apparent host IP address of the NAT entry.	REQUIRED
[outside_port]	The apparent port number of the NAT entry.	OPTIONAL

EXAMPLE:

=>nat list	Indx Prot Inside-addr:PortOutside-addr:Port Foreign-addr:Port Flgs Expir State Control
1 6 10.0.0.138:80 172.16.0.5:1080 0.0.0.0:0	19 8 9
2 17 10.0.0.138:138 10.0.0.140:138 10.0.0.20:138	11 20 10
3 17 10.0.0.138:137 10.0.0.140:137 10.0.0.254:137	11 20 10
4 17 10.0.0.138:7938 10.0.0.140:7938 10.0.0.96:4756	11 20 10
5 17 10.0.0.138:513 10.0.0.140:513 10.0.0.109:513	11 20 10
6 17 10.0.0.138:111 10.0.0.140:111 10.0.0.96:4756	11 20 10
=>nat delete protocol=tcp inside_addr=10.0.0.138 inside_port=80 outside_addr=172.16.0.5 outside_port 1080	
=>nat list	Indx Prot Inside-addr:PortOutside-addr:Port Foreign-addr:Port Flgs Expir State Control
1 17 10.0.0.138:138 10.0.0.140:138 10.0.0.20:138	11 20 10
2 17 10.0.0.138:137 10.0.0.140:137 10.0.0.254:137	11 20 10
3 17 10.0.0.138:7938 10.0.0.140:7938 10.0.0.96:4756	11 20 10
4 17 10.0.0.138:513 10.0.0.140:513 10.0.0.109:513	11 20 10
5 17 10.0.0.138:111 10.0.0.140:111 10.0.0.96:4756	11 20 10
=>	

RELATED COMMANDS:

nat create	Create a static NAPT entry.
nat disable	Disable NAPT on one of the SpeedTouch™ Pro with Firewall IP addresses.
nat enable	Enable NAPT on one of the SpeedTouch™ Pro with Firewall IP addresses.
nat list	List NAPT connection database.

nat disable

Disable NAPT on a **SpeedTouch™ Pro with Firewall** IP address.

SYNTAX:

nat disable	addr = <ip-address>
--------------------	----------------------------------

addr	One of SpeedTouch™ Pro with Firewall 's IP addresses one which NAPT is enabled.	REQUIRED
-------------	--	----------

EXAMPLE:

```
=>nat list
Indx Prot Inside-addr:PortOutside-addr:Port Foreign-addr:Port Flgs Expir State Control
1    6    10.0.0.138:80 172.16.0.5:1080 0.0.0.0:0      19     8    9
2    17   10.0.0.138:138 10.0.0.140:138 10.0.0.20:138 11    20   10
3    17   10.0.0.138:137 10.0.0.140:137 10.0.0.254:137 11    20   10
4    17   10.0.0.138:7938 10.0.0.140:7938 10.0.0.96:4756 11    20   10
5    17   10.0.0.138:513 10.0.0.140:513 10.0.0.109:513 11    20   10
6    17   10.0.0.138:111 10.0.0.140:111 10.0.0.96:4756 11    20   10
=>nat disable addr 172.16.0.5
=>nat list
Indx Prot Inside-addr:PortOutside-addr:Port Foreign-addr:Port Flgs Expir State Control
1    17   10.0.0.138:138 10.0.0.140:138 10.0.0.20:138 11    20   10
2    17   10.0.0.138:137 10.0.0.140:137 10.0.0.254:137 11    20   10
3    17   10.0.0.138:7938 10.0.0.140:7938 10.0.0.96:4756 11    20   10
4    17   10.0.0.138:513 10.0.0.140:513 10.0.0.109:513 11    20   10
5    17   10.0.0.138:111 10.0.0.140:111 10.0.0.96:4756 11    20   10
=>
```

RELATED COMMANDS:

nat create	Create a static NAPT entry.
nat delete	Delete a static NAPT entry.
nat enable	Enable NAPT on one of the SpeedTouch™ Pro with Firewall IP addresses.
nat list	List NAPT connection database.

nat enable

Enable NAPT on a **SpeedTouch™ Pro with Firewall** IP address.

SYNTAX:

nat enable	addr = <ip-address>	
	[type = <{none pat}>]	

addr	The SpeedTouch™ Pro with Firewall IP address on which NAPT must be applied.	REQUIRED
[type]	Enable port translation (pat) or not (none).	OPTIONAL

EXAMPLE:

```
=>ip aplist
1   eth0      Type:EthernetHWaddr 00:80:9f:24:ab:cf BRHWaddr ff:ff:ff:ff:ff:ff
    inet addr:10.10.10.147  Bcast: 10.10.10.255  Mask: 255.0.0.0
        UP RUNNING          MTU:1500  ReasmMAX:65535 Group:2
        IPRX bytes:19791886  unicastpkts:11341 broadcastpkts:290555
        IPTX bytes:839550   unicastpkts:11477 broadcastpkts:0      droppkts:0
        HWRX bytes:0       unicastpkts:0   broadcastpkts:0
        HWTX bytes:0       unicastpkts:0   broadcastpkts:0      droppkts:0
0   loop      Type:0
    inet addr:127.0.0.1      Bcast:127.255.255.255  Mask:255.0.0.0
        UP RUNNING          MTU:1500  ReasmMAX:65535 Group:1
        IPRX bytes:116      unicastpkts:0   broadcastpkts:2
        IPTX bytes:0       unicastpkts:0   broadcastpkts:0      droppkts:0
        HWRX bytes:0       unicastpkts:0   broadcastpkts:0
        HWTX bytes:0       unicastpkts:0   broadcastpkts:0      droppkts:0
=>nat enable addr=10.10.10.147 type=pat
=>ip aplist
1   eth0      Type:EthernetHWaddr 00:80:9f:24:ab:cf BRHWaddr ff:ff:ff:ff:ff:ff
    inet addr:10.10.10.147  Bcast: 10.10.10.255  Mask: 255.0.0.0
        UP RUNNING          MTU:1500  ReasmMAX:65535 Group:2
        IPRX bytes:19791886  unicastpkts:11341 broadcastpkts:290555
        IPTX bytes:839550   unicastpkts:11477 broadcastpkts:0      droppkts:0
        HWRX bytes:0       unicastpkts:0   broadcastpkts:0
        HWTX bytes:0       unicastpkts:0   broadcastpkts:0      droppkts:0
0   loop      Type:0
    inet addr:127.0.0.1      Bcast:127.255.255.255  Mask:255.0.0.0
        UP RUNNING          MTU:1500  ReasmMAX:65535 Group:1
        IPRX bytes:116      unicastpkts:0   broadcastpkts:2
        IPTX bytes:0       unicastpkts:0   broadcastpkts:0      droppkts:0
        HWRX bytes:0       unicastpkts:0   broadcastpkts:0
        HWTX bytes:0       unicastpkts:0   broadcastpkts:0      droppkts:0
=>
```

RELATED COMMANDS:

nat create	Create a static NAPT entry.
nat delete	Delete a static NAPT entry.
nat disable	Disable NAPT on one of the SpeedTouch™ Pro with Firewall IP addresses.
nat list	List NAPT connection database.

nat flush

Flush complete NAPT configuration.

The flush command does not impact previously saved configurations.

SYNTAX:

nat flush

EXAMPLE:

```
=>nat list
Indx Prot Inside-addr:PortOutside-addr:Port Foreign-addr:Port Flgs Expir State Control
1    17   10.0.0.138:138 10.0.0.140:138 10.0.0.20:138 11   20   10
2    17   10.0.0.138:137 10.0.0.140:137 10.0.0.254:137 11   20   10
3    17   10.0.0.138:7938 10.0.0.140:7938 10.0.0.96:4756 11   20   10
4    17   10.0.0.138:513 10.0.0.140:513 10.0.0.109:513 11   20   10
5    17   10.0.0.138:111 10.0.0.140:111 10.0.0.96:4756 11   20   10
=>nat bindlist
Application Proto Port
RAUDIO(PNA)  tcp   7071
H323          tcp   1720
FTP           tcp   21
RTSP          tcp   554
IRC           tcp   6667
RAUDIO(PNA)  tcp   7070
=>nat flush
=>nat list
Indx Prot Inside-addr:PortOutside-addr:Port Foreign-addr:Port Flgs Expir State Control
=>nat bindlist
=>
```

RELATED COMMANDS:

nat load

Load saved or default NAPT configuration.

nat save

Save current NAPT configuration.

nat list

Show NAPT connection database.

SYNTAX:

nat list	[addr = <ip-address>]
-----------------	------------------------------------

[addr]	The SpeedTouch™ Pro with Firewall IP address for which the NAPT connection database must be shown. In case the parameter is not specified the NAPT connection database for all IP addresses is shown.	OPTIONAL
--------	---	----------

EXAMPLE INPUT/OUTPUT:

=>nat list								
Indx	Prot	Inside-addr:Port	Outside-addr:Port	Foreign-addr:Port	Flgs	Expir	State	Control
1	6	10.0.0.138:80	172.16.0.5:1080	0.0.0.0:0	19	8	9	
2	17	10.0.0.138:135	10.0.0.140:135	10.0.0.155:1034	11	20	10	
3	17	10.0.0.138:138	10.0.0.140:138	10.0.0.20:138	11	20	10	
4	17	10.0.0.138:137	10.0.0.140:137	10.0.0.254:137	11	20	10	
5	17	10.0.0.138:7938	10.0.0.140:7938	10.0.0.96:4756	11	20	10	
6	17	10.0.0.138:513	10.0.0.140:513	10.0.0.109:513	11	20	10	
7	17	10.0.0.138:111	10.0.0.140:111	10.0.0.96:4756	11	20	10	
=>								

RELATED COMMANDS:

nat create	Create a static NAPT entry.
nat delete	Delete a static NAPT entry.
nat disable	Disable NAPT on one of the SpeedTouch™ Pro with Firewall IP addresses.
nat enable	Enable NAPT on one of the SpeedTouch™ Pro with Firewall IP addresses.

nat load

Load saved (or default) NAPT configuration.

Execute **nat flush** prior to **nat load**.

SYNTAX:

nat load	[defaults = <yes no>]
-----------------	------------------------------------

[defaults]	Load factory defaults (yes) or saved configuration (no).	OPTIONAL
	Not specifying this parameter loads the saved configuration	

EXAMPLE:

```
=>nat list
Indx Prot Inside-addr:PortOutside-addr:Port Foreign-addr:Port Flgs Expir State Control
1    17   10.0.0.138:138 10.0.0.140:138 10.0.0.20:138 11   20   10
2    17   10.0.0.138:137 10.0.0.140:137 10.0.0.254:137 11   20   10
3    17   10.0.0.138:7938 10.0.0.140:7938 10.0.0.96:4756 11   20   10
4    17   10.0.0.138:513 10.0.0.140:513 10.0.0.109:513 11   20   10
5    17   10.0.0.138:111 10.0.0.140:111 10.0.0.96:4756 11   20   10
=>nat save
=>nat flush
=>nat list
Indx Prot Inside-addr:PortOutside-addr:Port Foreign-addr:Port Flgs Expir State Control
=>nat load
=>nat list
Indx Prot Inside-addr:PortOutside-addr:Port Foreign-addr:Port Flgs Expir State Control
1    17   10.0.0.138:138 10.0.0.140:138 10.0.0.20:138 11   20   10
2    17   10.0.0.138:137 10.0.0.140:137 10.0.0.254:137 11   20   10
3    17   10.0.0.138:7938 10.0.0.140:7938 10.0.0.96:4756 11   20   10
4    17   10.0.0.138:513 10.0.0.140:513 10.0.0.109:513 11   20   10
5    17   10.0.0.138:111 10.0.0.140:111 10.0.0.96:4756 11   20   10
=>
```

RELATED COMMANDS:

nat flush	Flush complete NAPT configuration.
nat save	Save current NAPT configuration.

nat save

Save current NAPT configuration.

SYNTAX:

nat save

EXAMPLE:

=>nat list
Indx Prot Inside-addr:PortOutside-addr:Port Foreign-addr:Port Flgs Expir State Control
1 17 10.0.0.138:138 10.0.0.140:138 10.0.0.20:138 11 20 10
2 17 10.0.0.138:137 10.0.0.140:137 10.0.0.254:137 11 20 10
3 17 10.0.0.138:7938 10.0.0.140:7938 10.0.0.96:4756 11 20 10
4 17 10.0.0.138:513 10.0.0.140:513 10.0.0.109:513 11 20 10
5 17 10.0.0.138:111 10.0.0.140:111 10.0.0.96:4756 11 20 10
=> nat save
=>nat flush
=>nat list
Indx Prot Inside-addr:PortOutside-addr:Port Foreign-addr:Port Flgs Expir State Control
=>nat load
=>nat list
Indx Prot Inside-addr:PortOutside-addr:Port Foreign-addr:Port Flgs Expir State Control
1 17 10.0.0.138:138 10.0.0.140:138 10.0.0.20:138 11 20 10
2 17 10.0.0.138:137 10.0.0.140:137 10.0.0.254:137 11 20 10
3 17 10.0.0.138:7938 10.0.0.140:7938 10.0.0.96:4756 11 20 10
4 17 10.0.0.138:513 10.0.0.140:513 10.0.0.109:513 11 20 10
5 17 10.0.0.138:111 10.0.0.140:111 10.0.0.96:4756 11 20 10
=>

RELATED COMMANDS:

nat flush

Flush complete NAPT configuration.

nat load

Load saved or default NAPT configuration.

nat unbind

Delete an existing helper/port binding.

SYNTAX:

nat unbind	application = <string>
	port = <TCP/UDP service name or port number>

<i>application</i>	The name of a NAPT application helper. The name must be spelled exactly as listed in the application list (nat applist).	REQUIRED
<i>port</i>	The port number this application handler should work on.	REQUIRED

EXAMPLE:

```
=>nat applist
Application Proto DefaultPort
ils          tcp    0      OUTGOING
H254         tcp    0      OUTGOINGINCOMING
H323         tcp    1720   OUTGOINGINCOMING
RAUDIO(PNA)  tcp    7070   OUTGOING
RTSP          tcp    554    OUTGOING
IRC           tcp    6667   OUTGOING
FTP            tcp    21     OUTGOINGINCOMING
=>nat bindlist
Application Proto Port
RAUDIO(PNA)  tcp    7071
H323          tcp    1720
FTP            tcp    21
RTSP          tcp    554
IRC           tcp    6667
RAUDIO(PNA)  tcp    7070
=>
=>nat unbind application=RAUDIO(PNA) port=7071
=>nat bindlist
Application Proto Port
H323          tcp    1720
FTP            tcp    21
RTSP          tcp    554
IRC           tcp    6667
RAUDIO(PNA)  tcp    7070
=>
```

RELATED COMMANDS:

nat applist	List available NAPT protocol helpers.
nat bindlist	List current NAPT helper/port bindings.
nat bind	Create a new helper/port binding.

12 Phonebook Commands

phonebook (to access the Phonebook level)

phonebook add

phonebook autolist

phonebook delete

phonebook flush

phonebook list

phonebook load

phonebook save

phonebook add

Add a phonebook entry.

The number of entries is limited to 64. The number of active connections is limited to 12, but more may be configured at the same time.

SYNTAX:

phonebook add	name = <string>
	addr = <[port.]vpi.vci>
	type = <{any bridge ppp cip ans pptp}>

name	A free to choose phonebook name for the destination. Two limitations apply: <ul style="list-style-type: none">▪ The name of a phonebook entry intended for the Relayed PPPoA (PPPoA-to-PPTP Relaying) packet service may not start with capital P or capital T▪ The name of a phonebook entry intended for the PPP-to-DHCP spoofing packet service must start with DHCP, e.g. 'DHCP_Spoof01'.	REQUIRED
addr	The ATM address for this destination. It is composed of a Virtual Path Identifier (VPI) and a Virtual Channel Identifier (VCI) identifying ATM virtual channels. In most cases the values are provided by the Service Provider. Accepted VPI: a number between 0 and 15 Accepted VCI: a number between 0 and 511.	REQUIRED
type	The Connection Service supported by the destination. Choose between: <ul style="list-style-type: none">▪ any (All Packet Services)▪ bridge (Bridging, Routed Ethernet, Bridged PPPoE, Routed PPPoE)▪ ppp (Routed PPPoA and Relayed PPPoA)▪ cip (Classical IP & IP Routing)▪ ans (ATM Name Service)▪ pptp (Relayed PPPoA, PPPoA-to-PPTP Relaying).	REQUIRED

EXAMPLE:

```
=>phonebook list
Name      Type    Use   Address
PVC1      any     1     8.35
PVC2      bridge  0     8.36
Br3       bridge  0     8.36
Br4       bridge  0     8.38
CIPPVC3   cip    1     8.82
CIPPVC4   cip    1     8.83
=>phonebook add name=Alcatel addr=8.68 type=ppp
=>phonebook list
Name      Type    Use   Address
PVC1      any     1     8.35
PVC2      bridge  0     8.36
Br3       bridge  0     8.36
Br4       bridge  0     8.38
CIPPVC3   cip    1     8.82
CIPPVC4   cip    1     8.83
Alcatel  ppp    0     8.68
=>
```

RELATED COMMANDS:

- | | |
|-------------------------|---------------------------|
| phonebook delete | Remove a phonebook entry. |
| phonebook list | Show current phonebook. |

phonebook autolist

Show auto PVCs, if supported by the Central Office DSLAM. (Only applicable for Alcatel ASAM DSLAMs).

SYNTAX:

```
phonebook autolist
```

EXAMPLE INPUT/OUTPUT:

```
=>phonebook autolist
8.35
=>
```

RELATED COMMANDS:

phonebook list Show current phonebook.

phonebook delete

Remove an unused phonebook entry.

SYNTAX:

phonebook delete	name = <string>
-------------------------	------------------------------

name	the name of the phonebook entry to delete. Only applicable for phonebook entries that are not used, i.e. not configured for any packet service. Execute phonebook list to check whether the entry is used (Use=1) or not (Use=0).	REQUIRED
------	--	----------

EXAMPLE:

```
=>phonebook list
Name      Type     Use   Address
PVC1      any      1     8.35
PVC2      bridge   0     8.36
Br3       bridge   0     8.36
Br4       bridge   0     8.38
CIPPVC3   cip      1     8.82
CIPPVC4   cip      1     8.83
Alcatel  ppp      0     8.68
=>phonebook delete name=Alcatel
=>phonebook list
Name      Type     Use   Address
PVC1      any      1     8.35
PVC2      bridge   0     8.36
Br3       bridge   0     8.36
Br4       bridge   0     8.38
CIPPVC3   cip      1     8.82
CIPPVC4   cip      1     8.83
=>
```

RELATED COMMANDS:

phonebook add	Add a phonebook entry.
phonebook list	Show current phonebook.

phonebook flush

Flush complete phonebook.

The flush command does not impact previously saved configurations.

SYNTAX:

```
phonebook flush
```

EXAMPLE:

```
=>phonebook list
Name      Type     Use   Address
PVC1      any      1    8.35
PVC2      bridge   0    8.36
Br3       bridge   0    8.36
Br4       bridge   0    8.38
CIPPVC3   cip      1    8.82
CIPPVC4   cip      1    8.83
Alcatel   ppp      0    8.68
=>phonebook flush
=>phonebook list
Name      Type     Use   Address
=>
```

RELATED COMMANDS:

phonebook load

Load saved or default phonebook.

phonebook save

Save current phonebook.

phonebook list

Show current phonebook.

SYNTAX:

phonebook list	[<i>opt</i> = <{long}>]
-----------------------	--------------------------------------

[<i>opt</i>]	Select output format. For internal use only.	OPTIONAL
----------------	--	----------

EXAMPLE INPUT/OUTPUT:

=> phonebook list
Name Type Use Address
PVC1 any 1 8.35
PVC2 bridge 0 8.36
Br3 bridge 0 8.36
Br4 bridge 0 8.38
CIPPVC3 cip 1 8.82
CIPPVC4 cip 1 8.83
Alcatel ppp 0 8.68
=>

RELATED COMMANDS:

phonebook add	Add a phonebook entry.
phonebook autolist	Show auto PVCs.
phonebook delete	Remove a phonebook entry.

phonebook load

Load saved (or default) phonebook.

Execute **phonebook flush** prior to **phonebook load**.

SYNTAX:

phonebook load	[defaults <yes no>]
-----------------------	----------------------------------

[defaults]	Load factory defaults (yes) or saved configuration (no). Not specifying this parameter loads the saved configuration	OPTIONAL
------------	---	----------

EXAMPLE:

```
=>phonebook list
Name      Type     Use   Address
PVC2      bridge   0     8.36
Br4       bridge   0     8.38
CIPPVC4   cip      1     8.83
Alcatel   ppp      1     8.68
=>phonebook save
=>phonebook flush
=>phonebook list
Name      Type     Use   Address
=>phonebook load defaults=yes
=>phonebook list
Name      Type     Use   Address
Br1       bridge   0     8.35
Br2       bridge   0     8.36
Br3       bridge   0     8.37
Br4       bridge   0     8.38
RELAY_PPP1 ppp    0     8.48
RELAY_PPP2 ppp    0     8.49
RELAY_PPP3 ppp    0     8.50
RELAY_PPP4 ppp    0     8.51
DIAL_PPP1  ppp    0     8.64
DIAL_PPP2  ppp    0     8.65
DIAL_PPP3  ppp    0     8.66
DHCP_SPOOF ppp   0     8.67
CIPPVC1   cip     0     8.80
CIPPVC2   cip     0     8.81
CIPPVC3   cip     1     8.82
CIPPVC4   cip     1     8.83
=>phonebook load defaults=no
=>phonebook list
Name      Type     Use   Address
PVC2      bridge   0     8.36
Br4       bridge   0     8.38
CIPPVC4   cip      1     8.83
Alcatel   ppp      0     8.68
=>phonebook save
```

RELATED COMMANDS:

phonebook flush

Flush complete phonebook.

phonebook save

Save current phonebook.

phonebook save

Save current phonebook.

SYNTAX:

phonebook save

EXAMPLE:

```
=>phonebook list
Name      Type     Use   Address
PVC2      bridge   0    8.36
Br4       bridge   0    8.38
CIPPVC4   cip      1    8.83
Alcatel   ppp      1    8.68
=>phonebook save
=>phonebook flush
=>phonebook list
Name      Type     Use   Address
=>phonebook load
=>phonebook list
Name      Type     Use   Address
PVC2      bridge   0    8.36
Br4       bridge   0    8.38
CIPPVC4   cip      1    8.83
Alcatel   ppp      0    8.68
=>phonebook save
```

RELATED COMMANDS:

phonebook flush
phonebook load

Flush complete phonebook.
Load saved or default phonebook.

13 PPP Commands

ppp (to access the PPP level)
ppp flush
ppp ifadd
ppp ifattach
ppp ifconfig
ppp ifdelete
ppp ifdetach
ppp iflist
ppp load
ppp rtadd
ppp rtdelete
ppp save

ppp flush

Flush complete PPP configuration. The flush command does not impact previously saved configurations.

SYNTAX:

```
ppp flush
```

EXAMPLE:

```
=>ppp iflist
PPP1:  dest : PPP1
      Retry: 10   QoS  default encaps  VC-MUX
      mode = IP Routing
      flags= echo magicaccomp mru  addr route savepwd PPPOA
      transaddr = pat     mru = 1500
      route= 0.0.0.0/0 - 0.0.0.0/0 (metric 0)
      user name = guest  password= *****
      admin state= down  oper state= down  link state= not-connected
      LCP : state= initial retransm= 10 term.reason =
      IPCP : state= initial retransm= 0 term.reason =
=>ppp flush
=>ppp iflist
=>
```

RELATED COMMANDS:

ppp load	Load saved or default PPP configuration.
ppp save	Save current PPP configuration.

ppp ifadd

Create a new PPP interface.

SYNTAX:

ppp ifadd	<i>[intf = <string>] [dest = <phonebook entry>] [encaps = <{vcmux llc}>] [speed = <number{4800–10000000}>]</i>
------------------	--

<i>[intf]</i>	The name for the new PPP interface. If not specified, the destination parameter must be specified. In this case the name of the destination will double as interface name.	OPTIONAL
<i>[dest]</i>	The destination for the new PPP interface. Typically, an phonebook entry.	OPTIONAL
<i>[encaps]</i>	The type of encapsulation to be used for this PPP interface. Choose between: <ul style="list-style-type: none">▪ vcmux▪ llc/snap	OPTIONAL
<i>[speed]</i>	A number between 4800 and 10000000 (bits per second). Represents the speed of the peer-to-peer connection. Use for backward compatibility. Use Quality Of Service instead.	OPTIONAL

EXAMPLE:

```
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10 QoS default encaps VC-MUX
    mode = IP Routing
    flags= echo magicaccomp mru addr routesavepwd PPPOA
    transaddr = pat mru = 1500
    route= 0.0.0.0/0 - 0.0.0.0/0 (metric 0)
    user name = guest password= *****
    adminstate= down oper state= down link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>ppp ifadd intf=PPP2 dest=PVC2
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10 QoS default encaps VC-MUX
    mode = IP Routing
    flags= echo magicaccomp mru addr routesavepwd PPPOA
    transaddr = pat mru = 1500
    route= 0.0.0.0/0 - 0.0.0.0/0 (metric 0)
    user name = guest password= *****
    adminstate= down oper state= down link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
PPP2: dest : PVC2
    Retry: 10 QoS default encaps VC-MUX
    mode = IP Routing
    flags= echo magicaccomp restart mru addr savepwd PPPOA
    mru = 1500
    user name = password=
    adminstate= down oper state= down link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>
```

RELATED COMMANDS:

ppp ifattach	Attach a PPP interface.
ppp ifconfig	Configure a PPP interface.
ppp ifdelete	Delete a PPP interface.
ppp ifdetach	Detach a PPP interface.
ppp iflist	Show current PPP configuration.

ppp ifattach

Attach (i.e. connect) a PPP interface.

SYNTAX:

ppp ifattach	intf = <ifname>
---------------------	------------------------------

<i>intf</i>	The name of the PPP interface to attach.	REQUIRED
-------------	--	----------

EXAMPLE:

```
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10   QoS default encaps LLC
    mode = IP Routing
    flags= echo magicaccomp restart mru   addr routesavepwd PPPOE
    transaddr = pat      mru = 1492
    route=      0.0.0.0/0 -      0.0.0.0/0 (metric 0)
    user name = guest   password= *****
    adminstate= down   oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>ppp ifattach =intf=PPP1
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10   QoS default encaps LLC
    mode = IP Routing
    flags= echo magicaccomp restart mru   addr routesavepwd PPPOA
    transaddr = pat      mru = 1492
    route=      0.0.0.0/0 -      0.0.0.0/0 (metric 0)
    user name = guest   password= *****
    adminstate= up     oper state= down   link state= connected
    LCP : state= reqsent retransm= 10 term.reason =
    IPCP : state= initial retransm= 10 term.reason =
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10   QoS default encaps LLC
    mode = IP Routing
    flags= echo magicaccomp restart mru   addr routesavepwd PPPOA
    transaddr = pat      mru = 1492
    route=      0.0.0.0/0 -      0.0.0.0/0 (metric 0)
    user name = guest   password= *****
    adminstate= up     oper state= up     link state= connected
    LCP : state= opened retransm= 0 term.reason =
    IPCP : state= opened retransm= 10 term.reason =
    acname : , service = .
=>
```

RELATED COMMANDS:

ppp ifadd	Create a PPP interface.
ppp ifconfig	Configure a PPP interface.
ppp ifdelete	Delete a PPP interface.
ppp ifdetach	Detach a PPP interface.
ppp iflist	Show current PPP configuration.

ppp ifconfig

Configure a PPP interface. As the PPP interface to be configured may not be connected at the time of configuration, execute **ppp ifdetach** prior to executing the **ppp ifconfig** command.

SYNTAX:

```
ppp ifconfig      intf = <ifname>
                  [dest = <phonebook entry>]
                  [user = <string>]
                  [password = <string>]
                  [qos = <string>]
                  [proto = <{pppoa|pppoe}>]
                  [acname = <string>]
                  [servicename = <string>]
                  [encaps = <{vcmux|llc}>]
                  [pcomp = <{off|on}>]
                  [accomp = <{on|off|negotiate}>]
                  [trace = <{off|on}>]
                  [pap = <{off|on}>]
                  [restart = <{off|on}>]
                  [retryinterval = <number{0-65535}>]
                  [passive = <{off|on}>]
                  [silent = <{off|on}>]
                  [echo = <{off|on}>]
                  [mru = <number{293-8192}>]
                  [laddr = <ip-address>]
                  [raddr = <ip-address>]
                  [savepwd = <{off|on}>]
                  [demanddial = <{off|on}>]
                  [primdns = <ip-address>]
                  [secdns = <ip-address>]
                  [idle = <number{0-1000000}>]
                  [addrtrans = <{none|pat}>]
                  [unnumbered = <{off|on}>]
                  [poolstart = <ip-address>]
                  [poolend = <ip-address>]
                  [status = <{down|up}>]
```

<i>intf</i>	The name of the PPP interface to configure.	REQUIRED
<i>[dest]</i>	The destination for this PPP interface. Typically, a phonebook entry. Use: <ul style="list-style-type: none">▪ PPPoA (ppp) phonebook entries For the Routed PPPoA (PPP & IP Routing) packet service.▪ EThoA (bridge) phonebook entries For the Routed PPPoE packet service.	OPTIONAL
<i>[user]</i>	The user name for remote PAP/CHAP authentication.	OPTIONAL
<i>[password]</i>	The password for remote PAP/CHAP authentication.	OPTIONAL

[qos]	The name of a configured Quality Of Service book entry. This parameter never needs to be specified.	OPTIONAL
[proto]	The encapsulation method for the PPP frames, i.e. the applicable packet service for the connection. Select: <ul style="list-style-type: none">▪ pppoa<ul style="list-style-type: none">For a Routed PPPoA (PPP & IP Routing) connections.▪ pppoe<ul style="list-style-type: none">For a Routed PPPoE connection. Per default the PPPoA protocol applies.	OPTIONAL
[acname]	The Access Concentrator name for a Routed PPPoE connection. This parameter is applicable only for Routed PPPoE PPP interfaces (proto=pppoe). Execute the ppp ifscan command to see the names of available access concentrators, if any.	OPTIONAL
[servicename]	The Service Name for a Routed PPPoE connection. This parameter is applicable only for Routed PPPoE PPP interfaces (proto=pppoe). Execute the ppp ifscan command to see the available service names, if any.	OPTIONAL
[encaps]	The type of encapsulation to be used for this PPP interface. Choose between: <ul style="list-style-type: none">▪ vcmux (default)<ul style="list-style-type: none">Standard encapsulation method for PPPoA (ppp) frames.▪ llc<ul style="list-style-type: none">Standard encapsulation method for EThoA (bridge) frames.	OPTIONAL
[pcomp]	Try (on) or do not try (off) to negotiate PPP protocol compression (LCP PCOMP). Per default the negotiation is disabled (off).	OPTIONAL
[accomp]	Try (on), do never try (off) or negotiate (negotiate) to negotiate PPP address & control field compression (LCP ACCOMP). In the very most cases LCP ACCOMP should not be disabled nor negotiated, i.e. the address field FF-03 should not be sent over ATM. Therefore by default this parameter is enabled (on). In case the accomp parameter is set 'negotiate' the local side of the PPP connection demands to do ACCOMP and adapts itself to the result of this negotiation.	OPTIONAL
[trace]	Enable (on) or disable (off) verbose console logging. By default tracing is disabled (off).	OPTIONAL
[pap]	Force PAP based authentication (on) or use CHAP based authentication, if available (off). For security reasons PAP negotiation is disabled (off) per default.	OPTIONAL
[restart]	Automatically restart the connection when LCP link goes down (on) or do not restart automatically (off). By default restart is disabled (off).	OPTIONAL

[retryinterval]	A number between 0 and 65535 (seconds). Represents the intermediate interval between two retries to establish the connection on ATM level.. Only applicable in an SVC environment.	OPTIONAL
[passive]	Put the link in listening state in case LCP times out (on) or not (off). This parameter allows to determine whether the link should be left open to wait for incoming messages from the remote side after 10 unsuccessful tries to establish the connection or not. Per default the listening state is disabled.	OPTIONAL
[silent]	Do not send anything at startup and just listen for incoming LCP messages (on) or retry up to 10 times to establish the connection (off). Per default the silent state is disabled.	OPTIONAL
[echo]	Send LCP echo requests at regular intervals (on) or not (off). Per default the sending of LCP echo requests is enabled.	OPTIONAL
[mru]	A number between 293 and 8192. Represents the maximum packet size the SpeedTouch™ Pro with Firewall should negotiate to be able to receive.	OPTIONAL
[laddr]	The local IP address of the peer-to-peer connection. Specifying a local IP address forces the remote side of the PPP link (if it allows to) to accept this IP address as the SpeedTouch™ Pro with Firewall PPP session IP address. If not specified, the SpeedTouch™ Pro with Firewall will accept any IP address. Typically the local IP address parameter is not specified.	OPTIONAL
[raddr]	The remote IP address of the peer-to-peer connection. Specifying a remote IP address forces the remote side of the PPP link (if it allows to) to accept this IP address as its PPP session IP address. If not specified, the SpeedTouch™ Pro with Firewall will accept any IP address. Typically the remote IP address parameter is not specified.	OPTIONAL
[savepwd]	Save password (on), if supplied, or do not save the password (off). Per default the saving of the password is disabled.	OPTIONAL
[demanddial]	Enable (on) or disable (off) the dial-on-demand feature.	OPTIONAL
[primdns]	The IP address of the primary DNS server. In case a primary DNS server is specified the SpeedTouch™ Pro with Firewall will negotiate this IP address with the remote side. If not specified, the SpeedTouch™ Pro with Firewall will accept any IP address.	OPTIONAL
[secdns]	The IP address of the (optional) secondary DNS server. In case a secondary DNS server is specified the SpeedTouch™ Pro with Firewall will negotiate this IP address with the remote side. If not specified, the SpeedTouch™ Pro with Firewall will accept any IP address.	OPTIONAL

[idle]	A number between 1 and 1000000 (seconds). Represents after how many seconds an idle link goes down.	OPTIONAL
[addrtrans]	Automatically enable address translation for the IP address of this link (pat) or do not use address translation (none).	OPTIONAL
[unnumbered]	Takes the local IP address from 'laddr' field and remote IP address from the IP address pool assigned to the incoming PPP link. In case the unnumbered parameter is disabled the same IP address is used for each connection on the server side, thus reducing the number of IP addresses used.	OPTIONAL
[poolstart]	The lower bound of the IP address pool assigned to the incoming PPP link.	OPTIONAL
[poolend]	The upper bound of the IP address pool assigned to the incoming PPP link.	OPTIONAL
[status]	Force automatically to attach the PPP interface (up) or use the regular ppp ifattach command (down). Per default the startup status is down (recommended).	OPTIONAL

EXAMPLE:

```
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10   QoS  default encaps  LLC
    mode = IP Routing
    flags= echo magicaccomp  restart mru  addr route savepwd PPPOE
    transaddr = pat      mru = 1492
    route=      0.0.0.0/0 -      0.0.0.0/0 (metric 0)
    user name = My_Connection@MY_ISP  password= *****
    adminstate= down   oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>ppp ifconfig intf=PPP1 prot=pppoa encaps=vcmux
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10   QoS  default encaps VC-MUX
    mode = IP Routing
    flags= echo magicaccomp  restart mru  addr route savepwd PPPOA
    transaddr = pat      mru = 1492
    route=      0.0.0.0/0 -      0.0.0.0/0 (metric 0)
    user name = My_Connection@MY_ISP  password= *****
    adminstate= down   oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>
```

RELATED COMMANDS:

ppp ifadd	Create a PPP interface.
ppp ifattach	Attach a PPP interface.
ppp ifdelete	Delete a PPP interface.
ppp ifdetach	Detach a PPP interface.
ppp iflist	Show current PPP configuration.

ppp ifdelete

Delete a PPP interface.

SYNTAX:

ppp ifdelete	intf = <ifname>
---------------------	------------------------------

<i>intf</i>	The name of the PPP interface to delete.
-------------	--

EXAMPLE:

```
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10   QoS default encaps VC-MUX
    mode = IP Routing
    flags= echo magicaccomp mru   addr route savepwd PPPOA
    transaddr = pat      mru = 1500
    route= 0.0.0.0/0 - 0.0.0.0/0 (metric 0)
    user name = guest   password= *****
    adminstate= down    oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
PPP2: dest : PVC2
    Retry: 10   QoS default encaps VC-MUX
    mode = IP Routing
    flags= echo magicaccomp restart mru   addr savepwd PPPOA
    mru = 1500
    user name = password=
    adminstate= down    oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>ppp ifdelete intf=PPP2
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10   QoS default encaps VC-MUX
    mode = IP Routing
    flags= echo magicaccomp mru   addr route savepwd PPPOA
    transaddr = pat      mru = 1500
    route= 0.0.0.0/0 - 0.0.0.0/0 (metric 0)
    user name = guest   password= *****
    adminstate= down    oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>
```

RELATED COMMANDS:

ppp ifadd	Create a PPP interface.
ppp ifattach	Attach a PPP interface.
ppp ifconfig	Configure a PPP interface.
ppp ifdetach	Detach a PPP interface.
ppp iflist	Show current PPP configuration.

ppp ifdetach

Detach a PPP interface.

SYNTAX:

ppp ifdetach	intf = <ifname>
---------------------	------------------------------

<i>intf</i>	The name of the PPP interface.	REQUIRED
-------------	--------------------------------	----------

EXAMPLE:

```
=>ppp iflist
PPP1:  dest : PPP1
      Retry: 10   QoS  default encaps  LLC
      mode = IP Routing
      flags= echo magicaccomp  restart mru  addr routesavepwd PPPOA
      transaddr = pat      mru = 1492
      route= 0.0.0.0/0 - 0.0.0.0/0 (metric 0)
      user name = guest  password= *****
      adminstate= up    oper state= up    link state= connected
      LCP : state= opened retransm= 0 term.reason =
      IPCP : state= opened retransm= 10 term.reason =
      acname : , service = .
=>ppp ifdetach =intf=PPP1
=>ppp iflist
PPP1:  dest : PPP1
      Retry: 10   QoS  default encaps  LLC
      mode = IP Routing
      flags= echo magicaccomp  restart mru  addr routesavepwd PPPOE
      transaddr = pat      mru = 1492
      route= 0.0.0.0/0 - 0.0.0.0/0 (metric 0)
      user name = guest  password= *****
      adminstate= down  oper state= down  link state= not-connected
      LCP : state= initial retransm= 10 term.reason =
      IPCP : state= initial retransm= 0 term.reason =
=>
```

RELATED COMMANDS:

ppp ifadd	Create a PPP interface.
ppp ifattach	Attach a PPP interface.
ppp ifconfig	Configure a PPP interface.
ppp ifdelete	Delete a PPP interface.
ppp iflist	Show current PPP configuration.

ppp iflist

Show current configuration of all or a specified PPP interface(s).

SYNTAX:

<i>ppp iflist</i>	<i>[intf = <ifname>]</i>
--------------------------	---------------------------------------

<i>intf <ifname></i>	the name of the PPP interface.	OPTIONAL
	In case this parameter is not specified all PPP interfaces are shown.	

EXAMPLE INPUT/OUTPUT :

```
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10   QoS default encaps VC-MUX
    mode = IP Routing
    flags= echo magicaccomp mru   addr route savepwd PPPOA
    transaddr = pat      mru = 1500
    route= 0.0.0.0/0 - 0.0.0.0/0 (metric 0)
    user name = guest   password= *****
    adminstate= down    oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=
```

RELATED COMMANDS:

<i>ppp ifadd</i>	Create a PPP interface.
<i>ppp ifattach</i>	Attach a PPP interface.
<i>ppp ifconfig</i>	Configure a PPP interface.
<i>ppp ifdelete</i>	Delete a PPP interface.
<i>ppp ifdetach</i>	Detach a PPP interface.

ppp ifscan

Scan a PPPoE interface (proto=pppoe) for available Access Concentrator names and Service Names.

Execute the **ppp ifdetach** command for this interface prior to perform a scan on it.

SYNTAX:

ppp ifscan	intf = <ifname>
	[time = <number{0–36000}>]
	[kit = <number{0–8}>]

intf	The name of the PPP interface to scan.	REQUIRED
[time]	A number between 0 and 36000 (seconds). Represents the time to scan for services.	OPTIONAL
[kit]	A number between 0 and 8. Represents the way the scan progress is visually indicated. Per default no progress indicator is applied (kit=0). kit=1 up to kit=8 are diverse progress indicators. Try it !	OPTIONAL

EXAMPLE:

```
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10   QoS  default encaps  LLC
    mode = IP Routing
    flags= echo magicaccomp  restart mru  addr route savepwd PPPOE
    transaddr = pat      mru = 1492
    route=      0.0.0.0/0 -      0.0.0.0/0 (metric 0)
    user name = guest    password= *****
    adminstate= down    oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>ppp ifscan intf=PPP1 time=45
          Service Name           Access Concentrator
Done !
=>
```

RELATED COMMANDS:

ppp ifconfig Configure a PPP interface.

ppp load

Load saved (or default) PPP configuration.

Execute **ppp flush** prior to **ppp load**.

SYNTAX:

ppp load	[defaults = <yes no>]
-----------------	------------------------------------

[defaults]	Load factory defaults (yes) or saved configuration (no).	OPTIONAL
	Not specifying this parameter loads the saved configuration	

EXAMPLE:

```
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10   QoS  default encaps  VC-MUX
    mode = IP Routing
    flags= echo magicaccomp mru  addr route savepwd PPPOA
    transaddr = pat      mru = 1500
    route= 0.0.0.0/0 - 0.0.0.0/0 (metric 0)
    user name = guest  password= *****
    adminstate= down   oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>ppp save
=>ppp flush
=>ppp iflist
=>ppp load
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10   QoS  default encaps  VC-MUX
    mode = IP Routing
    flags= echo magicaccomp mru  addr route savepwd PPPOA
    transaddr = pat      mru = 1500
    route= 0.0.0.0/0 - 0.0.0.0/0 (metric 0)
    user name = guest  password= *****
    adminstate= down   oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>
```

RELATED COMMANDS:

ppp flush	Flush complete PPP configuration.
ppp save	Save current PPP configuration.

ppp rtadd

Automatically add a route configuration to the routing table in case the specified PPP interface link comes up.

This route configuration will determine which local hosts are allowed to use this link and/or which remote destinations should be or should not be reachable.

Execute the **ppp ifdetach** command for this interface prior to configuring routes.

SYNTAX:

ppp rtadd	<i>intf = <ifname></i> <i>dst = <ip-address></i> <i>[dstmsk = <ip-mask(dotted or cidr)>]</i> <i>[src = <ip-address>]</i> <i>[srcmsk = <ip-mask(dotted or cidr)>]</i> <i>[metric = <number{0-100}>]</i>	
<i>intf</i>	The name of the PPP interface.	REQUIRED
<i>dst</i>	The destination IP address specification for the route to be added when the link comes up.	REQUIRED
<i>[dstmsk]</i>	<p>The destination IP mask. Depending on the destination netmask:</p> <ul style="list-style-type: none"> ▪ Any remote destination is reachable, i.e. the PPP connection acts as default route (dstmsk=0) ▪ Only the remote (sub)net is reachable (dstmsk=1) The actual destination mask will be the default netmask applicable for destination IP address ▪ Only the single remote host is reachable (dstmsk=32) ▪ Any valid (contiguous) netmask in case of VLSM. 	OPTIONAL
<i>[src]</i>	The source IP address specification for the route to be added when the link comes up.	OPTIONAL
<i>[srcmsk]</i>	<p>The source IP mask. Depending on the source netmask:</p> <ul style="list-style-type: none"> ▪ Everybody is allowed to use this PPP connection (dstmsk=0) ▪ Only members of the same subnet as the host which opened the PPP connection are allowed to use the PPP connection (dstmsk=1) The actual destination mask will be the netmask applicable for the IP address of the host which opened the PPP connection. ▪ Only the host which opened the PPP connection is allowed to use the PPP connection. (dstmsk=32) ▪ Any valid (contiguous) netmask in case of VLSM. 	OPTIONAL
<i>[metric]</i>	The route metric, i. e. the cost factor of the route. Practically, the cost is determined by the hop count. It is recommended not to use this parameter.	OPTIONAL

EXAMPLE:

```
=>ppp iflist
PPP1: dest : PVC3
  Retry: 10  QoS default encaps LLC
  mode = IP Routing
  flags= echo magicaccomp restart mru  addr routesavepwd PPPOE
  transaddr = pat    mru = 1492
  user name = guest  password= *****
  adminstate= down   oper state= down   link state= not-connected
  LCP : state= initial retransm= 10 term.reason =
  IPCP : state= initial retransm= 0 term.reason =
=>ppp rtadd intf=PPP1 dst=172.16.0.5 dstmsk=24 src=10.0.0.2 srcmask=24
=>ppp iflist
PPP1: dest : PVC3
  Retry: 10  QoS default encaps LLC
  mode = IP Routing
  flags= echo magicaccomp restart mru  addr routesavepwd PPPOE
  transaddr = pat    mru = 1492
  route= 10.0.0.2/24 - 172.16.0.5/24 (metric 1)
  user name = guest  password= *****
  adminstate= down   oper state= down   link state= not-connected
  LCP : state= initial retransm= 10 term.reason =
  IPCP : state= initial retransm= 0 term.reason =
=>
```

RELATED COMMANDS:

ppp rtdelete Delete the route specification for an upcoming PPP link.

ppp rtdelete

Delete the route specification for a PPP link.

Execute the **ppp ifdetach** command for this interface prior to deleting route configurations.

SYNTAX:

ppp rtdelete	intf = <ifname>
---------------------	------------------------------

<i>intf</i>	The PPP interface name for which to delete the route settings.	REQUIRED
-------------	--	----------

EXAMPLE:

```
=>ppp iflist
PPP1: dest : PVC3
    Retry: 10   QoS  default encaps  LLC
    mode = IP Routing
    flags= echo magicaccomp restart mru  addr routesavepwd PPPOE
    transaddr = pat      mru = 1492
    route=      10.0.0.2/24 -      172.16.0.5/24  (metric 1)
    user name = guest  password= *****
    adminstate= down   oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>ppp rtdelete intf=PPP1
=>ppp iflist
PPP1: dest : PVC3
    Retry: 10   QoS  default encaps  LLC
    mode = IP Routing
    flags= echo magicaccomp restart mru  addr routesavepwd PPPOE
    transaddr = pat      mru = 1492
    user name = guest  password= *****
    adminstate= down   oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>
```

RELATED COMMANDS:

ppp rtadd	Configure a route specification for an upcoming PPP link.
------------------	---

ppp save

Save current PPP configuration.

SYNTAX:

```
ppp save
```

EXAMPLE:

```
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10   QoS default encaps VC-MUX
    mode = IP Routing
    flags= echo magicaccomp mru addr routesavepwd PPPOA
    transaddr = pat     mru = 1500
    route=      0.0.0.0/0 -      0.0.0.0/0 (metric 0)
    user name = guest   password= *****
    adminstate= down   oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>ppp save
=>ppp flush
=>ppp iflist
=>ppp load
=>ppp iflist
PPP1: dest : PPP1
    Retry: 10   QoS default encaps VC-MUX
    mode = IP Routing
    flags= echo magicaccomp mru addr routesavepwd PPPOA
    transaddr = pat     mru = 1500
    route=      0.0.0.0/0 -      0.0.0.0/0 (metric 0)
    user name = guest   password= *****
    adminstate= down   oper state= down   link state= not-connected
    LCP : state= initial retransm= 10 term.reason =
    IPCP : state= initial retransm= 0 term.reason =
=>
```

RELATED COMMANDS:

ppp flush

Flush complete PPP configuration.

ppp load

Load saved or default PPP configuration.

14 PPTP Commands

pptp (to access the PPTP level)

pptp flush

pptp list

pptp load

pptp profadd

pptp profdelete

pptp proflist

pptp save

pptp flush

Flush complete PPTP configuration.

The flush command does not impact previously saved configurations.

SYNTAX:

```
pptp flush
```

EXAMPLE:

```
=>pptp profadd name=Relay PPP1 encaps=nlpid ac=always
=>pptp proflist
Profile          QoS           Encaps        AC
Relay PPP1      default       nlpid        always
=>pptp flush
=>pptp proflist
=>
```

RELATED COMMANDS:

pptp load

Load saved or default PPTP configuration.

pptp save

Save current PPTP configuration.

pptp list

Show current PPTP configuration.

SYNTAX:

```
pptp list
```

EXAMPLE INPUT/OUTPUT:

```
=>pptp list
Dialstr      Destination      QoS      Encaps      AC      State      User
              DIALUP PPP3    default    vcmux     never   CONNECTED  (10.0.0.2)
=>
```

pptp load

Load saved (or default) PPTP configuration.

Execute **pptp flush** prior to **pptp load**.

SYNTAX:

pptp load	[defaults = <yes no>]	
[defaults]	Load factory defaults (yes) or saved configuration (no). Not specifying this parameter loads the saved configuration	OPTIONAL

EXAMPLE:

```
=>pptp proplist
Profile          QoS      Encaps      AC
Relay_PPP1       default   nlpid      always
PPTPLink        default   vcmux     never
=>pptp save
=>pptp flush
=>pptp proplist
=>pptp load defaults=yes
Profile          QoS      Encaps      AC
default         default   vcmux     never
=>pptp load defaults=no
=>pptp proplist
Profile          QoS      Encaps      AC
Relay_PPP1       default   nlpid      always
PPTPLink        default   vcmux     never
=>
```

RELATED COMMANDS:

pptp flush	Flush complete PPTP configuration.
pptp save	Save current PPTP configuration.

pptp profadd

Define a new PPTP profile.

SYNTAX:

```
pptp profadd      name = <string>
                     [qos = <string>]
                     [encaps = <{vcmux|nlpid}>]
                     [ac = <{never|always|keep}>]
```

<i>name</i>	The name for the PPTP profile.	REQUIRED
[<i>qos</i>]	The name of the Quality Of Service book entry. This parameter never needs to be specified.	OPTIONAL
[<i>encaps</i>]	The type of encapsulation applicable to Relayed PPPoA interfaces using this PPTP profile. Choose between: <ul style="list-style-type: none">▪ vcmux▪ nlpid	OPTIONAL
[<i>ac</i>]	The HDLC framing option applicable to Relayed PPPoA interfaces using this PPTP profile. Before relaying the encapsulated PPP frames over the PPPoA link, make sure that the address and control field (0xFF03) is always in front of the frames (always), make sure the address and control field will never be found in front of the frames (never) or do not change the frames arriving via the PPTP tunnel (keep). By default the address and control field is never sent (compliant to RFC2364). It is recommended to keep this setting.	OPTIONAL

EXAMPLE:

```
=>pptp proflist
Profile          QoS        Encaps       AC
Relay_PPP1       default    nlpid       always
=>pptp profadd name=PPTPLink encaps=vcmux ac=never
=>pptp proflist
Profile          QoS        Encaps       AC
Relay_PPP1       default    nlpid       always
PPTPLink       default    vcmux      never
=>
```

RELATED COMMANDS:

pptp profdelete	Delete a PPTP profile.
pptp proflist	Show current PPTP profiles.

pptp profdelete

Delete a PPTP profile.

SYNTAX:

pptp profdelete	name <string>
------------------------	----------------------------

name	The name for the PPTP profile.	REQUIRED
------	--------------------------------	----------

EXAMPLE:

```
=>pptp proflist
Profile          QoS           Encaps        AC
Relay_PPP1      default       nlpid        always
PPTPLink      default       vcmux        never
=>pptp profdelete name=PPTPLink
=>pptp proflist
Profile          QoS           Encaps        AC
Relay_PPP1      default       nlpid        always
=>
```

RELATED COMMANDS:

pptp profadd	Define a new PPTP profile.
pptp proflist	Show current PPTP profiles.

pptp proflist

Show all current PPTP profiles.

```
pptp proflist
```

EXAMPLE:

```
=>pptp proflist
Profile          QoS        Encaps      AC
Relay_PPP1       default    nlpid      always
PPTPLink         default    vcmux      never
=>
```

RELATED COMMANDS:

pptp profadd Define a new PPTP profile.
pptp profdelete Delete a PPTP profile.

pptp save

Save current PPTP configuration.

SYNTAX:

```
pptp save
```

EXAMPLE:

```
=>pptp proflist
Profile          QoS        Encaps      AC
Relay_PPP1       default    nlpid      always
PPTPLink         default    vcmux      never
=>pptp save
=>pptp flush
=>pptp proflist
=>pptp load defaults=no
=>pptp proflist
Profile          QoS        Encaps      AC
Relay_PPP1       default    nlpid      always
PPTPLink         default    vcmux      never
=>
```

RELATED COMMANDS:

pptp flush	Flush complete PPTP configuration.
pptp load	Load saved or default PPTP configuration.

15 Software Commands

software (to access the Software level)

software cleanup

software deletepassive

software setpassive

software switch

software version

software cleanup

Remove all unused files from the passive software subdirectory.

This command frees the passive software subdirectory from corrupted software files and configuration files. Software marked as passive software is not deleted.

SYNTAX:

```
software cleanup
```

EXAMPLE:

```
=>software cleanup
=>
```

RELATED COMMANDS:

software deletepassive

Delete the passive software.

software setpassive

Mark an uploaded file as passive software version.

software deletepassive

Delete passive software.

SYNTAX:

```
software deletepassive
```

EXAMPLE:

```
=>Software version
Active : Sascha3.424          Passive : Bene3.420
=>Software deletepassive
=>Software version
Active : Sascha3.424          Passive : _____
=>
```

RELATED COMMANDS:

software cleanup

Remove all unused files from the passive software subdirectory.

software setpassive

Mark a file as passive software version.

software setpassive

Mark a file as passive software version. Only correctly uploaded software, valid for the **SpeedTouch™ Pro with Firewall** can be marked as passive software.

SYNTAX:

software setpassive file = <string>
--

file	the filename (without directory path) of the software package.	REQUIRED
-------------	--	----------

EXAMPLE:

```
=>Software version
Active : Sascha3.423          Passive : Bene3.420
=>Software deletepassive
=>Software version
Active : Sascha3.423          Passive :
.....
(FTP file transfer or upload via the SpeedTouch™ Pro with Firewall pages of new software
Sascha3.428)
.....
=>software setpassive file=Sascha3.722
=>Software version
Active : Sascha3.423          Passive : Sascha3.428
=>
```

RELATED COMMANDS:

software cleanup	Remove all unused files from the passive software subdirectory.
software deletepassive	Delete passive software.

software switch

Switch active and passive versions and reboot the **Speed Touch™ Pro with Firewall**.

Because rebooting implies a flush of all non-saved configurations it is highly recommended to save the current configuration if needed, e.g. by executing the **config save** command prior to executing a software switch.

SYNTAX:

```
software switch
```

EXAMPLE:

```
=>Software version
Active : Sascha3.423          Passive : Sascha3.428
=>software switch
.....
(after reboot and re-opening the Telnet session)
.....
=>Software version
Active : Sascha3.428          Passive : Sascha3.423
=>
```

RELATED COMMANDS:

software version

Show active and passive software versions.

system reboot

Reboot the **Speed Touch™ Pro with Firewall**.

software version

Show active and passive software versions.

SYNTAX:

```
software version
```

EXAMPLE:

```
=>Software version
Active  : Sascha3.428          Passive : Sascha3.423
=>
```

RELATED COMMANDS:

software switch

Switch active and passive software versions and reboot the **Speed Touch™ Pro with Firewall**.

16 SHDSL Commands

The shdsl command group is only applicable to the **Speed Touch™ Pro with Firewall** SHDSL variant, NOT to the **Speed Touch™ Pro with Firewall** ADSL variants.

shdsl (to access the SHDSL level)

shdsl info

shdsl load

shdsl psd

shdsl save

shdsl info

Show SHDSL statistics and information about the **SpeedTouch™ Pro with Firewall** status.

SYNTAX:

```
shdsl info
```

EXAMPLE:

```
=>shdsl info
WAN interface      : SHDSL
Line Status        : UP at 2304 kbit/s
Total bytes since power on:
    Downstream : 9932253      Upstream   : 244701
PSD mask           : Symmetric PSD mask for Europe
Shdsl uptime       : 47:55:28
SNR margin         : 7 dB
Attenuation        : 24 dB
Transmit Power     : 15 dBm
=>
```

shdsl load

Load saved (or default) SHDSL configuration.

SYNTAX:

shdsl load	[defaults = <{yes no}>]
-------------------	--------------------------------------

[defaults]	Load factory defaults (yes) or saved configuration (no). Not specifying this parameter loads the saved configuration	OPTIONAL
------------	---	----------

EXAMPLE:

```
=>shdsl load default=yes
=>shdsl info
WAN interface      : SHDSL
Line Status        : UP at 2304 kbit/s
Total bytes since power on:
    Downstream: 9932253      Upstream   : 244701
PSD mask           : Symmetric PSD mask for Europe
Shdsl uptime       : 0:0:21
SNR margin         : 7 dB
Attenuation        : 24 dB
Transmit Power     : 15 dBm
=>shdsl psd mask=asym_EU_2304
=>shdsl info
WAN interface      : SHDSL
Line Status        : DATA MODE
Total bytes since power on:
    Downstream: 0          Upstream   : 0
PSD mask           : Asymmetric PSD mask for 2304kbps (European)
Shdsl uptime       : 0:00:00
=>shdsl save
=>shdsl load defaults=yes
=>shdsl info
WAN interface      : SHDSL
Line Status        : UP at 2304 kbit/s
Total bytes since power on:
    Downstream: 895      Upstream   : 632
PSD mask           : Symmetric PSD mask for Europe
Shdsl uptime       : 00:00:15
SNR margin         : 7 dB
Attenuation        : 24 dB
Transmit Power     : 15 dBm
=>shdsl load defaults=no
=>shdsl info
WAN interface      : SHDSL
Line Status        : DATA MODE
Total bytes since power on:
    Downstream: 0          Upstream   : 0
PSD mask           : Asymmetric PSD mask for 2304kbps (European)
Shdsl uptime       : 0:00:00
=>
```

RELATED COMMANDS:

shdsl save	Save current SHDSL configuration.
-------------------	-----------------------------------

shdsl psd

Configure the PSD mask to be used, then restart the SHDSL line.

SYNTAX:

shdsl psd	mask = <{sym_NA sym_EU asym_NA_768 asym_NA_1536 asym_EU_2048 asym_EU_2304}>
------------------	--

mask The selected PSD mask must comply to the regional demands and to REQUIRED the required payload rate.
 Choose between:

- **sym_NA**
Symmetric PSD mask for North America
- **sym_EU**
Symmetric PSD mask for Europe
- **asym_NA_768**
Asymmetric PSD mask for 768kbps (North American)
- **asym_NA_1536**
Asymmetric PSD mask for 1536bps (North American)
- **asym_EU_2048**
Asymmetric PSD mask for 2048bps (European)
- **asym_EU_2304**
Asymmetric PSD mask for 2304bps (European)

EXAMPLE:

```
=>shdsl info
WAN interface      : SHDSL
Line Status        : UP at 2304 kbit/s
Total bytes since power on:
    Downstream : 9932253      Upstream   : 244701
PSD mask           : Symmetric PSD mask for Europe
Shdsl uptime       : 0:0:21
SNR margin         : 7 dB
Attenuation        : 24 dB
Transmit Power     : 15 dBm
=>shdsl psd mask=asym_EU_2304
=>shdsl info
WAN interface      : SHDSL
Line Status        : DATA MODE
Total bytes since power on:
    Downstream : 0          Upstream   : 0
PSD mask           : Asymmetric PSD mask for 2304kbps (European)
Shdsl uptime       : 0:00:00
=>
```

shdsl save

Save current SHDSL configuration.

SYNTAX:

shdsl save

EXAMPLE:

```
=>shdsl info
WAN interface      : SHDSL
Line Status        : UP at 2304 kbit/s
Total bytes since power on:
    Downstream: 9932253      Upstream   : 244701
PSD mask          : Symmetric PSD mask for Europe
Shdsl uptime      : 47:55:28
SNR margin        : 7 dB
Attenuation       : 24 dB
Transmit Power    : 15 dBm
=>shdsl psd mask=asym_EU_2304
=>shdsl info
WAN interface      : SHDSL
Line Status        : DATA MODE
Total bytes since power on:
    Downstream: 0      Upstream   : 0
PSD mask          : Asymmetric PSD mask for 2304kbps (European)
Shdsl uptime      : 0:00:00
=>shdsl save
=>shdsl flush
=>shdsl load defaults=yes
=>shdsl info
WAN interface      : SHDSL
Line Status        : UP at 2304 kbit/s
Total bytes since power on:
    Downstream: 895      Upstream   : 632
PSD mask          : Symmetric PSD mask for Europe
Shdsl uptime      : 00:00:15
SNR margin        : 7 dB
Attenuation       : 24 dB
Transmit Power    : 15 dBm
=>shdsl flush
=>shdsl load defaults=no
=>shdsl info
WAN interface      : SHDSL
Line Status        : DATA MODE
Total bytes since power on:
    Downstream: 0      Upstream   : 0
PSD mask          : Asymmetric PSD mask for 2304kbps (European)
Shdsl uptime      : 0:00:03
=>
```

RELATED COMMANDS:

shdsl load

Load saved (or default) SHDSL configuration.

17 System Commands

system (to access the System level)
system clearpassword
system flush
system load
system reboot
system save
system setpassword

system clearpassword

Clear current **SpeedTouch™ Pro with Firewall** system password.

To avoid unrestricted and unauthorized access to the **SpeedTouch™ Pro with Firewall** it is highly recommended always to make sure that it is protected by a **SpeedTouch™ Pro with Firewall** system password (by executing **system setpassword**) and to change the password regularly.

SYNTAX:

```
system clearpassword
```

EXAMPLE:

```
=>system clearpassword  
=>
```

RELATED COMMANDS:

system setpassword Set/change current system password.

system flush

Flush current **SpeedTouch™ Pro with Firewall** system configuration, i.e. the System password. The flush command does not impact previously saved configurations.

To avoid unrestricted and unauthorized access to the **SpeedTouch™ Pro with Firewall** it is highly recommended always to make sure that it is protected by a **SpeedTouch™ Pro with Firewall** system password (by executing **system setpassword**) and to change the password regularly.

SYNTAX:

```
system flush
```

EXAMPLE:

```
=>system flush  
=>
```

RELATED COMMANDS:

system load	Load saved or default system configuration.
system save	Save current system configuration.

system load

Load saved (or default) system configuration.

Execute **system flush** prior to **system load**.

In most cases loading the default system configuration causes the **SpeedTouch™ Pro with Firewall** system password to be CLEARED.

Therefore, to avoid unrestricted and unauthorized access to the **SpeedTouch™ Pro with Firewall** it is highly recommended always to make sure that it is protected by a **SpeedTouch™ Pro with Firewall** system password (by executing **system setpassword**) and to change the password regularly.

SYNTAX:

system load	[defaults = <yes no>]
--------------------	------------------------------------

[defaults]	Load factory defaults (yes) or saved configuration (no).	OPTIONAL
	Not specifying this parameter loads the saved configuration	

EXAMPLE:

=> system load defaults=no
=>

RELATED COMMANDS:

system flush	Flush complete system configuration.
system save	Save current system configuration.

system reboot

Reboot the **SpeedTouch™ Pro with Firewall**.

Because rebooting implies a flush of all non-saved configurations it is highly recommended to save the current configuration by executing **config save**.

To avoid unrestricted and unauthorized access to the **SpeedTouch™ Pro with Firewall** it is highly recommended always to make sure that it is protected by a **SpeedTouch™ Pro with Firewall** system password (by executing **system setpassword**) and to save it (by executing **system save**) prior to executing this command.

SYNTAX:

```
system reboot
```

EXAMPLE:

```
=>system reboot
.....
(lost session connectivity due to reboot)
.....
```

system save

Save current system configuration, i.e. the System password.

To avoid unrestricted and unauthorized access to the **SpeedTouch™ Pro with Firewall** it is highly recommended always to make sure that it is protected by a **SpeedTouch™ Pro with Firewall** system password (by executing **system setpassword**) and to save it (by executing **system save**) prior to executing this command.

SYNTAX:

```
system save
```

EXAMPLE:

```
=>system save  
=>
```

RELATED COMMANDS:

system load
system flush

Load saved or default system configuration.
Flush complete system configuration.

system setpassword

Set/change the current **SpeedTouch™ Pro with Firewall** system password.

To avoid unrestricted and unauthorized access to the **SpeedTouch™ Pro with Firewall** it is highly recommended always to make sure that it is protected by a **SpeedTouch™ Pro with Firewall** system password and to change it regularly.

SYNTAX:

system setpassword password = <string>

password A free to choose password <string>. The password is limited to a maximum of 15 characters. It is advised only to use characters from the ranges a–z, A–Z, 0–9. REQUIRED

EXAMPLE:

```
=>system setpassword password=Sascha  
=>system save  
=>system reboot
```

After reboot a telnet session is opened:

```
/home/doejohn{1}$ telnet 10.0.0.138
Trying 10.0.0.138...
Connected to 10.0.0.138.
Escape character is '^['.
User :
SpeedTouch (00-90-D0-00-01-23-45)
```

The logo consists of a stylized tree or hexagonal pattern formed by a series of connected lines and nodes. The text "Alcatel Speed Touch Pro with Firewall DSL Router Version R3.4" is positioned to the right of the central node, and "Copyright (c) 1999-2001 Alcatel" is at the bottom right.

18 TD Commands

td (to access this level)
td call

td call

Call a 'Trace & Debug' command. For qualified personnel only.

SYNTAX:

<i>td call</i>	<i>cmd = <string></i>	
<i>cmd</i>	The quoted trace & debug command string.	REQUIRED

Alcatel SpeedTouch™ Pro with Firewall

CLI Command Index

Index

A

add
 atmfc add, 24
 dhcp server add, 81
 dns add, 102
 phonebook add, 198

apadd, ip apadd, 150
 apdelete, ip apdelete, 152
 aplist, ip aplist, 153
 applist, nat applist, 182
 arpadd, ip arpadd, 154
 arpdelete, ip arpdelete, 155
 arplist, ip arplist, 156
 assign, firewall assign, 124
 autolist, phonebook autolist, 200

B

bind, nat bind, 183
 bindlist, nat bindlist, 184

C

call, td call, 254
 cleanup, software cleanup, 234
 clear
 dhcp client clear, 65
 dns clear, 103
 firewall rule clear, 139
 clearpassword, system clearpassword, 246
 client, dhcp server client, 82
 clrstats
 dhcp server clrstats, 83
 dns clrstats, 104
 config
 bridge config, 32
 dhcp client config, 66
 dhcp server config, 84
 ip config, 157

create

firewall chain create, 134
 firewall rule create, 140
 nat create, 185

D

defserver, nat defserver, 187
 delete
 atmfc delete, 25
 dhcp server delete, 86
 dns delete, 105
 firewall chain delete, 135
 firewall rule delete, 144
 nat delete, 188
 phonebook delete, 201

deletepassive, software deletepassive, 235
 disable, nat disable, 189
 domain, dns domain, 106

E

enable, nat enable, 190
 erase, config erase, 58

F

flush
 atmfc flush, 26
 bridge flush, 33
 cip flush, 48
 config flush, 59
 dhcp client flush, 67
 dhcp server flush, 87
 dns flush, 107
 firewall flush, 125
 firewall rule flush, 145
 ip flush, 160
 mer flush, 172
 nat flush, 191
 phonebook flush, 202
 ppp flush, 208
 pptp flush, 226
 system flush, 247

fwdadd, dns fwdadd, 108

fwddelete, dns fwddelete, 109

fwdlist, dns fwdlist, 110

fwdtable, dns fwdtable, 111

ifscan, ppp ifscan, 219

info

adsl info, 22
shdsl info, 240

H

help, 12

I

ifadd

bridge ifadd, 34

cip ifadd, 49

dhcp client ifadd, 68

mer ifadd, 173

ppp ifadd, 209

ifattach

bridge ifattach, 35

dhcp client ifattach, 69

mer ifattach, 174

ppp ifattach, 211

ifconfig

bridge ifconfig, 36

dhcp client ifconfig, 70

ip ifconfig, 161

mer ifconfig, 175

ppp ifconfig, 212

ifdelete

bridge ifdelete, 38

cip ifdelete, 50

dhcp client ifdelete, 72

mer ifdelete, 176

ppp ifdelete, 216

ifdetach

bridge ifdetach, 39

mer ifdetach, 177

ppp ifdetach, 217

iflist

bridge iflist, 40

cip iflist, 51

dhcp client iflist, 73

ip iflist, 162

mer iflist, 178

ppp iflist, 218

ifrelease, dhcp client ifrelease, 74

ifrenew, dhcp client ifrenew, 76

ifscan, ppp ifscan, 219
info
atmf info, 22
shdsl info, 240

L

list

atmf list, 27
dhcp server list, 88
dns list, 112
firewall chain list, 136
firewall list, 126
firewall rule list, 146
nat list, 192
phonebook list, 203
pptp list, 227

load

atmf load, 28
bridge load, 41
cip load, 52
config load, 60
dhcp client load, 78
dhcp server load, 89
dns load, 113
firewall chain load, 137
firewall load, 127
ip load, 163
mer load, 179
nat load, 193
phonebook load, 204
ppp load, 220
pptp load, 228
shdsl load, 241
system load, 248

M

macadd, bridge macadd, 42
macdelete, bridge macdelete, 43
maclist, bridge maclist, 44
match, firewall match, 128

N

nslookup, dns nslookup, 114

P

ping, ip ping, 164
 policy, dhcp server policy, 90
 profadd, pptp profadd, 229
 profdelete, pptp profdelete, 230
 proflist, pptp proflist, 231
 psd, shdsl psd, 242
 pvcadd, cip pvcadd, 53
 pvcdelete, cip pvcdelete, 54
 pvclist, cip pvclist, 55

R

reboot, system reboot, 249
 reset, config reset, 61
 rtadd
 ip rtadd, 165
 ppp rtadd, 221
 rtdelete
 ip rtdelete, 166
 ppp rtdelete, 223
 rtlist, ip rtlist, 167

S

save
 atmf save, 29
 bridge save, 45
 cip save, 56
 config save, 62
 dhcp client save, 79
 dhcp server save, 91
 dns save, 115
 firewall chain save, 138
 firewall save, 131
 ip save, 168
 mer save, 180
 nat save, 194
 phonebook save, 205
 ppp save, 224
 pptp save, 232
 shdsl save, 243
 system save, 250

sendto, ip sendto, 169
 setpassive, software setpassive, 236
 setpassword, system setpassword, 251
 spoof, dhcp server spoof, 92
 start
 dhcp server start, 94
 dns start, 116
 stats
 dhcp client stats, 80
 dhcp server stats, 95
 dns stats, 117
 firewall rule stats, 147
 status
 dhcp server status, 97
 dns status, 118
 stop
 dhcp server stop, 98
 dns stop, 119
 switch, software switch, 237

T

toutfwd, dns toutfwd, 120
 troff
 dhcp server troff, 99
 dns troff, 121
 tron
 dhcp server tron, 100
 dns tron, 122

U

unbind, nat unbind, 195

V

version, software version, 238

